

ACCUMETRIC INC -- ACCUMETRIC 210H FLUID -- 9150-00-480-7869

=====
Product Identification
=====

Product ID:ACCUMETRIC 210H FLUID

MSDS Date:06/18/1986

FSC:9150

NIIN:00-480-7869

MSDS Number: BJYXH

=== Responsible Party ===

Company Name:ACCUMETRIC INC

Address:350 RING RD

Box:843

City:ELIZABETHTOWN

State:KY

ZIP:42701

Country:US

Info Phone Num:502-769-3385

Emergency Phone Num:502-769-3385

Preparer's Nam

e:DEBBIE DUNN

CAGE:58149

=== Contractor Identification ===

Company Name:ACCUMETRIC INC

Address:350 RING RD

Box:843

City:ELIZABETHTOWN

State:KY

ZIP:42701

Country:US

Phone:502-769-3385

CAGE:58149

=====
Composition/Information on Ingredients
=====

Ingred Name:SILICONE FLUID

Other REC Limits:NONE SPECIFIED

=====
Hazards Identification
=====

Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES

Reports of Carcinogenicity:NTP:NO IARC:NO OSH

A:NO
Health Hazards Acute and Chronic:EYES/SKIN: PROLONGED CONTACT CAN CAUSE SLIGHT IRRITATION. GENERAL: LOW TOXICITY LEVEL ON CONTACT OR INGESTION.

Explanation of Carcinogenicity:NONE OF THE CHEMICALS IN THIS PRODUCT IS LISTED BY IARC, NTP OR OSHA AS A CARCINOGEN.

Effects of Overexposure:IRRITATION OF EYES/SKIN/RESPIRATORY TRACT.

Medical Cond Aggravated by Exposure:PERSONS WITH A HISTORY OF SKIN AND RESPIRATORY DISORDERS MAY BE AT INCREASED RISK FROM EXPOSURE.

=====
===== First Aid Measures =====

First Aid:EYE: IMMEDIATELY FLUSH WITH PLENTY OF WATER FOR 15 MINUTES. GET MEDICAL ATTENTION. SKIN: WASH WITH SOAP AND WATER. INHALATION: REMOVE TO FRESH AIR. INGESTION: MANUFACTURER REPORTS THAT NO FIRST AIR SH OULD BE NEEDED FOR SMALL ORAL AMOUNTS ACCIDENTALLY INGESTED.

===== Fire Fighting Measures =====

Flash Point Method:OC
Flash Point:>550F,>288C
Extinguishing Media:USE WATER FOG, CARBON DIOXIDE, FOAM, OR DRY CHEMICAL.

Fire Fighting Procedures:WEAR FIRE FIGHTING PROTECTIVE EQUIPMENT AND A FULL FACED SELF CONTAINED BREATHING APPARATUS. EVACUATE AREA. COOL FIRE EXPOSED CONTAINERS WITH WATER SPRAY.

Unusual Fire/Explosion Hazard:NONE KNOWN; COMBUSTION OR HEAT OF FIRE MAY PRODUCE HAZARDOUS DECOMPOSITION PRODUCTS AND VAPORS.

===== Accidental Release Measures =====

Spill Release Procedures:MOP OR WIPE UP SPILL WITH ABSORBENT MATERIAL.
Neutralizing Agent:NONE

===== Handling and Storage =====

Handling and Storage Precautions:STORE IN A COOL, DRY, WELL VENTILATED AREA AWAY FROM SOURCES OF IGNITION. KEEP CONTAINER CLOSED WHEN NOT IN USE. PROTECT FROM PHYSICAL DAMAGE.

Other Precautions:NONE SPECIFIED BY MANUFACTURER.

===== Exposure Controls/Personal Protection =====

Respiratory Protection:IF VENTILATION DOES NOT MAINTAIN INHALATION EXPOSURES BELOW PEL (TLV), USE NIOSH/MSH

A APPROVED RESPIRATOR AS
PER CURRENT 29 CFR 1910.134, INSTRUCTIONS/WARNINGS AND
NIOSH-RESPIRATOR SELECTION.

Ventilation:MECHANICAL (GENERAL) VENTILATION IS USUALLY ADEQUATE.

Protective Gloves:RUBBER OR PLASTIC GLOVES

Eye Protection:SAFETY GLASSES/CHEMICAL SPLASH GOGGLES

Other Protective Equipment:NONE SPECIFIED BY MANUFACTURER.

Work Hygienic Practices:WASH AT MEALTIME AND END OF SHIFT. AVOID DIRECT
CONTACT WITH MATERIAL.

Supplemental Safety and Health
USE REASONABLE CARE AND CAUTION.

===== Physical/Chemical Properties =====

HCC:V6

Boiling Pt:B.P. Text:>600F,>316C

Vapor Pres: