

DOWELL SCHLUMBERGER -- VERTAN 650 CHELANT V650 -- 5840-00-839-1236

=====
Product Identification
=====

Product ID:VERTAN 650 CHELANT V650

MSDS Date:10/31/1988

FSC:5840

NIIN:00-839-1236

MSDS Number: BJZDT

=== Responsible Party ===

Company Name:DOWELL SCHLUMBERGER

Address:P. O. BOX 2710

Box:2710

City:TULSA

State:OK

ZIP:74101

Country:US

Emergency Phone Num:918-582-0104

Preparer's Name:W. W. SHEPHERD

C

AGE:FO294

=== Contractor Identification ===

Company Name:DOW CHEMICAL U.S.A.

City:MIDLAND

State:MI

ZIP:48674

Country:US

Phone:517-636-4400

CAGE:71983

Company Name:DOWELL SCHLUMBERGER

Box:21

City:TULSA

State:OK

ZIP:74102

Phone:(918) 582-0104

CAGE:FO294

=====
Composition/Information on Ingredients
=====

Ingred Name:TRISODIUM NITRILOTRIACETATE

CAS:5064-31-3

RTECS #:MB8400000

Fraction by Wt: 200F,>93C

Extinguishing Media:USE WATER FOG, CARBON DIOXIDE, FOAM, OR DRY
CHEMICAL.

F

Fire Fighting Procedures:WEAR FIRE FIGHTING PROTECTIVE EQUIPMENT AND A FULL FACED SELF CONTAINED BREATHING APPARATUS. EVACUATE AREA. COOL FIRE EXPOSED CONTAINERS WITH WATER SPRAY.

Unusual Fire/Explosion Hazard:COMBUSTION OR HEAT OF FIRE MAY PRODUCE HAZARDOUS DECOMPOSITION PRODUCTS AND VAPORS.

===== Accidental Release Measures =====

Spill Release Procedures:CONTAIN SPILL WITH DIKES AND VACUUM RECOVER TO A SEPTIC TANK TRUCK OR PUT IN STEEL OR PLASTIC DR

UMS. DO NOT ALLOW

RUNOFF TO A SEWER UNLESS MATERIAL IS DILUTED AND NEUTRALIZED WITH DILUTE ACID SOLUTION . FLUSH RESIDUAL WITH PLENTY OF WATER.

Neutralizing Agent:5% ACETIC ACID (VINEGAR)

===== Handling and Storage =====

Handling and Storage Precautions:STORE IN A COOL, VENTILATED WORK AREA. KEEP CONTAINERS CLOSED WHEN NOT IN USE. MATERIAL WILL CORRODE ALUMINUM.

Other Precautions:SPILLAGE CAN BE SLIPPERY. IF DILUTING OR DISSOLVING THIS PR

ODUCT, ALWAYS ADD THIS PRODUCT TO WATER SLOWLY AND WITH CONSTANT STIRRING.

===== Exposure Controls/Personal Protection =====

Respiratory Protection:NOT NORMALLY REQUIRED. USE NIOSH/MSHA APPROVED RESPIRATOR FOR HANDLING MIST IF PROLONGED CONTACT WITH MATERIAL.

Ventilation:ADEQUATE ROOM VENTILATION SUFFICIENT TO MEET TLV.

Protective Gloves:IMPERVIOUS PLASTIC OR RUBBER GLOVES

Eye Protection:CHEMICAL SAFETY GOGGLES WITH SIDE SHIELD

Other Protective Equipment:EYE WASH AND

SHOWER. APRON AND FULL RUBBER

BOOTS RECOMMENDED. NOT WEAR THIN RUBBER COVERS OVER LEATHER SHOES.

Work Hygienic Practices:DO NOT TAKE INTERNALLY. AVOID SKIN CONTACT.

WASH SKIN AFTER USING PRODUCT. DO NOT EAT, DRINK OR SMOKE IN WORK AREA.

Supplemental Safety and Health

CORROSIVE LIQUID - AVOID CONTACT. DO NOT STORE IN CONTACT WITH ALUMINUM. LEAVE LABEL ON DRUM AT ALL TIMES.

===== Physical/Chemical Properties =====

HCC:B3

Boiling Pt:B.P. Text:223F,106

C

Spec Gravity:1.31

pH:11-12

Solubility in Water:100%

Appearance and Odor:LIGHT STRAW COLORED LIQUID; FAINT ODOR

Percent Volatiles by Volume:>30

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES

STRONG OXIDIZING AGENTS, ALUMINUM (MAY RELEASE HYDROGEN GAS IN CONTACT WITH ALUMINUM)

Stability Condition to Avoid:HIGH HEAT, OPEN FLAMES AND OTHER SOURCES OF IGNITION

Hazardous Decomposition Products:LIBERATES FLAMMABLE HYDROGEN GAS ON

CONTACT WITH ACTIVE METALS SUCH AS ZN,AL,SN. CAN ALSO GENERATE CARBON MONOXIDE.

===== Disposal Considerations =====

Waste Disposal Methods:WASTE DILUTED AND NEUTRALIZED LIQUID COULD BE FLUSHED TO A WASTE WATER TREATMENT SYSTEM VIA THE SEWER OR GIVEN TO A LICENSED DISPOSAL CONTRACTOR. CONFORM TO ALL APPLICABLE REGULATIONS.

Disclaimer (provided with this information by the compiling agencies):

This information is formulated for use by ele

ments of the Department

of Defense. The United States of America in no manner whatsoever,

expressly or implied, warrants this information to be accurate and

disclaims all liability for its use. Any person utilizing this

document should seek competent professional advice to verify and

assume responsibility for the suitability of this information to their

particular situation.