

FURANE PRODUCTS COMPANY -- URALANE 5753 A -- 8030-01-097-9102

=====
Product Identification
=====

Product ID:URALANE 5753 A

MSDS Date:03/06/1987

FSC:8030

NIIN:01-097-9102

Kit Part:Y

MSDS Number: BJZKJ

=== Responsible Party ===

Company Name:FURANE PRODUCTS COMPANY

Address:5121 SAN FERNANDO ROAD WEST

City:LOS ANGELES

State:CA

ZIP:90039

Country:US

Info Phone Num:818-247-6210

Emergency Phone Num:818-24

7-6210

CAGE:OO131

=== Contractor Identification ===

Company Name:CIBA-GEIGY COMPANY, FURANE PRODUCTS

Address:5121 SAN FERNANDO ROAD WEST

Box:City:LOS ANGELES

State:CA

ZIP:90039

Country:US

Phone:818-247-6210 OR 800-334-9481

CAGE:0EJE3

Company Name:FURANE PRODUCTS COMPANY

Phone:(201) 499-2401

CAGE:OO131

=====
Composition/Information on Ingredients
=====

Ingred Name:METHYLENE BISPHENYL ISOCYANATE (MDI) (SARA III)

CAS:101-68-8

RTECS #:NQ9350000

Fraction by Wt: 80%

Other REC Limi

ts:NONE SPECIFIED
OSHA PEL:C, 0.02 PPM
ACGIH TLV:0.005 PPM; 9192
EPA Rpt Qty:1 LB
DOT Rpt Qty:1 LB

Ingred Name:HIGHER MOLECULAR WEIGHT POLYMERS OF MDI
Fraction by Wt: 20%
Other REC Limits:NONE SPECIFIED

=====
===== Hazards Identification =====

Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES
Effects of Overexposure:INHALED:SEVERE IRRIT OF RESPIRATORY TRACT &
MUCOUS MEMBRANES,TIGHTNESS OF THE CHEST,SHORTNESS OF
BREATH,COUGHING & HEADACHES.BRONCHITIS
& PULMONARY EDEMA MAY
DEVELOP.RESPIRATORY SENSITIZER:CAUSES ALLERGIC RESPIRATORY
REACTION WITH ASTHMA LIKE ATTACKS.SYMPTOMS MAY BE
DELAYED.EYE:IRRIT.POSSIBLE EYE DAMAGE.SKIN:IRRITATION

=====
===== First Aid Measures =====

First Aid:INHALED:MOVE TO FRESH AIR. GIVE OXYGEN IF BREATHING
DIFFICULT, ARTIFICIAL RESPIRATION IF STOPPED. EYES:FLUSH WITH
PLENTY OF WATER FOR 15 MINUTES AND GET PROMPT MEDICAL ATTENTION.
SKIN:WASH THOROUGHLY WITH SOAP
AND WATER, REMOVE AND WASH CLOTHING
BEFORE REUSE. INGESTION:IF SWALLOWED DILUTE BY GIVING 2 GLASSES OF
WATER TO DRINK. SEE A PHYSICIAN. NEVER GIVE ANYTHING BY MOUTH TO AN
UNCONSCIOUS PERSON.

=====
===== Fire Fighting Measures =====

Flash Point Method:PMCC
Flash Point:349F,176C
Extinguishing Media:CO2, DRY CHEMICAL
Fire Fighting Procedures:WEAR BREATHING APPARATUS (MSHA/NIOSH
APPROVED,PRESSURE DEMAND,SELF CONTAINED OR EQUIVALENT) AND FULL
PROTEC

TIVE GEAR. KEEP WATER OUT OF CONTAINERS.

Unusual Fire/Explosion Hazard:REACTS WITH WATER TO FORM CARBON DIOXIDE.

AVOID BREATHING VAPORS OF FIRE EXPOSED MATERIAL.

===== Accidental Release Measures =====

Spill Release Procedures:WEAR PROT EQUIP.VENTILATE.AVOID BREATHING VAPOR.SCBA FOR LARGE SPILLS IN CONFINED AREAS.DIKE/ABSORB SPILL W/INERT MAT'L.SWEEP UP/PLACE IN CONTAINER FOR DISPOSAL.REMOVE CONTAM CLOTHES PROMPTLY/WASH EXP OSED SKIN W/SOAP/WATER.KEEP SPILL

OUT OF SEWER/H2O

Neutralizing Agent:90% WATER, 8% AMMONIUM HYDIOXIDE, 2% DETERGENT

===== Handling and Storage =====

Handling and Storage Precautions:STORE INDOORS IN A COOL, DRY AREA WITH ADEQUATE VENTILATION. USE INERT GAS BLANKETING FOR BULK STORAGE. MAX STORAGE TEMPERATURE IS 37C. MIN IS 23C.

===== Exposure Controls/Personal Protection =====

Respiratory Protection:WEAR SUITABLE MSHA/NIOSH APPROVED RESPIRATOR
WHER

E EXPOSURE LIMITS ARE EXCEEDED.

Ventilation:MECHANICAL LOCAL EXHUAST AT POINT OF CONTAMINANT RELEASE.

Protective Gloves:IMPERVIOUS (LATEX)

Eye Protection:CHEMICAL SPLASH GOGGLES (ANSI Z-87.1)

Other Protective Equipment:EYEWASH FACILITY, SAFETY SHOWER AND PROTECTIVE CLOTHING.

Supplemental Safety and Health

===== Physical/Chemical Properties =====

Boiling Pt:B.P. Text:392F,200C

Vapor Pres:0.0003@25C

Vapor Density:8.6

Spec Gravity:1.24

Viscosity:50 CPS

Evaporation

Rate & Reference:< 1 (BUTYL ACETATE=1)

Solubility in Water:REACT WITH WATER

Appearance and Odor:YELLOW COLOR CLEAR LIQUID; CHARACTERISTIC ODOR

Percent Volatiles by Volume:NIL

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES

WATER, STRONG BASES, ALCOHOLS AND METAL COMPOUNDS.

Stability Condition to Avoid:AVOID PROLONG HEATING OVER 50C OR STORAGE BELOW 23C.

Hazardous Decomposition Products:CARBON MONOXIDE AND/OR CARBON DIOXIDE, OXIDES OF NITROGEN, TRACES OF HCN.

Conditions to Avoid Polymerization:CONTACT WITH WATER OR OTHER REACTIVE MATERIALS.

===== Disposal Considerations =====

Waste Disposal Methods:DILUTE WITH SUITABLE FLAMMABLE SOLVENT, THEN INCINERATE IN APPROVED EQUIPMENT. DECONTAMINATE DIKING MATERIAL WITH DECONTAMINANT LIQUID, THEN LANDFILL IN ACCORDANCE WITH LOCAL, STATE AND FEDERAL REGULATIONS.

Disclaimer (provided with this information by the compiling agencies):

This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.