

DOW CORNING CORP -- MOLYKOTE(R) 44 GREASE-MIL-L-15719A -- 9150-01-041-6648
===== Product Identification =====

Product ID:MOLYKOTE(R) 44 GREASE-MIL-L-15719A

MSDS Date:09/27/1985

FSC:9150

NIIN:01-041-6648

Kit Part:Y

MSDS Number: BJZXT

=== Responsible Party ===

Company Name:DOW CORNING CORP

Address:3901 SOUTH SAGINAW ROAD

Box:997

City:MIDLAND

State:MI

ZIP:48686

Country:US

Info Phone Num:517-496-6000

Emergency Phone Num:517-496-5900

Preparer's Name:JACK SHENEBERGER

CAGE:5D028

=== Contractor Identification ===

Company Name:DOW CORNING CORP

Address:3901 S SAGINAW RD

Box:997

City:MIDLAND

State:MI

ZIP:48686-0997

Country:US

Phone:517-496-6000/517-496-6315

CAGE:5D028

Company Name:DOW CORNING CORP

Address:2200 W SALZBURG RD

Box:City:AUBURN

State:MI

ZIP:48611

Country:US

Phone:517-496-4388

CAGE:71984

Company Name:PENN DETROIT DIESEL ALLISON INC

Address:SIPE ROAD

Box:RD 1

City:YORK HAVEN

State:PA

ZIP:

17370-9785
Country:US
Phone:717-938-5141
CAGE:62860

===== Composition/Information on Ingredients =====

Ingred Name:NON-HAZARDOUS INGREDIENTS
Fraction by Wt: 100%
Other REC Limits:NONE RECOMMENDED

===== Hazards Identification =====

LD50 LC50 Mixture:NONE SPECIFIED BY MANUFACTURER.
Routes of Entry: Inhalation:YES Skin:NO Ingestion:NO
Health Hazards Acute and Chronic:EYE: MAY CAUSE TEMPORARY DISCOMFORT.
SKIN: SINGLE, PRLNG EXPOS (HRS) CA
USES NO EFFECT. SEV RPTD, PRLNG
EXPOS MAY CAUSE SLIGHT IRRIT. INHAL: NO IRRIT TO NOSE/THROAT
EXPECTED. NO INJURY IS LIKELY FROM R ELATIVELY SHORT EXPOS. ORAL:
AMTS TRANSFERRED TO MOUTH BY FINGERS, ETC., DURING NORMAL
OPERATIONS (SEE EFTS OF OVEREXP)
Explanation of Carcinogenicity:NONE SPECIFIED BY MANUFACTURER.
Effects of Overexposure:HLTH HAZ: SHOULD NOT CAUSE INJURY. NO KNOWN
ADVERSE CHRONIC HEALTH EFFECTS, BUT UNNECESSARY EXPOS TO ANY
CHEMICAL SHOULD BE AVOIDED. THIS P
ROD, AS WITH ANY CHEM, MAY
ENHANCE ALLERGIC CONDITIONS ON CER TAIN PEOPLE. WE DO NOT KNOW OF
ANY MEDICAL CONDITIONS THAT MIGHT BE AGGRAVATED BY EXPOSURE TO THIS
PRODUCT.
Medical Cond Aggravated by Exposure:NONE SPECIFIED BY MANUFACTURER.

===== First Aid Measures =====

First Aid:EYES: FLUSH WITH WATER FOR AT LEAST 15 MINUTES. SKIN: WIPE
OFF AND FLUSH WITH WATER. INHAL: NO PROBLEM. ORAL: NO PROBLEM.

===== Fire Fighting Measures =====

Flash Point Method:OC
Flash Point:250F,121C
Extinguishing Media:WATER FOG, CO2, DRY CHEMICAL, FOAM & OTHER.
Fire Fighting Procedures:USE NIOSH/MSHA APPROVED SCBA AND FULL PROT
EQUIP .
Unusual Fire/Explosion Hazard:NONE KNOWN TO DOW CORNING.

===== Accidental Release Measures =====

Spill Release Procedures:REMOVE PRODUCT AND USE ABSORBENT MATERIAL TO
TAKE CARE OF ANY OIL-LIKE RESIDUES.
Neutralizing Agent:NONE SPECIFIED BY MANUFACTUR

ER.

===== Handling and Storage =====

Handling and Storage Precautions:USE REASONABLE CARE AND CAUTION.

Other Precautions:THE FOLLOWING PREC ARE FOR ROOM TEMP HANDLING, USE AT ELEVATED TEMPS, OR AEROSOL/SPRAY APPLICATNS, MAY REQUIRE ADDED PREC.

===== Exposure Controls/Personal Protection =====

Respiratory Protection:NONE SHOULD BE NEEDED. USE NIOSH/MSHA APPROVED RESPIRATOR APPROPRIATE FOR EXPOSURE OF CONCERN .

Ventilation:LOCAL

EXHAUST: NONE. MECHANICAL (GENERAL): RECOMMENDED.

Protective Gloves:NONE SPECIFIED BY MANUFACTURER.

Eye Protection:CHEMICAL WORKERS GOGGLES .

Other Protective Equipment:NONE SPECIFIED BY MANUFACTURER.

Work Hygienic Practices:GOOD PRACTICE REQ THAT GROSS AMT OF ANY CHEM BE REMOVED FROM SKIN AS SOON AS POSSIBLE, ESPECIALLY BEFORE EATING/SMOKING.

Supplemental Safety and Health

NONE SPECIFIED BY MANUFACTURER.

===== Physical/Chemical Properties =====

HCC:V6

Boili

ng Pt:B.P. Text:>300F,>149C

Vapor Pres: