

SOUTH COAST TERMINALS INC -- SCT SF/CD MOTOR OIL SAE 30 (WS234) -- 9150-00-186-6681
===== Product Identification =====

Product ID:SCT SF/CD MOTOR OIL SAE 30 (WS234)

MSDS Date:03/05/1990

FSC:9150

NIIN:00-186-6681

MSDS Number: BKBJQ

=== Responsible Party ===

Company Name:SOUTH COAST TERMINALS INC

Address:7401 WALLISVILLE RD

Box:15535

City:HOUSTON

State:TX

ZIP:77020-3555

Country:US

Info Phone Num:71

3-672-2401 EXT 232

Emergency Phone Num:713-672-2401-232/800-424-9300(CHEM

Preparer's Name:DOD-HMIS/DGSC-SSH

CAGE:1L506

=== Contractor Identification ===

Company Name:CHEMICAL SPECIALISTS AND DEVELOPMENT INC

Address:2210 HACKBERRY LN

Box:687

City:CONROE

State:TX

ZIP:77305

Country:US

Phone:409-756-1065

CAGE:4N760

Company Name:SOUTH COAST TERMINALS, INC

Address:7401 WALLISVILLE ROAD

Box:15535

City:HOUSTON

State:TX

ZIP:77020

Country:US

Phone:713-672-2401/800-424-9300(CHEMTREC)

CAGE:1L506

=====

==== Composition/Information on Ingredients =====

Ingred Name:PETROLEUM OIL/BASE OIL/LUBRICATING OIL BASESTOCK
CAS:8002-05-9
RTECS #:SE7175000
Fraction by Wt: 80-90%
Other REC Limits:NONE SPECIFIED
OSHA PEL:5 MG/M3 (OIL MIST)
ACGIH TLV:5 MG/M3 (OIL MIST)

Ingred Name:PHOSPHORODITHIOIC ACID, ZINC SALT
RTECS #:TD5110000
Other REC Limits:NONE SPECIFIED

Ingred Name:ADE SECRETS ARE EXCLUDED FROM THE MSDS LIST.
RTECS #:9999999ZZ
Other REC Limits:NONE SPECIFIED

==== Hazard
Identification =====

Routes of Entry: Inhalation:NO Skin:YES Ingestion:NO
Health Hazards Acute and
Chronic:ACUTE-EYE:IRRITATION.SKIN:IRRITATION.INHALE:EXPOSURE TO
HEATED MIST/VAPOR MAY CAUSE
IRRITATION.INGESTION:IRRITATION.CHRONIC-SKIN:DERMATITIS.
Effects of Overexposure:EYE:DIRECT CONTACT MAY CAUSE BURNING,TEARING,
AND REDNESS.SKIN:REDNESS AND BURNING.INHALATION:IRRITATION TO NOSE
AN THROAT.INGESTION:IRRITATION TO THE DIGESTIVE TRACT.
Medical Cond Aggravated by Exposure:PERSONS WITH A HISTORY OF AILMENTS

==== First Aid Measures =====

First Aid:EYE:FLUSH WITH CLEAN WATER.IF IRRITATION/REDNESS PERSISTS,SEE
A DOCTOR.SKIN:WASH WITH SOAP & WATER.IF IRRITATION PERSISTS, SEE A
PHYSICIAN.INHALATION:MOVE TO FRESH AIR.IF IRRITATIO PERSISTS, SEE A
DOC TOR.INGESTION:DON'T INDUCE VOMITING.CALL A PHYSICIAN.

==== Fire Fighting Measures =====

Flash Point:200C(MIN)
Extingu

ishing Media:WATER FOG, CARBON DIOXIDE, FOAM, DRY CHEMICAL, SAND OR EARTH. WATER AND FOAM MAY CAUSE FROTHING.

Fire Fighting Procedures:RESPIRATORY PROTECTION AND EYE PROTECTION REQUIRED FOR FIRE FIGHTING PERSONNEL.

Unusual Fire/Explosion Hazard:NONE

===== Accidental Release Measures =====

Spill Release Procedures:TREAT AS AN OIL SPILL. CONTAIN AND REMOVE BY MECHANICAL MEANS.

Neutralizing Agent:NOT APPLICABLE.

===== Handling and Storage

=====

Handling and Storage Precautions:NONE NORMALLY REQUIRED.

Other Precautions:NONE

===== Exposure Controls/Personal Protection =====

Respiratory Protection:NONE NORMALLY REQUIRED.

Ventilation:MECHANICAL (GENERAL) ROOM VENTILATION IS NORMALLY ADEQUATE.

Protective Gloves:NEOPRENE, NITRILE, PVC OR NATURAL RUBBER

Eye Protection:SAFETY GOGGLES WITH OPTIONAL FACE SHIELD

Other Protective Equipment:NONE

Work Hygienic Practices:OBSERVE GOOD PERSONAL HYGIENE PRACTICES AND

RECOMMENDED PROCEDURES. DO NOT WEAR CONTAMINATED CLOTHING OR FOOTWEAR.

Supplemental Safety and Health

VENDOR CSD, INC. CLAIMED TO HAVE SUPPLIED THIS PRODUCT TO CONTRACE DLA400-86-C-5097 BUT TO HAVE NO COPIES OF THE MSDS. THUS THE MSDS COPIED FROM NSN FOR 5 GALLONS, SAMD MFR SAMD SPEC.

===== Physical/Chemical Properties =====

HCC:V6

Boiling Pt:B.P. Text:>500F,>260C

Vapor Pres:1

Spec Gravity:.87-.88

pH:7

Evaporation Rate & Reference: