

EASTMAN KODAK COMPANY -- 1230432 KODAK EKTACOLOR RA DEVELOPER REPLENISHER, 25 GAL -- 6750-01-354-1029

=====
===== Product Identification =====

Product ID:1230432 KODAK EKTACOLOR RA DEVELOPER REPLENISHER, 25 GAL

MSDS Date:03/02/1987

FSC:6750

NIIN:01-354-1029

MSDS Number: BKGTL

=== Responsible Party ===

Company Name:EASTMAN KODAK COMPANY

Address:343 STATE STREET

City:ROCHESTER

State:NY

ZIP:14650

Info Phon

e Num:(716) 722-5151

Emergency Phone Num:(716) 722-5151

CAGE:19139

=== Contractor Identification ===

Company Name:EASTMAN KODAK CO GOVERNMENT MARKETS CONTRACTS

Address:343 STATE ST

Box:City:ROCHESTER

State:NY

ZIP:14650-1115

Country:US

Phone:716-722-5151/(800) 242-2424

CAGE:19139

=====
===== Composition/Information on Ingredients =====

Ingred Name:WATER, H2O

CAS:7732-18-5

RTECS #:ZC0110000

Fraction by Wt: 55-60%

Ingred Name:TRIETHANOLAMINE

INTENDED CHANGE (IC)

CAS:1

02-71-6
RTECS #:KL9275000
Fraction by Wt: 20-25%
Other REC Limits:A2 CARCINOGEN
ACGIH TLV:3.1 MG/CUM IC

Ingred Name:N,N-DIETHYLHYDROXYLAMINE
CAS:3710-84-7
RTECS #:NC3500000
Fraction by Wt: 10-15%

Ingred Name:STILBENE
CAS:588-59-0
RTECS #:WJ4925000
Fraction by Wt: 5-10%

=====
===== Hazards Identification =====

LD50 LC50 Mixture:ORAL LD50 (RAT): 5 G/KG
Routes of Entry: Inhalation:NO Skin:YES Ingestion:YES
Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO
Health
Hazards Acute and Chronic:EYES/SKIN/INGESTION: IRRITATION. LOW
HAZARD.
Explanation of Carcinogenicity:TRIETHANOLAMINE IS A SUSPECTED A2
CARCINOGEN BY ACGIH.
Effects of Overexposure:EYES/SKIN/INGESTION: IRRITATION.

=====
===== First Aid Measures =====

First Aid:EYES/SKIN: FLUSH W/PLENTY OF WATER. INGESTION: DRINK 1-2
GLASSES OF WATER. OBTAIN MEDICAL ATTENTION IN ALL CASES.

=====
===== Fire Fighting Measures =====

Flash Po
int:NONE
Extinguishing Media:WATER SPRAY, DRY CHEMICAL, OR CO2
Fire Fighting Procedures:WEAR SELF-CONTAINED BREATHING APPARATUS & FULL
PROTECTIVE CLOTHING.

=====
===== Accidental Release Measures =====

Spill Release Procedures:FLUSH MATERIAL TO SEWER W/LARGE AMOUNTS OF
WATER.

=====
===== Handling and Storage =====

Handling and Storage Precautions:KEEP FROM CONTACT W/OXIDIZING
MATERIALS. KEEP CONTAINER TIGHTLY CLOSED & AWAY FROM S

TRONG ACIDS.

===== Exposure Controls/Personal Protection =====

Respiratory Protection:NEEDED IN SPECIAL CIRCUMSTANCES.

Ventilation:GOOD VENTILATION SHOULD BE SUFFICIENT AT 10 ROOM VOLUMES PERHOUR.

Eye Protection:SAFETY GLASSES

Supplemental Safety and Health

===== Physical/Chemical Properties =====

Boiling Pt:B.P. Text:>212F

Vapor Pres:18

Vapor Density:0.6

Spec Gravity:1.065

pH:10.4

Solubility in Water:COMPLETE

Appearance and Odor:YELLOW LIQUI

D W/STRONG AMINE ODOR.

Percent Volatiles by Volume:90%/WT

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES

STRONG OXIDIZERS OR ACIDS

Stability Condition to Avoid:EXCESSIVE HEAT OR FIRE

Hazardous Decomposition Products:CO₂, CO, OR OXIDES OF NITROGEN

===== Disposal Considerations =====

Waste Disposal Methods:DISCHARGE, TREATMENT, OR DISPOSAL MAY BE SUBJECT TO FEDERAL, STATE, OR LOCAL LAWS.

Discl

claimer (provided with this information by the compiling agencies):

This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.