View NSN Online: https://aerobasegroup.ae/nsn/3439-00-246-0564 J.W. HARRIS CO., INC. -- AWSA5.2-80 RG60 0.062 STEEL-OXY FUEL WELDING ROD 3439-00-246-0564 Product ID:AWSA5.2-80 RG60 0.062 STEEL-OXY FUEL WELDING ROD MSDS Date:11/01/1985 FSC:3439 NIIN:00-246-0564 MSDS Number: BKHJR === Responsible Party === Company Name: J.W. HARRIS CO., INC. Address:10930 DEERFIELD ROAD City:CINCINNATI State:OH ZIP:45242 Info Phone Num:(513) 891-2000 Emergency Phone Num: (513) 891-2000 CAGE:27911 === Contractor Identification === Company Name: J. W. HARRIS CO INC & HARRIS WELCO, DIVISION/J.W. HARRIS CO Address:1051 YORK RD Box:City:KINGS MOUNTAIN State:NC ZIP:28086 Country:US Phone:704-739-6421 CAGE:34920 Company Name: J. W. HARRIS CO., INC. Address:10930 DEERFIELD ROAD Box:City:CINCINNATI

Phone:513-891-2000 CAGE:27911

Ingred

State:OH

ZIP:45242-4110 Country:US

Name:SULFUR CAS:7704-34-9 RTECS #:WS4250000 Fraction by Wt: 0.022%

Ingred Name:MANGANESE (SARA III) CAS:7439-96-5 RTECS #:OO9275000 Fraction by Wt: 0.94% OSHA PEL:(C) 5 MG/M3 DUST ACGIH TLV:5 MG/M3 DUST 9293

Ingred Name:PHOSPHOROUS (YELLOW) (SARA III) CAS:7723-14-0 RTECS #:TH3500000 Fraction by Wt: 0.010% Other REC Limits:100 UG/CUM OSHA PEL:0.1 MG/M3 ACGIH TLV:0.1 MG/M3; 9192 EPA Rpt Qty:1 LB DOT Rpt Qty:1 LB

Ingred Name:IRON CAS:7439-89-6 RTECS #:NO4565500 Fraction by Wt: BALANCE

Ingred Name:IRON OXIDE CAS:1309-37-1 RTECS #:NO7400000 OSHA PEL:10 MG/M3 (FE) ACGIH TLV:5 MG/M3(FE),B2; 9293

Routes of Entry: Inhalation:YES Skin:YES Ingestion:NO Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO Health Hazards Acute and Chronic:INHALATION: DISCOMFORT, DIZZINESS, NAUSEA, DRYNESS, IRRITATION OF THE THROAT, PULMONARY IRRITATION, PNEUMOCONIOSIS, & SIDEROSIS. EYE: INJURY. SKIN: BURN. Explanation of Carcinog

enicity:NONE Effects of Overexposure:INHALATION: DISCOMFORT, DIZZINESS, NAUSEA, DRYNESS, IRRITATION OF THE THROAT, PULMONARY IRRITATION, PNEUMOCONIOSIS, SIDEROSIS. EYE: INJURY. SKIN: BURN. Medical Cond Aggravated by Exposure:IMPAIRED PULMONARY FUNCTIONS OR ILLNESS.
======================================
First Aid:INHALATION: REMOVE TO FRESH AIR. GIVE CPR IF NEEDED. EYES/SKIN: FLUSH W/WATER. OBTAIN MEDICAL ATTENTION IN ALL CASES.
======================================
Flash Point:NON-FLAMMABLE Unusual Fire/Explosion Hazard:WELDING ARC, OPEN FLAME, & SPARKS CAN IGNITE COMBUSTIBLES.
======================================
Handling and Storage Precautions:TRAIN THE EMPLOYEE NOT TO TOUCH ELECTRICAL PARTS & TO INSULATE HIMSELF FROM WORK & GROUND. ELECTRIC SHOCK FROM ARC WELDING EQUIPMENT CAN KILL. Other Precautions:TO DETERMINE THE COMPOSITION & QUANTITY OF FUMES/GASE
S TO WHICH WORKERS ARE EXPOSED IS TO TAKE AN AIR SAMPLE FROM INSIDE THE WELDER'S HELMET IF WORN OR IN THE WORKER'S BREATHING ZONE. TRAIN THE EMPLOY EE TO KEEP HIS HEAD OUT OF THE FUMES.

====== Exposure Controls/Personal Protection =========

Respiratory Protection:USE A RESPIRABLE FUME RESPIRATOR OR AIR SUPPLIED RESPIRATOR WHEN WELDING, BRAZING, OR SOLDERING IN A CONFINED SPACE OR WHERE LOCAL EXHAUST OR VENTILATION DOES NOT KEEP EXPOSURE