

PRATT AND LAMBERT INC -- LACQUER SPRAYING RED 11105 -- 8010-00-577-4524
===== Product Identification =====

Product ID:LACQUER SPRAYING RED 11105

MSDS Date:03/11/1991

FSC:8010

NIIN:00-577-4524

MSDS Number: BKJLW

=== Responsible Party ===

Company Name:PRATT AND LAMBERT INC

Address:16116 E 13TH ST

Box:2153

City:WICHITA

State:KS

ZIP:67201

Country:US

Info Phone Num:316-733-1361

Emergency Phone Num:716

-873-6000

Preparer's Name:W. A. ELLISON

CAGE:61196

=== Contractor Identification ===

Company Name:PRATT AND LAMBERT INC

Box:6027

City:CLEVELAND

State:OH

ZIP:44101-1027

Country:US

Phone:216-566-2902

CAGE:61196

===== Composition/Information on Ingredients =====

Ingred Name:VM&P NAPHTHA (VAPOR PRESSURE 40 MM HG @ 20 C) (LFL 1.0; UFL
6.0) (SOLVENT)

CAS:8030-30-6

RTECS #:DE3030000

Fraction by Wt: 5%

Other REC Limits:NONE SPECIFIED

OSHA PEL:300 PPM;400 PPM STEL

ACGIH TLV:300 PP

M; 1350 MG/M3

Ingred Name:ISOBUTYL ALCOHOL (VAPOR PRESSURE 10 MM HG @ 20 C) (LFL 1.0; UFL 11.0) (SOLVENT)

CAS:78-83-1

RTECS #:NS1752000

Fraction by Wt: 5%

Other REC Limits:NONE SPECIFIED

OSHA PEL:100 PPM

ACGIH TLV:50 PPM; 9293

EPA Rpt Qty:5000 LBS

DOT Rpt Qty:5000 LBS

Ingred Name:PROPYLENE GLYCOL METHYL ETHER ACETATE (VAPOR PRESSURE 2 MM HG @ 20 C) (SOLVENT)

CAS:108-65-6

RTECS #:AI8925000

Fraction by Wt: 10%

Other REC Limits:NONE SPECIFIED

OSHA PEL:NONE ESTABLISHED

ACGIH TLV:NONE ESTAB

LISHED

Ingred Name:DI-SEC-OCTYL PHTHALATE (DI-2-ETHYLHEXYL-PHTHALATE) (SARA III)

CAS:117-81-7

RTECS #:TI0350000

Fraction by Wt: AIR

Spec Gravity:0.9

pH:4-7 *

Viscosity:15-35 SEC. F4

Evaporation Rate & Reference:SLOWER THAN DIETHYL ETHER

Solubility in Water:SLIGHT IN WATER

Appearance and Odor:LIQUID, SOLVENT ODOR.

Percent Volatiles by Volume:76

=====
===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES

STRONG ACIDS OR ALKALINE MATERI

ALS. OXIDIZING MATERIALS.

Stability Condition to Avoid:AVOID EXCESSIVE HEAT (>100 F (38 C)) AND SOURCES OF IGNITION.

Hazardous Decomposition Products:BURNING, INCLUDING WHEN HEATED BY WELDING OR CUTTING, WILL PRODUCE SMOKE, CO AND CO2. NITROGEN OXIDES MAY BE GENERATED.

===== Disposal Considerations =====

Waste Disposal Methods:DISPOSE IN ACCORDANCE WITH FEDERAL, STATE & LOCAL LAWS & REGULATIONS. INCINERATE ONLY IN EPA FACILITY. DO NOT INCINERATE CLOSED CONTAINERS.USE PRECAUTIONS FOR DISPOSAL OF FLAMMABLE MATERIALS-D001. USE HAZARDOUS WASTE LANDFILL FOR USED ABSORBENTS.

Disclaimer (provided with this information by the compiling agencies): This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.