

INJECTORALL ELECTRONICS CORP -- POLY SPRAY -- 5970-01-298-5590

=====
Product Identification
=====

Product ID:POLY SPRAY

MSDS Date:07/23/1990

FSC:5970

NIIN:01-298-5590

MSDS Number: BKNWX

=== Responsible Party ===

Company Name:INJECTORALL ELECTRONICS CORP

Address:98-100 GLEN ST

City:GLEN COVE

State:NY

ZIP:11542

Country:US

Info Phone Num:516-671-6010

Emergency Phone Num:516-671-6010/516-563-3388

CAGE

:21223

=== Contractor Identification ===

Company Name:INJECTORALL ELECTRONICS CORP

Address:98-100 GLEN ST

Box:City:GLEN COVE

State:NY

ZIP:11542

Country:US

Phone:516-671-6010/516-563-3388

CAGE:21223

=====
Composition/Information on Ingredients
=====

Ingred Name:TOLUENE (SARA III)

CAS:108-88-3

RTECS #:XS5250000

Fraction by Wt: < 30%

Other REC Limits:NONE SPECIFIED

OSHA PEL:200 PPM/150 STEL

ACGIH TLV:50 PPM; 9293

EPA Rpt Qty:1000 LBS

DOT Rpt Qty:1000 LBS

Ingred Name:XYLENES (O

-,M-,P- ISOMERS) (SARA III)

CAS:1330-20-7

RTECS #:ZE2100000

Fraction by Wt: < 20%

Other REC Limits:NONE SPECIFIED

OSHA PEL:100 PPM/150 STEL

ACGIH TLV:100 PPM/150STEL;9192

EPA Rpt Qty:1000 LBS

DOT Rpt Qty:1000 LBS

Ingred Name:ETHYL BENZENE (SARA III)

CAS:100-41-4

RTECS #:DA0700000

Fraction by Wt: < 5%

Other REC Limits:NONE SPECIFIED

OSHA PEL:100 PPM/125 STEL

ACGIH TLV:100 PPM/125STEL 9192

EPA Rpt Qty:1000 LBS

DOT Rpt Qty:1000 LBS

Ingred Name:CHLORODIFLUOROMETHANE

CAS:75-45-6

RTECS #:PA6390000

Other REC Limits:NONE SPECIFIED

OSHA PEL:1000 PPM

ACGIH TLV:1000PPM; 9192

Ozone Depleting Chemical:2

=====
===== Hazards Identification =====
=====

Routes of Entry: Inhalation:YES Skin:YES Ingestion:NO

Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO

Health Hazards Acute and Chronic:ACUTE-EYES:SLIGHT

IRRITATION,CONJUNCTIVITIS. SKIN:PROLONGED/REPEATED CONTACT CAN

CAUSE DEFATTING,IRRITATION & DERMATITIS.INHALED:MAY CAUSE

IRRITATION OF RESPIRATORY TRACT.PRO

LONGED/HIGH CONCENTRATION MAY

CAUSE CNS DEPRESSION,CONVULSION,UNCONSCIOUSNESS & EVEN

DEATH.SWALLOWED:UNLIKELY.IT MAY BE HARMFUL.CHRONIC-NOT GIVEN.

Explanation of Carcinogenicity:PRODUCT CONTAINS NO INGREDIENTS

CURRENTLY CLASSIFIED AS CARCINOGENIC BY NTP, IARC OR OSHA.

Effects of Overexposure:SYMPTOMS OF CNS DEPRESSION:HEADACHE,NAUSEA,
LOSS OF COORDINATION,FATIGUE,RESPIRATORY DEPRESSION,CONVULSION,
UNCONSCIOUSNESS.

Medical Cond Aggravated by Exposure:NONE SPECIFIED BY MANUFAC

TURER.

=====
===== First Aid Measures =====

First Aid:SEEK IMMEDIATE MEDICAL ATTENTION.SKIN:WASH WITH MILD SOAP AND WATER.INHALATION:REMOVE TO FRESH AIR.GIVE OXYGEN OR CPR AS NEEDED.EYE:IRRIGATE WITH WATER FOR 15 MINUTES WITH EYELIDS HELD OPEN. INGESTION :NO SPECIFIC ANTIDOTE.THE DECISION OF WHETHER TO INDUCE VOMITING OR NOT SHOULD BE MADE BY AN ATTENDING PHYSICIAN.

=====
===== Fire Fighting Measures =====

Extinguish

ing Media:CARBON DIOXIDE, FOAM, OR DRY CHEMICAL.USE COLD WATER TO REDUCE VAPOR PRESSURE IN CONTAINERS.

Fire Fighting Procedures:WEAR FIRE FIGHTING PROTECTIVE EQUIPMENT AND A FULL FACED SELF CONTAINED BREATHING APPARATUS. EVACUATE AREA. COOL FIRE EXPOSED CONTAINERS WITH WATER SPRAY.

Unusual Fire/Explosion Hazard:EXTREMELY FLAMMABLE. THIS IS AN AEROSOL PRODUCT. CONTENTS UNDER PRESSURE. EXPOSURE IN EXCESS OF 120F MAY CAUSE BURSTING OF CAN.

=====
===== Accidental Release Measures =====

Spill Release Procedures:FLOOR MAY BE SLIPPERY, USE CARE TO AVOID FALLING. ELIMINATE ALL SOURCES OF IGNITION. STOP LEAK OR REMOVE LEAKY CAN TO A SAFE OPEN AREA AND VENT SLOWLY TO AIR.

Neutralizing Agent:NONE SPECIFIED BY MANUFACTURER.

=====
===== Handling and Storage =====

Handling and Storage Precautions:STORAGE-STORE & USE IN WELL VENTILATED,LOW FIRE RISK AREA,AWAY FROM HEAT,IGNITION SOURCES & OXIDIZERS.

Other Precau

tions:KEEP AWAY FROM STOVES, FURNACES, AND DIRECT SUNLIGHT.

DO NOT PUNCTURE OR INCINERATE. FOR BRIEF CONTACT/SPRAY, NO PRECAUTIONS OTHER THAN CLEAN BODY COVERING SHOULD BE NEEDED. TRAIN EMPLOYEES IN PROPER USE. FOLLOW LABEL DIRECTION.

=====
===== Exposure Controls/Personal Protection =====

Respiratory Protection:USE NIOSH/MSHA APPROVED AIR-PURIFYING OR SUPPLIED AIR RESPIRATOR AS APPROPRIATE.

Ventilation:MECHANICAL(GENERAL) EXHAUST RECOMMENDED. NO SPECIAL VENTIL

ATION IS USUALLY REQUIRED TO MEET EXPOSURE STANDARDS.

Protective Gloves:POLYFLUORINATED OR POLYVINYL ALCOHOL

Eye Protection:CHEMICAL SPLASH GOGGLES &/OR FACESHIELD

Other Protective Equipment:EYE WASH STATION & SAFETY SHOWERS SHOULD BE AVAILABLE IN THE IMMEDIATE VICINITY OF ANY POTENTIAL EXPOSURE.PLASTIC APRON.

Work Hygienic Practices:WASH HANDS BEFORE EATING, DRINKING, SMOKING, OR USING TOILET FACILITIES. WASH CONTAMINATED CLOTHING BEFORE REUSE.

Supplemental Safety and Health

FORMULA

TION CHANGED. FOR PREVIOUS FORMULATION, SEE PART A SAME NSN.

===== Physical/Chemical Properties =====

HCC:V3

Boiling Pt:B.P. Text:>-41F,>-41C

Vapor Pres:2586

Vapor Density:> 1

Spec Gravity:0.96

Solubility in Water:NEGLIGIBLE

Appearance and Odor:CLEAR THICK LIQUID- TYPICAL AROMATIC ODOR

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES

STRONG OXIDIZING AGENTS, ALKALIES, ALUMINUM, ZINC AND THEIR ALLOYS

Sta

bility Condition to Avoid:HIGH HEAT, OPEN FLAMES, SPARKS AND OTHER SOURCES OF IGNITION

Hazardous Decomposition Products:AT HIGH TEMPERATURES OR FLAMES, IT DECOMPOSES TO GIVE OFF CARBON DIOXIDE, CARBON MONOXIDE AND WATER.

===== Disposal Considerations =====

Waste Disposal Methods:REPLACE CAP AND DISCARD CONTAINER IN TRASH. DISPOSE OF IN ACCORDANCE WITH ALL LOCAL, STATE AND FEDERAL REGULATIONS.

Disclaimer (provided with this information by the compiling agencies):

This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.