

STIC-ADHESIVE PRODUCTS CO INC -- ENAMEL, ALKYD SEMI-GLOSS -- 8010-00-145-0164

=====
Product Identification
=====

Product ID:ENAMEL, ALKYD SEMI-GLOSS

MSDS Date:01/01/1987

FSC:8010

NIIN:00-145-0164

MSDS Number: BKPFZ

=== Responsible Party ===

Company Name:STIC-ADHESIVE PRODUCTS CO INC

Address:3950 MEDFORD ST

City:LOS ANGELES

State:CA

ZIP:90063

Country:US

Info Phone Num:213-268-2956

Emergency Phone

Num:213-268-2956

CAGE:1BH90

=== Contractor Identification ===

Company Name:STIC-ADHESIVE PRODUCTS CO INC

Address:3950 MEDFORD ST

Box:City:LOS ANGELES

State:CA

ZIP:90063-1675

Country:US

CAGE:1BH90

=====
Composition/Information on Ingredients
=====

Ingred Name:MINERAL SPIRITS

Fraction by Wt: 37.1%

Other REC Limits:NONE SPECIFIED

ACGIH TLV:200 PPM

=====
Hazards Identification
=====

LD50 LC50 Mixture:200 PPM FOR 8 HOUR WORKING DAY.

Health Hazar

ds Acute and Chronic:SEVERE EYE IRRITATION, DRYING OF SKIN,
EXCESSIVE INHALATION CAUSES HEADACHE, DIZZINESS AND NAUSEA.

===== First Aid Measures =====

First Aid:EYE CONTACT: FLUSH WITH WATER. SKIN CONTACT: REMOVE PAINT WITH MINERAL SPIRITS. THEN WASH WITH MILD SOAP AND WATER AND APPLY SKIN CREAM. INHALATION: REMOVE TO FRESH AIR AND CALL A PHYSICIAN. APPLY ART IFICIAL RESPIRATION IF NECESSARY.

===== Fire Fighting Measures =====

Flash Point Method:TCC
Flash Point:105F,41C
Lower Limits:1.1
Upper Limits:6.0
Extinguishing Media:FOAM, CO2, DRY CHEMICALS, WATERSPRAY OR FOG.
Fire Fighting Procedures:USE AIR SUPPLIED RESCUE EQUIPMENT FOR ENCLOSED AREAS. COOL EXPOSED CONTAINERS WITH WATER.
Unusual Fire/Explosion Hazard:KEEP AWAY FROM HEAT, SPARKS OR OPEN FLAME.

===== Accidental Release Measures =====

Spill Release Procedures:KEEP PEOPLE AWAY. REMOVE ALL SOURCES OF IGNITION AND PROVIDE VENTILATION. LARGE SPILLS MAY BE SCOOPED UP WITH NON- SPARKING TOOLS. AVOID EXPOSURE TO SPARKS, FIRE OR HOT METAL SURFACES. AVOID BREATHING VAPORS.

===== Handling and Storage =====

Handling and Storage Precautions:KEEP CONTAINERS CLOSED. USE WITH ADEQUATE VENTILATION. GROUND CONTAINERS. LIMIT FREE FALL TO A FEW INCHES TO PREVENT STATIC SPARKS.
Other Precautions:IMMERSE SPRAY BOOTH CLEANINGS (ACCUMULATION) IMMEDIATELY IN WATER. AVOID PROLONGED OR REPEATED CONTACT WITH THE SKIN.

===== Exposure Controls/Personal Protection =====

Respiratory Protection:SELF-CONTAINED BREATHING APPARATUS FOR CONCENTRATIONS ABOVE TLV LIMITS.
Ventilation:FACE VELOCITY OVER 60 FT./MIN. EXPLOSION-PROOF VENT EQUIP. USE W/ADEQUATE VENT. NO SMOKING, OPEN FLAMES OR LIGHT BULBS.
Protective Gloves:HYDROCARBON INSOL, RUBBER OR PLASTIC.
Eye Protection:CHEM. SPLASH GOGGLES/FACE SPLASH SHIELD.
Other Protective

Equipment:EYE BATH AND SAFETY SHOWER. NEOPRENE APRON.
Supplemental Safety and Health

===== Physical/Chemical Properties =====

HCC:F4
Boiling Pt:B.P. Text:310 TO 390F
Vapor Pres:2 MM @ 68F
Vapor Density:4.0
Spec Gravity:1.224
Evaporation Rate & Reference:0.28 (BUAC=1)
Solubility in Water:NEGLIGIBLE
Appearance and Odor:GRAY AND/OR WHITE VISCOUS LIQUID OF MINERAL SPIRITS
ORDER. (LIGHT)
Percent Volatiles by Volume:57.1

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES
STRONG OXIDIZING AGENTS WILL DISSOLVE OR SOFTEN SOME PLASTICS & RUBBER.
Stability Condition to Avoid:HEAT, SPARKS, OPEN FLAME AND FIRE.
Hazardous Decomposition Products:THERMAL DECOMPOSITION MAY YIELD CARBON
MONOXIDE, CO2 AND POSSIBLY ACROLEIN.

===== Disposal Considerations =====

Waste Disposal Methods:PLACE IN CLOSED CONTAINERS. RAGS & ABSORBENT
MATERIALS SHOULD BE IMMEDIATELY IMMERS
ED IN WATER. DISPOSE OF IN
ACCORDANCE WITH LOCAL, STATE AND FEDERAL REGULATIONS. NOTIFY FIRE
AND HEALTH AGENCIES.

Disclaimer (provided with this information by the compiling agencies):
This information is formulated for use by elements of the Department
of Defense. The United States of America in no manner whatsoever,
expressly or implied, warrants this information to be accurate and
disclaims all liability for its use. Any person utilizing this
document should seek competent pro
fessional advice to verify and
assume responsibility for the suitability of this information to their
particular situation.