

BAKER SEALANTS AND COATINGS CO -- PAINT FOR CONCRETE AND MASONARY --
8010-00-597-8219

===== Product Identification =====

Product ID:PAINT FOR CONCRETE AND MASONARY
MSDS Date:03/25/1991
FSC:8010
NIIN:00-597-8219
MSDS Number: BKPJC
=== Responsible Party ===
Company Name:BAKER SEALANTS AND COATINGS CO
Address:234 SUYDAM AVE
Box:B
City:JERSEY CITY
State:NJ
ZIP:07304
Country:US
Info Phone Num:201-333-6
986
Emergency Phone Num:201-333-6986/800-356-3129(CHEMTREC)
Preparer's Name:CHARLES FRIEDMAN
CAGE:34094

=== Contractor Identification ===

Company Name:BAKER SEALANTS AND COATINGS CO
Address:234 SUYDAM AVE
Box:City:JERSEY CITY
State:NJ
ZIP:07304-3306
Country:US
Phone:201-333-6986
CAGE:34094

===== Composition/Information on Ingredients =====

Ingred Name:2-BUTOXYETHANOL
CAS:111-76-2
RTECS #:KJ8575000
Fraction by Wt: 5-10%
Other REC Limits:NONE SPECIFIED
OSHA PEL:S, 50 PPM
ACGIH

TLV:S, 25 PPM; 9293

Ingred Name:CALCIUM CARBONATE (MARBLE) (LIMESTONE)

CAS:1317-65-3

RTECS #:EV9580000

Fraction by Wt: 10-15%

Other REC Limits:NONE SPECIFIED

OSHA PEL:15 MG/M3 TDUST

ACGIH TLV:10 MG/M3 TDUST; 9192

Ingred Name:TITANIUM DIOXIDE

CAS:1317-80-2

RTECS #:VM2940000

Fraction by Wt: 5-10%

Other REC Limits:NONE SPECIFIED

Ingred Name:ACRYLIC RESIN

Fraction by Wt: 20-30%

Other REC Limits:NONE SPECIFIED

Ingred Name:VM & P NAPHTHA

CAS:8030-30-6

RTECS #:DE3030000

Fraction by Wt: 20-25%

Other

REC Limits:NONE SPECIFIED

Ingred Name:PETROLEUM SOLVENT

CAS:64742-95-6

Fraction by Wt: 5-10%

Other REC Limits:NONE SPECIFIED

ACGIH TLV:100 PPM TWA

Ingred Name:TOLUENE (SARA III)

CAS:108-88-3

RTECS #:XS5250000

Fraction by Wt: 5-10%

Other REC Limits:NONE SPECIFIED

OSHA PEL:200 PPM/150 STEL

ACGIH TLV:50 PPM; 9293

EPA Rpt Qty:1000 LBS

DOT Rpt Qty:1000 LBS

Ingred Name:VOC: 508

RTECS #:9999999VO

Other REC Limits:NONE SPECIFIED

==== Hazards Identification =====

Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES
Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO
Health Hazards Acute and Chronic:EYES: HIGH VAPOR CONCENTRATION CAUSES IRRITATION, REDNESS AND TEARING. SKIN: PROLONGED AND REPEATED CONTACT MAY CAUSE IRRITATION, DRY SKIN AND DERMATITIS. INHALATION: MAY CAUSE HEADACHES, DIZZINESS, DAMAGE TO THE NERVOUS SYSTEM. INGESTION:MAY CAUSE IRRITATION OF DIGESTIVE TRACT, SIGNS OF NERVOUS SYSTEM DEPRESSION.

Effects of Overexposure:INGESTION: DROWSINESS, DIZZINESS, LOSS OF COORDINATION AND FATIGUE).
Medical Cond Aggravated by Exposure:PRE-EXISTING DERMATITIS.

=====
===== First Aid Measures =====

First Aid:EYES: MOVE TO FRESH AIR. FLUSH W/FRESH WATER. SKIN: REMOVE CONTAM CLOTHING. CLEANSE AFFECTED AREAS W/MILD SOAP & WATER. INHALE: MOVE TO FRESH AIR. GIVE CPR IF BREATHING STOPS. INGEST: IF VICTIM IS CON SCIOUS, INDUCE VOMIT, PREFERABLY W/SYRUP OF IPECAC UNDER PHYSICIAN DIRECTION. IF DROWSY, PLACE ON LEFT SIDE W/HEAD DOWN. DO NOT LEAVE VICTIM UNATTENDED. SEEK NEEDED MEDICAL AID FOR CONDITIONS ABOVE.

=====
===== Fire Fighting Measures =====

Flash Point Method:SCC
Flash Point:105F,41C
Autoignition Temp:Autoignition Temp Text:480 F
Lower Limits:1.0
Upper Limits:7.0
Extinguishing Media:WATER FOG, FOAM, DRY CHEMICAL OR CARBON DIOXIDE.
Unusual Fire/Explosion Hazard:NONE

=====
===== Accidental Release Measures =====

Spill Release Procedures:STAY UPWIND & AWAY FROM SPILL. EXTINGUISH IGNITE SOURCES. USE SAND OR OTHER INERT MATERIAL TO DAM & CONTAIN SPILL. DO NOT FLUSH AREA W/WATER. ABSORB INTO ABSORBENT PADS & DISPOSE IN ACCORDANCE W/LOCAL , STATE AND FEDERAL REGULATIONS. VENT SPILL AREA.

=====
===== Handling and Storage =====

Handling and Storage Precautions:AVOID USE NEAR OPEN FLAMES AND OTHER SOURCES OF IGNITION. STORE IN DRY, COOL AREA.

====

===== Exposure Controls/Personal Protection =====

Respiratory Protection:USING SELF-CONTAINED BREATHING APPARATUS IS RECOMMENDED IF AIRBORNE VAPOR CONCENTRATION EXCEEDS THE LIMIT.
Ventilation:LOCAL EXHAUST MAY BE REQUIRED IF VAPOR EXCEEDS THE LIMIT.
Protective Gloves:IMPERVIOUS, CHEMICAL RESISTANT GLOVES.
Eye Protection:CHEMICAL RESISTANT GOGGLES.
Supplemental Safety and Health

===== Physical/Chemical Properties =====

HCC:F4
Boiling Pt:B.P. Text:3
13 TO 382F
Vapor Pres:7.5
Vapor Density:9.0
Spec Gravity:1.12
pH:6.5
Viscosity:67-85 KU
Evaporation Rate & Reference:1.8 (BUAC = 1)
Solubility in Water:NEGLIGIBLE
Appearance and Odor:LIQUID, SOLVENT ODOR
Percent Volatiles by Volume:69

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES
Stability Condition to Avoid:STRONG ACIDS, BASES AND OXIDIZERS.
Hazardous Decomposition Products:CARBON MONOXIDE AND CARBON DIOXIDE.

===== Disposal Considerations =====

Waste Disposal Methods:DISPOSE IN ACCORDANCE WITH LOCAL, STATE AND FEDERAL REGULATIONS.

Disclaimer (provided with this information by the compiling agencies):
This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document

should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.