

CAULK/DENTSPLY -- 666005-TEMPORARY BRIDGE RESIN LIQUID -- 6520-01-162-2073

=====
Product Identification
=====

Product ID:666005-TEMPORARY BRIDGE RESIN LIQUID

MSDS Date:08/17/1988

FSC:6520

NIIN:01-162-2073

Status Code:A

MSDS Number: BKTCV

=== Responsible Party ===

Company Name:CAULK/DENTSPLY

Address:LAKEVIEW AND CLARKE AVE

Box:359

City:MILFORD

State:DE

ZIP:19963-0359

Country:US

Info Phone Num:302-4

22-4511

Emergency Phone Num:302-422-4511

CAGE:11107

=== Contractor Identification ===

Company Name:CAULK/DENTSPLY

Address:38 W CLARKE AVE

Box:359

City:MILFORD

State:DE

ZIP:19963-0359

Country:US

Phone:302-422-4511/ 703-451-1900

CAGE:11107

=====
Composition/Information on Ingredients
=====

Ingred Name:METHYL METHACRYLATE, (MONOMER)

CAS:80-62-6

RTECS #:OZ5075000

Other REC Limits:100 PPM

OSHA PEL:410 MG/CUM

ACGIH TLV:410 MG/CUM

EPA Rpt Qty:1000 LBS

DOT Rpt Qty:1000 LBS

Ingred Na

me:HYDROQUINONE, 1,4-DIHYDROXYBENZENE, 1,4-BENZENEDIOL

CAS:123-31-9

RTECS #:MX3500000

OSHA PEL:2 MG/CUM

ACGIH TLV:2 MG/CUM

EPA Rpt Qty:1 LB

DOT Rpt Qty:1 LB

=====
===== Hazards Identification =====

Routes of Entry: Inhalation:YES Skin:NO Ingestion:YES

Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO

Health Hazards Acute and Chronic:SKIN: IRRITATION & ALLERGIC REACTION.

EYES: IRRITATION. CHRONIC EXPOSURE: LIVER & KIDNEY DAMAGE.

Explanation of Carcinogenicit

y:NONE

Effects of Overexposure:SKIN/EYES: REDDENING.

Medical Cond Aggravated by Exposure:SKIN RASHES

=====
===== First Aid Measures =====

First Aid:INHALATION: REMOVE TO FRESH AIR. GIVE OXYGEN IF BREATHING IS
DIFFICULT. GIVE ARTIFICIAL RESPIRATION IF BREATHING STOPS.

INGESTION: INDUCE VOMITING. EYES: FLUSH W/PLENTY OF WATER FOR 15
MINS. SKIN: WASH W/SOAP & WATER. OBTAIN MEDICAL ATTENTION IN ALL
CASES.

=====
===== Fire Fighting Measure

s =====

Flash Point Method:OC

Flash Point:50F, 10C

Lower Limits:2.1%

Upper Limits:12.5%

Extinguishing Media:FOAM, CO2, DRY CHEMICAL OR CARBON TETRACHLORIDE.

Fire Fighting Procedures:WATER MAY BE INEFFECTIVE UNLESS USED AS A FINE
SPRAY OR FOG. USE WATER SPRAY TO COOL FIRE EXPOSED CONTAINERS OF
METHYL METHACRYLATE. USE SCBA.

Unusual Fire/Explosion Hazard:VAPORS MAY TRAVEL TO IGNITION SOURCE &
FLASH BACK. CLOSED CONTAINERS MAY RUPTURE EXPLOSIVELY.

=====

Accidental Release Measures =====

Spill Release Procedures:ELIMINATE IGNITION SOURCES. DIKE & ABSORB SPILL W/INERT MATERIAL (SAND, SODA, ASH, VERMICULITE) & TRANSFER TO CONTAINERS FOR DISPOSAL. USE NON-SPARKING TOOLS.

===== Handling and Storage =====

Handling and Storage Precautions:STORE AT AMBIENT TEMPERATURES OUT OF DIRECT SUNLIGHT. USE OLDER MATERIALS FIRST. USE ADEQUATE VENTILATION. KEEP CONTAINERS CLOSED.

Other Precautions

:KEEP AWAY FROM HEAT, SPARKS, & OPEN FLAME. AVOID BREATHING VAPORS & CONTACT W/SKIN.

===== Exposure Controls/Personal Protection =====

Respiratory Protection:USE SELF-CONTAINED BREATHING APPARATUS DURING HIGH VAPOR CONCENTRATION.

Ventilation:LOCAL EXHAUST AT PROCESSING EQUIPMENT. MECHANICAL (GENERAL): IF NECESSARY DURING HANDLING.

Protective Gloves:IMPERVIOUS

Eye Protection:SPLASH-PROOF GOGGLES

Other Protective Equipment:IMPERVIOUS APRON, OVERSHOES

Work Hygienic P

ractices:REMOVE/LAUNDER CONTAMINATED CLOTHING BEFORE REUSE.

Supplemental Safety and Health

===== Physical/Chemical Properties =====

Boiling Pt:B.P. Text:214F/101C

Vapor Pres:29

Vapor Density:3.45

Spec Gravity:0.94

Evaporation Rate & Reference:(ETHER = 1): >1

Solubility in Water:SLIGHT

Appearance and Odor:WATER CLEAR LIQUID W/CHARACTERISTIC ACRYLIC ODOR

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoi

d:YES

AMINES, REDUCING OR OXIDIZING AGENTS

Stability Condition to Avoid:ELEVATED TEMPERATURES, HEAT, SPARKS,
DIRECT SUNLIGHT & OTHER IGNITION SOURCES.

Hazardous Decomposition Products:ACRID FUMES, CO, CO2

===== Disposal Considerations =====

Waste Disposal Methods:INCINERATE UNDER CONTROLLED CONDITIONS IN A SAFE
OPEN AREA, OR LANDFILL IN ACCORDANCE W/LOCAL, STATE, & FEDERAL
REGULATIONS. BIOLOGICAL DEGRADATION IS ALSO POSSIBLE.

Disclaimer (provided w

ith this information by the compiling agencies):

This information is formulated for use by elements of the Department
of Defense. The United States of America in no manner whatsoever,
expressly or implied, warrants this information to be accurate and
disclaims all liability for its use. Any person utilizing this
document should seek competent professional advice to verify and
assume responsibility for the suitability of this information to their
particular situation.