

SPORLAN VALVE COMPANY -- RC10098 CATCH ALL BRAND -- 4330-00-407-0994
===== Product Identification =====

Product ID:RC10098 CATCH ALL BRAND
MSDS Date:11/24/1985
FSC:4330
NIIN:00-407-0994
MSDS Number: BKYKP
=== Responsible Party ===
Company Name:SPORLAN VALVE COMPANY
Address:7525 SUSSEX AVENUE
City:ST. LOUIS
State:MO
ZIP:63143
Info Phone Num:(314) 647-2775
Emergency Phone Num:(314) 647-2775
Prepare
r's Name:JOHN E. HOFFMAN
CAGE:78462
=== Contractor Identification ===
Company Name:SPORLAN VALVE COMPANY
Address:7525 SUSSEX AVE.
Box:City:ST LOUIS
State:MO
ZIP:63143
Phone:314-647-2775
CAGE:78462

===== Composition/Information on Ingredients =====

Ingred Name:ALPHA-ALUMINA (ALUMINUM OXIDE) (EPA LISTS ONLY FIBROUS
FORMS) (SARA III)
CAS:1344-28-1
RTECS #:BD1200000
OSHA PEL:15 MG/M3 TDUST
ACGIH TLV:10 MG/M3 TDUST; 9293

Ingred Name:SODIUM ALUMINOSILICATE
CAS:1344-00-9

Ing

red Name:ALUMINUM PHOSPHATE, MONOAMMONIUM PHOSPHATE

CAS:7784-30-7

RTECS #:TB6450000

ACGIH TLV:2 MG/CUM

Ingred Name:KAOLIN

CAS:1332-58-7

RTECS #:GF1670500

OSHA PEL:15 MG/M3 TDUST

ACGIH TLV:2 MG/M3 TDUST; 9293

=====
===== Hazards Identification =====

Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES

Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO

Health Hazards Acute and Chronic:INHALATION/SKIN/EYES/INGESTION: LOW
RISK OF IRRITABILITY.

Explanation of

Carcinogenicity:NONE

Effects of Overexposure:INHALATION/SKIN/EYES/INGESTION: LOW RISK OF
IRRITABILITY.

=====
===== Fire Fighting Measures =====

Flash Point:NON-FLAMMABLE

=====
===== Accidental Release Measures =====

Spill Release Procedures:FLUSH SMALL AMOUNTS W/WATER, MOP UP OR SWEEP
UP, & DISPOSE OF IN THE SAME MANNER AS CONVENTIONAL PAPER TRASH.

=====
===== Handling and Storage =====

Handling and Stor

age Precautions:NO PRECAUTIONS ARE NECESSARY FOR

STORING. STORE IN NORMAL CONDITIONS. CORE WILL PICK UP WATER BY
ADSORPTION PROCESS/WILL GET WARM DURING WATER PICKUP.

Other Precautions:TO OPEN THE METAL CAN CONTAINING THE PRODUCT, THE
TEAR STRIP ON THE SIDE OF THE CAN SHOULD BE OPENED CAUTIOUSLY USING
PLIERS TO AVOID BEING CUT BY THE SHARP METAL EDGE OF THE TEAR
STRIP.

=====
===== Exposure Controls/Personal Protection =====

Other Protective Equipment:AS NECESSAR

Y

Supplemental Safety and Health

PRODUCT TO REMOVE CONTAMINANTS FROM CIRCULATING REFRIGERANT ON REFRIGERATION/AIR CONDITIONING SYSTEMS/UTILIZE SOLID FILTER CORE MOLDED FROM DESICCANT GRANULES. IF MOLDED BLOCK IS CRUSHED, IT IS POSSIBLE THE RESULTING POWDER TO BE CONSIDERED A NUISANCE DUST IF >10 MG/CUM. 8% VOL AT 1700F.

===== Physical/Chemical Properties =====

Spec Gravity:1.1 G/ML
Solubility in Water:INSOLUBLE
Appearance and Odor:CORE IS ABRASIVE SOLID MATERIAL/ODORLESS, COMPOSED OF WHITE/BUFF/BLACK GRAINS.
Percent Volatiles by Volume:0%

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES

===== Disposal Considerations =====

Waste Disposal Methods:DISPOSAL SHOULD BE HANDLED ACCORDING TO LOCAL LAWS. HOWEVER, SPILLED MATERIAL NEED NOT BE CONSIDERED A HAZARDOUS WASTE.

Disclaimer (provided with this information by the compiling agencies

):
This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.