

SEYMOUR OF SYCAMORE INC -- TOOLMAKER BLUE LAYOUT INK FORMULA 00-0016-0 --
3680-00-237-3457

===== Product Identification =====

Product ID:TOOLMAKER BLUE LAYOUT INK FORMULA 00-0016-0

MSDS Date:08/28/1991

FSC:3680

NIIN:00-237-3457

MSDS Number: BLFDW

=== Responsible Party ===

Company Name:SEYMOUR OF SYCAMORE INC

Address:917 CROSBY AVE

City:SYCAMORE

State:IL

ZIP:60178-1343

Country:US

Info Phone Num:81

5-895-9101

Emergency Phone Num:815-895-9101

CAGE:59581

=== Contractor Identification ===

Company Name:EISON INDUSTRIAL SALES INC/DBS GOV. PROCUREMENT

Address:5800 OAKBROOK PKY

Box:City:NORCROSS

State:GA

ZIP:30093-1805

Country:US

Phone:404-448-7100

CAGE:1FY72

Company Name:SEYMOUR OF SYCAMORE

Address:917 CROSBY AVE.

Box:City:SYCAMORE

State:IL

ZIP:60178-1343

Country:US

Phone:815-895-9101/800-255-3924

CAGE:59581

===== Composition/Information on Ingredients =====

Ingred Name:BLUE

PIGMENT

CAS:147-14-8

Fraction by Wt: 0.50%

Other REC Limits:NONE SPECIFIED

Ingred Name:ETHYL ALCOHOL (ETHANOL)

CAS:64-17-5

RTECS #:KQ6300000

Fraction by Wt: 5.15%

Other REC Limits:NONE SPECIFIED

OSHA PEL:1000 PPM

ACGIH TLV:1000 PPM; 9192

Ingred Name:XYLENES (O-,M-,P- ISOMERS) (SARA III)

CAS:1330-20-7

RTECS #:ZE2100000

Fraction by Wt: 2.18%

Other REC Limits:NONE SPECIFIED

OSHA PEL:100 PPM/150 STEL

ACGIH TLV:100 PPM/150STEL;9192

EPA Rpt Qty:1000 LBS

DOT Rpt Qty:1000 LBS

Ingred Name:ETHYL BENZEN

E (SARA III)

CAS:100-41-4

RTECS #:DA0700000

Fraction by Wt: 0.54%

Other REC Limits:NONE SPECIFIED

OSHA PEL:100 PPM/125 STEL

ACGIH TLV:100 PPM/125STEL 9192

EPA Rpt Qty:1000 LBS

DOT Rpt Qty:1000 LBS

Ingred Name:ETHYL ALCOHOL (ETHANOL)

CAS:64-17-5

RTECS #:KQ6300000

Fraction by Wt: 0.24%

Other REC Limits:NONE SPECIFIED

OSHA PEL:1000 PPM

ACGIH TLV:1000 PPM; 9192

Ingred Name:DIBUTYL PHTHALATE (SARA III)

CAS:84-74-2

RTECS #:TI0875000

Fraction by Wt: 0.55%

Other REC Limits:NONE SPECIFIED

OSHA PEL:5

MG/M3
ACGIH TLV:5 MG/M3; 9192
EPA Rpt Qty:10 LBS
DOT Rpt Qty:10 LBS

Ingred Name:DI-SEC-OCTYL PHTHALATE (DI-2-ETHYLHEXYL-PHTHALATE) (SARA III)

CAS:117-81-7
RTECS #:TI0350000
Fraction by Wt: 0.12%
Other REC Limits:NONE SPECIFIED
OSHA PEL:5 MG/M3/10 STEL
ACGIH TLV:5 MG/M3; 9192
EPA Rpt Qty:100 LBS
DOT Rpt Qty:100 LBS

Ingred Name:TOLUENE (SARA III)

CAS:108-88-3
RTECS #:XS5250000
Fraction by Wt: 1.98%
Other REC Limits:NONE SPECIFIED
OSHA PEL:200 PPM/150 STEL
ACGIH TLV:50 PPM; 9293
EPA Rpt Qty:
1000 LBS
DOT Rpt Qty:1000 LBS

Ingred Name:METHYL ISOBUTYL KETONE (SARA III)

CAS:108-10-1
RTECS #:SA9275000
Fraction by Wt: 2.40%
Other REC Limits:NONE SPECIFIED
OSHA PEL:100 PPM/75 STEL
ACGIH TLV:50 PPM/75 STEL; 9293
EPA Rpt Qty:5000 LBS
DOT Rpt Qty:5000 LBS

Ingred Name:ISOPROPYL ACETATE

CAS:108-21-4
RTECS #:AI4930000
Fraction by Wt: 14.06%
Other REC Limits:NONE SPECIFIED
OSHA PEL:250 PPM/310 STEL
ACGIH TLV:250 PPM/310STEL;9192

Ingred Name:ACETONE (SARA III)

CAS:67-64-1
RTECS #:AL3150000
Fr

action by Wt: 37.24%
Other REC Limits:NONE SPECIFIED
OSHA PEL:1000PPM
ACGIH TLV:750PPM/1000STEL;9293
EPA Rpt Qty:5000 LBS
DOT Rpt Qty:5000 LBS

Ingred Name:ETHYL ACETATE (SARA III)
CAS:141-78-6
RTECS #:AH5425000
Fraction by Wt: 1.60%
Other REC Limits:NONE SPECIFIED
OSHA PEL:400 PPM
ACGIH TLV:400 PPM; 9192
EPA Rpt Qty:5000 LBS
DOT Rpt Qty:5000 LBS

Ingred Name:METHYL ETHYL KETONE (2-BUTANONE) (MEK) (SARA III)
CAS:78-93-3
RTECS #:EL6475000
Fraction by Wt: 1.84%
Other REC Limits:NONE SPECIFIED
OS
HA PEL:200 PPM/300 STEL
ACGIH TLV:200 PPM/300STEL 9192
EPA Rpt Qty:5000 LBS
DOT Rpt Qty:5000 LBS

Ingred Name:ISOPROPYL ALCOHOL (SARA III)
CAS:67-63-0
RTECS #:NT8050000
Fraction by Wt: 1.51%
Other REC Limits:NONE SPECIFIED
OSHA PEL:400 PPM/500 STEL
ACGIH TLV:400 PPM/500STEL;9192

Ingred Name:PROPANE
CAS:74-98-6
RTECS #:TX2275000
Fraction by Wt: 13.6%
Other REC Limits:NONE SPECIFIED
OSHA PEL:1000 PPM
ACGIH TLV:ASPHYXIAN; 9192

Ingred Name:ISOBUTANE
CAS:75-28-5
RTECS #:TZ4300000
Fraction by Wt:

9.1%

Other REC Limits:NONE SPECIFIED

Ingred Name:METHYL ALCOHOL (METHANOL) (SARA III)

CAS:67-56-1

RTECS #:PC1400000

Fraction by Wt: 0.27%

Other REC Limits:NONE SPECIFIED

OSHA PEL:S,200PPM/250STEL

ACGIH TLV:S,200PPM/250STEL; 93

EPA Rpt Qty:5000 LBS

DOT Rpt Qty:5000 LBS

=====
===== Hazards Identification =====
=====

Routes of Entry: Inhalation:YES Skin:YES Ingestion:NO

Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO

Health Hazards Acute and Chronic:ACUTE: IRRITATIO

N TO EYES, SKIN AND

RESPIRATORY SYSTEM, CENTRAL NERVOUS SYSTEM EFFECTS. CHRONIC: SKIN
DEFFATTING, DERMATITIS.

Effects of Overexposure:EYES: IRRITATION. SKIN: IRRITATION. INHALATION:

NOSE, THROAT, LUNG IRRITATION, HEADACHE, DIZZINESS, NAUSEA,
UNCONSCIOUSNESS, ASPHYXIATION. INGESTION: NOT LIKELY, AEROSOL.

Medical Cond Aggravated by Exposure:INDIVIDUALS WITH A HISTORY OF

RESPIRATORY OR SKIN ALLERGIC CONDITIONS MAY BE AT INCREASED RISK.

=====
===== First Aid Measure
=====

S =====

First Aid:EYES: FLUSH WITH PLENTY OF WATER FOR 15 MINUTES.IF IRRITATION

PERSISTS SEE DOCTOR. SKIN: WASH WITH SOAP AND WATER.IF IRRITATION

PERSISTS.SEE DOCTOR. INHALATION: REMOVE TO FRESH AIR.GIVE

OXYGEN/CPR IF NEEDED.SEE DOCTOR. INGESTION: SEE DOCTOR.

=====
===== Fire Fighting Measures =====
=====

Flash Point Method:TOC

Flash Point:10F,-12C

Extinguishing Media:USE CARBON DIOXIDE, FOAM, OR DRY CHEMICAL. WATER

SPRAY MAY BE INEFFE

CTIVE.

Fire Fighting Procedures:WEAR FIRE FIGHTING PROTECTIVE EQUIPMENT AND A FULL FACED SELF CONTAINED BREATHING APPARATUS. EVACUATE AREA. COOL FIRE EXPOSED CONTAINERS WITH WATER FOG.

Unusual Fire/Explosion Hazard:EXPOSURE TO HEAT MAY CAUSE BURSTING OF AEROSOL CANS. COMBUSTION OR HEAT OF FIRE MAY PRODUCE HAZARDOUS DECOMPOSITION PRODUCTS AND VAPORS.

===== Accidental Release Measures =====

Spill Release Procedures:REMOVE IGNITION SOURCES.EVACUATE

PERSONNEL.VENTILATE.WEAR RESPIRATOR AND PROTECTIVE CLOTHING.ABSORB IN INERT MATERIAL AND PLACE IN APPROPRIATE DISPOSAL CONTAINER.WASH AREA WITH SOAP AND WATER.

===== Handling and Storage =====

Handling and Storage Precautions:STORE IN COOL, DRY, WELL VENTILATED, LOW FIRE RISK AREA.PROTECT CONTAINER FROM PHYSICAL DAMAGE.DO NOT STORE ABOVE 120F(49C).

Other Precautions:KEEP AT ROOM TEMPERATURE AS EXPOSURE TO SUNLIGHT MAY CAUSE BURSTING.

=====

===== Exposure Controls/Personal Protection =====

Respiratory Protection:NIOSH/MSHA-APPROVED RESPIRATOR APPROPRIATE FOR EXPOSURE OF CONCERN IF TLV IS EXCEEDED.

Ventilation:LOCAL EXHAUST TO MAINTAIN EXPOSURE BELOW TLV.

Protective Gloves:NITRILE,PVA, OPTIONAL.

Eye Protection:GOGGLES.

Other Protective Equipment:AS REQUIRED TO PREVENT PROLONGED CONTACT.

Work Hygienic Practices:WASH THOROUGHLY AFTER HANDLING.LAUNDER CONTAMINATED CLOTHING BEFORE REUSE.

Supplemental Safety and Health

NONE.

===== Physical/Chemical Properties =====

HCC:V3

Boiling Pt:B.P. Text:N/R,AEROSOL

Vapor Pres:40 PSIA

Vapor Density:>1

Evaporation Rate & Reference:>1 (ETHER = 1)

Appearance and Odor:NOT SPEFIED BY MANUFACTURER. PRODUCT COMES IN AN AEROSOL CAN.

Percent Volatiles by Volume:85

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES

DO NOT BLEND WITH AMINES, ALKALINE MATERIALS OR STRONG ACIDS.

Stabili

ty Condition to Avoid:AVOID TEMPERATURES HIGHER THAN 120F,
SPARKS, PILOT LIGHTS, OPEN FLAMES.

Hazardous Decomposition Products:OXIDES OF NITROGEN, HYDROGEN CYANIDE,
CARBON MONOXIDE.

===== Disposal Considerations =====

Waste Disposal Methods:CONTACT YOUR LOCAL ENVIRONMENTAL OFFICER.DO NOT
PUNCTURE OR INCINERATE CONTAINER.GIVE TO DISPOSAL SERVICE.DISPOSE
OF IN ACCORDANCE WITH FEDERAL,STATE AND LOCAL ENVIRONMENTAL
REGULATIONS.FULL OR PARTIA LLY
FILLED CONTAINERS ARE CONSIDERED
HAZARDOUS.

Disclaimer (provided with this information by the compiling agencies):
This information is formulated for use by elements of the Department
of Defense. The United States of America in no manner whatsoever,
expressly or implied, warrants this information to be accurate and
disclaims all liability for its use. Any person utilizing this
document should seek competent professional advice to verify and
assume responsibility for the suitability
of this information to their
particular situation.