

J C ENTERPRISES INC -- 1000, LUBRICATING OIL, WATCH -- 9150-00-252-6382

=====
Product Identification
=====

Product ID:1000, LUBRICATING OIL, WATCH

MSDS Date:05/01/1994

FSC:9150

NIIN:00-252-6382

MSDS Number: BLJGT

=== Responsible Party ===

Company Name:J C ENTERPRISES INC

Address:724 WESTCLIFF RD

Box:7345

City:WILMINGTON

State:DE

ZIP:19803-1712

Country:US

Info Phone Num:302-478-8326

Emergency Phon

e Num:302-478-8326

Preparer's Name:VERNON C. WOLFF

CAGE:2S598

=== Contractor Identification ===

Company Name:J C ENTERPRISES INC

Address:724 WESTCLIFF RD

Box:7345

City:WILMINGTON

State:DE

ZIP:19803-1712

Country:US

Phone:302-478-8326

CAGE:2S598

=====
Composition/Information on Ingredients
=====

Ingred Name:PER MSDS HAZ INGRED-NONE.

Fraction by Wt: 100%

Other REC Limits:NONE SPECIFIED

=====
Hazards Identification
=====

Routes of Entry: Inhala

tion:NO Skin:YES Ingestion:NO
Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO
Health Hazards Acute and Chronic:SKIN:AVOID PROLONGED EXPOSURE.
INHALATION:LOW HAZARD. INGESTION:EXPECTED LOW. HEALTH HAZARD
(ACUTE/CHRONIC):NOT ESTABLISHED.
Effects of Overexposure:NOT DETERMINED.
Medical Cond Aggravated by Exposure:NOT DETERMINED

=====
First Aid Measures
=====

First Aid:GET MEDICAL ATTENTION IF NEEDED. INHALATION/INGESTION:NONE
SHOULD BE NEEDED
D. EYES:IMMEDIATELY FLUSH WITH WATER FOR 15 MINUTES.
SKIN:FLUSH WITH WATER.

=====
Fire Fighting Measures
=====

Flash Point Method:TCC
Flash Point:392F,200C
Extinguishing Media:WATER SPRAY, CARBON DIOXIDE, DRY CHEMICAL.
Fire Fighting Procedures:WEAR SELF-CONTAINED BREATHING APPARATUS AND
PROTECTIVE CLOTHING.
Unusual Fire/Explosion Hazard:NONE

=====
Accidental Release Measures
=====

Spill Release Procedures:ABSORB WITH INERT
ABSORBENT MATERIAL SUCH AS
VERMICULITE AND PLACE IN IMPERVIOUS CONTAINER.
Neutralizing Agent:NOT APPLICABLE.

=====
Handling and Storage
=====

Handling and Storage Precautions:WEAR SAFETY GLASSES AND GLOVES.
Other Precautions:KEEP FROM CONTACT WITH STRONG OXIDIZING MATERIALS.

=====
Exposure Controls/Personal Protection
=====

Respiratory Protection:NONE. WEAR NIOSH-APPROVED SELF CONTAINED
BREATHING APPARATUS IF MISTS/VAPORS ARE HIGH

Ventilation:GOOD VENTILATION SHOULD BE SUFFICIENT.
Protective Gloves:STANDARD CHEMICAL OPERATION GLOVES.
Eye Protection:SAFETY GLASSES
Other Protective Equipment:NONE.
Work Hygienic Practices:WASH HANDS AFTER HANDLING PRODUCT.
Supplemental Safety and Health

===== Physical/Chemical Properties =====

HCC:V6
Boiling Pt:B.P. Text:752F,400C
Vapor Pres:1.5 @ 185C
Vapor Density:1.06
Spec Gravity:1.0
Evaporation Rate & Reference:NEGL (N-BUTYL ACETATE=1)
Solubility in Water:NONE
Appearance and Odor:COLORLESS TO YELLOW LIQUID, SLIGHT WOOD ODOR

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES
STRONG OXIDIZERS
Stability Condition to Avoid:DIRECT FLAME
Hazardous Decomposition Products:COMBUSTION WILL PRODUCE CARBON DIOXIDE
AND WATER.

===== Disposal Considerations =====

Waste Disposal Methods:DISPOSE BY INCINERATION OR CONTRACT WITH
LICENSED CHEMICAL WASTE DISPOSAL AGENCY. DISCHARGE OR TREATMENT MAY
BE SUBJECT TO FEDERAL, STATE AND LOCAL LAWS AND REGULATIONS.

Disclaimer (provided with this information by the compiling agencies):
This information is formulated for use by elements of the Department
of Defense. The United States of America in no manner whatsoever,
expressly or implied, warrants this information to be accurate and
disclaims all liability for its use. Any person utilizing this
document should seek competent professional advice

to verify and
assume responsibility for the suitability of this information to their
particular situation.