

NILES CHEMICAL PAINT CO -- N-1301A AIRCRAFT RED 31136 -- 8010-01-144-9873

=====
Product Identification
=====

Product ID:N-1301A AIRCRAFT RED 31136

MSDS Date:10/06/1991

FSC:8010

NIIN:01-144-9873

Kit Part:Y

MSDS Number: BLJNF

=== Responsible Party ===

Company Name:NILES CHEMICAL PAINT CO

Address:225 FORT STREET

Box:307

City:NILES

State:MI

ZIP:49120

Country:US

Info Phone Num:616-683-3377

Emergency Ph

one Num:219-236-5956

Preparer's Name:MIKE LICHATOWICH

CAGE:02388

=== Contractor Identification ===

Company Name:NILES CHEMICAL PAINT

Address:225 FORT STREET

Box:307

City:NILES

State:MI

ZIP:49120

Country:US

Phone:616-683-3377/219-236-5856

CAGE:02388

=====
Composition/Information on Ingredients
=====

Ingred Name:METHYL ETHYL KETONE (SARA III) (VAPOR PRESSURE 71.2 MM @ 20
C)

CAS:78-93-3

RTECS #:EL6475000

Fraction by Wt: 16%

Other REC Limits:NONE SPECIFIED

OSHA PEL:200 PPM

AC

GIH TLV:200 PPM/300 PPM STEL
EPA Rpt Qty:5000 LBS
DOT Rpt Qty:5000 LBS

Ingred Name:POLYESTER RESIN
Fraction by Wt: 13%
Other REC Limits:NONE SPECIFIED

Ingred Name:BARIUM SULFATE
CAS:7727-43-7
RTECS #:CR0600000
Fraction by Wt: 12%
Other REC Limits:NONE SPECIFIED
OSHA PEL:15 MG/M3 TDUST
ACGIH TLV:10 MG/M3 TDUST; 9293

Ingred Name:PM ACETATE (VAPOR PRESSURE 3.7 MM @ 20 C)
CAS:108-65-6
RTECS #:AI8925000
Fraction by Wt: 12%
Other REC Limits:NONE SPECIFIED

Ingred Name:BUTYL ACETATE (SARA III) (VAPOR PRESSURE 10 MM @ 20 C)
CAS:123-86-4
RTECS #:AF7350000
Fraction by Wt: 10%
Other REC Limits:NONE SPECIFIED
OSHA PEL:150 PPM
ACGIH TLV:150 PPM/200 PPM STEL
EPA Rpt Qty:5000 LBS
DOT Rpt Qty:5000 LBS

Ingred Name:PROPRIETARY INGREDIENTS (MFR STATES UNIDENTIFIED INGREDIENTS ARE NOT CONSIDERED HAZARDOUS UNDER FED HAZARD COMM REGULATIONS)
Fraction by Wt: BALANCE
Other REC Limits:NONE SPECIFIED

Ingred Name:VOC: 4.59 LBS/GAL.
RTECS #:9999999VO
Other REC Limits:NONE SPECIFIED

===== H

azards Identification =====

Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES
Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO
Health Hazards Acute and Chronic:EYES: SEVERE IRRITATION, LACRIMATION.
SKIN: IRRITATION, DEFATTING & DERMATITIS. INHALATION: NASAL &
RESPIRATORY IRRITATION, CNS DEPRESSION. INGESTION: GASTROINTESTINAL
IRRITATION. TARGET ORGANS: EYES, SKIN, RESPIRATORY SYSTEM, CNS,
LUNGS.

Explanation of Carcinogenicity:NOT LISTED BY NTP, IARC,
OR OSHA.

Effects of Overexposure:EYES: REDNESS, BLURRED VISION. SKIN: REDNESS.
INHALATION: CNS: DIZZINESS, DROWSINESS, WEAKNESS, FATIGUE,
CONFUSION. NAUSEA, HEADACHE, VERTIGO, POSSIBLE UNCONSCIOUSNESS,
ASPHYXIATION. INGESTION: ABDOMINAL PAIN, NAUSEA, VOMITING,
DIARRHEA.

Medical Cond Aggravated by Exposure:NONE KNOWN.

===== First Aid Measures =====

First Aid:INHALATION: MOVE TO FRESH AIR IMMED. IF BREATH STOPPED, GIVE
ARTIF RESP. GET MED AID ASAP. SKIN: IMMED FLUSH W/WATER. IF CLOTH
CONTAM, REMOVE & FLUSH SKIN W/WATER. GET MED AID. WASH
CLOTH/DECONTAM SHOES BEFORE REUSE. EYE: IMMED FLUSH W/WATER 15
MIN, OCCAS LIFT EYELIDS. GET MED AID IMMED. INGEST: DRINK 1-2
GLASSES WATER. DON'T INDUCE VOMIT. SEE DR/POISON CNTRL CTR IMMED.
TREAT SYMPTOMATICALLY.

===== Fire Fighting Measures =====

Flash Point Method:TCC
Flash Point:20.0F,-6.7C
Lower Limits:1.3
Upper Limits:10.0
Extinguishing Media:DRY CHEMICAL, FOAM, CO2.
Fire Fighting Procedures:WEAR SCBA W/FULL FACEPIECE (POS PRESSURE MODE)
FULL PROTECT CLOTH. WATER MAY BE USED TO COOL CLSD CNTNRS TO
PREVENT PRESSURE BLDUP/AUTO IGNIT/EXPLOSION W/HEAT.
Unusual Fire/Explosion Hazard:VAPOR HEAVY, MAY TRAVEL TOIGNIT SOURCE.
CNTNR EXPLODE W/HEAT. KEEP FROM HEAT/IGN SOURCE. APPL TO HOT SRFCS
REQUIRES SPCL PRECAUTIONS. DECOMP PROD ARE HLTH HZD.

===== Accidental Release Measures =====

S

Spill Release Procedures:SMALL: ELIM IGNIT SOURCE. DON'T BREATHE/AVOID SKIN CONTACT. ABSORB W/INERT MAT'L. RECLAIM LIQ/ABSORB INTO RECOVERY/SALVAGE DRUMS. LRG: ELIM IGNIT SOURCE. DON'T BREATHE/AVOID SKIN CONTACT. DIKE. RECLAIM INTO RECOVERY/SALVAGE DRUMS/TANK TRUCK-DISPOSAL.

==== Handling and Storage =====

Handling and Storage Precautions:AVOID STORAGE IN HIGH TEMPERATURE AREAS OR NEAR FIRE OR OPEN FLAME. KEEP CONTAINERS TIGHTLY CLOSED

WHEN NOT IN USE. AVOID ROUGH HANDLING.

Other Precautions:CONTAINERS OF THIS MATERIAL MAY BE HAZARDOUS WHEN EMPTY. DO NOT WELD OR FLAME CUT ON EMPTY DRUMS.

==== Exposure Controls/Personal Protection =====

Respiratory Protection:WEAR (TC-23C-75) FITTED HALF-MASK/FULL FACEPIECE RESPIRATOR (NIOSH/MSHA) DURING & AFTER APPLICATION UNLESS AIR MONITORING DEMONSTRATES VAPOR/MIST LEVELS ARE BELOW APPLICABLE LIMITS. FOLLOW RESPIRATOR MANUFACTURER'S DIRECTION FOR USE.

V

ventilation:PROVIDE SUFF VENT (VOL/PATTRN)-KEEP AIR CONC BELOW TLV/PEL. REMOVE DECOMP PROD (WELD/FLAME CUT). VENT VAPOR FROM BAKING.

Protective Gloves:NITRILE, OR VITON GLOVES.

Eye Protection:CHEM GOGGLES, SAFETY GLASSES, FACE SHLD

Other Protective Equipment:WEAR CHEM RESISTANT (NITRILE, VITON) CLOTHING AS NEEDED TO PREVENT SKIN CONTACT. DON'T WEAR CONTACT LENSES.

Work Hygienic Practices:REMOVE CLOTH THAT BECOMES WET, WASH BEFORE REUSE. WASH HANDS BEFORE EATING, SMOKING, OR USING RESTROOM.

Supplemental Safety and Health

==== Physical/Chemical Properties =====

Boiling Pt:B.P. Text:175 TO 302F

Vapor Density:> AIR

Spec Gravity:11.20 LBS/GAL

Viscosity:70-85 KU

Evaporation Rate & Reference:SLOWER THAN ETHER.

Solubility in Water:SLIGHT.

Appearance and Odor:LIQUID, ODOR OF SOLVENT.

Percent Volatiles by Volume:64.19

==== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES

NITRATES, STRONG

OXIDIZERS, ALKALIES, ACIDS.

Stability Condition to Avoid:HIGH TEMPERATURES, SHOCK FROM DROPPING.

Hazardous Decomposition Products:CAN PRODUCE CARBON MONOXIDE AND/OR CARBON DIOXIDE.

===== Disposal Considerations =====

Waste Disposal Methods:DISPOSE OF IN ACCORDANCE WITH APPLICABLE LOCAL, STATE AND FEDERAL REGULATIONS. D001.

Disclaimer (provided with this information by the compiling agencies):

This information is formulated for use by elements of the D

epartment

of Defense. The United States of America in no manner whatsoever,

expressly or implied, warrants this information to be accurate and

disclaims all liability for its use. Any person utilizing this

document should seek competent professional advice to verify and

assume responsibility for the suitability of this information to their

particular situation.