

N/P -- PSI-601 CLEAR SILICONE SEALANT -- 8040-01-331-7469

Product ID:PSI-601 CLEAR SILICONE SEALANT

MSDS Date:01/01/1987

FSC:8040

NIIN:01-331-7469

MSDS Number: BLJQX

=== Responsible Party ===

CAGE:0KND3

=== Contractor Identification ===

Company Name:POLYMERIC SYSTEMS, INC.

Address:723 WHEATLAND STREET

Box:City:PHOENIXVILLE

State:PA

ZIP:19460

Country:US

Phone:610-935-1170

CAGE:0KND3

=====
Composition/Information on Ingredients
=====

Ingred Name:METHYL TRIACETOXY SILANE

CAS:4253-34-3

RTECS #:VV4500000

Fraction by Wt: 2-6%

Other REC Limits:NONE SPECIFIED

OSHA PEL:NIF

ACGIH TLV:NIF

Ingred Name:ETHYLTRIACETOXYSILANE

CAS:17689-77-9

Fraction by Wt: 2-6%

Other REC Limits:NONE SPECIFIED

OSHA PEL:NIF

ACGIH TLV:NIF

Ingred Name:DIHYDROXYPOLYDIMETHYLSILOXANE

CAS:70131-67-8

Other REC Limits:NONE SPECIFIED

OSHA PEL:NIF

ACGIH TLV:NIF

Ingred Name:POLYDIMETHYLSILOXANE FLUID

CAS:63148-62-9

Other REC Limits:NONE SPECI

FIED
OSHA PEL:NIF
ACGIH TLV:NIF

Ingred Name:AMORPHOUS SILICA, FUMED
CAS:112945-52-5
RTECS #:VV7310000
Other REC Limits:NONE SPECIFIED
OSHA PEL:80 MG/M3
ACGIH TLV:NIF

Ingred Name:VOC: 0.4 LB/GL; 40 GRAMS/LITER
RTECS #:9999999VO
Other REC Limits:NONE SPECIFIED

===== Hazards Identification =====

Health Hazards Acute and Chronic:ACUTE: SEVERE IRRITATION TO
RESPIRATORY TRACT, PULMONARY EDEMA, EYE LACRIMATION, CORNEAL EDEMA;
SKIN IRRITATION AND DERMATITIS.
CHRONIC: BRONCHITIS, LARYNGITIS,
DERMATITIS, CONJUNCTIVITIS.

Explanation of Carcinogenicity:NOT CARCINOGENIC.

Effects of Overexposure:IRRITATION TO SKIN, EYES AND MUCOUS MEMBRANES.

MAY CAUSE DISCOMFORT, TEARING, CHOKING OR BURNING SENSATION.

Medical Cond Aggravated by Exposure:RESPIRATORY, SKIN OR EYE DISEASES.

===== First Aid Measures =====

First Aid:REMOVE TO FRESH AIR. WASH SKIN WITH SOAP AND WATER. FLUSH
EYES WITH WATER FOR AT LEAST 15 MIN
UTES.

===== Fire Fighting Measures =====

Flash Point:>400F,>204C; CC

===== Accidental Release Measures =====

Spill Release Procedures:MATERIAL RELEASES ACETIC ACID ON EXPOSURE TO
AIR. PROVIDE ADEQUATE VENTILATION DURING CLEAN UP. TRANSFER TO A
WASTE CONTAINER. LET CURE TO SOLID RUBBER, ALLOWING ALL LIBERATED
ACETIC ACID TO DISSIPATE .

Neutralizing Agent:AQUEOUS SODIUM BICARBONATE

===== Handling and St

orage =====

Handling and Storage Precautions:AVOID PROLONGED CONTACT WITH MOISTURE DURING STORAGE.

Other Precautions:AVOID PROLONGED SKIN CONTACT. LIBERATED ACETIC ACID VAPORS CAUSE IRRITATION TO SKIN, EYES AND BRONCHIAL TISSUES. DO NOT INGEST.

===== Exposure Controls/Personal Protection =====

Respiratory Protection:IF USED IN A CLOSED SPACE WHERE VENTILATION IS INADEQUATE USE A CHEMICAL CARTRIDGE RESPIRATOR WITH FULL FACE PIECE AND ORGA

NIC VAPOR CARTRIDGE(S) (NIOSH/MSHA APPROVED) TO PROTECT AGAINST ACETIC ACID V APORS.

Ventilation:RECOMMENDED 10 AIR CHANGES PER HOUR.

Protective Gloves:DISPOSIBLE PLASTIC GLOVES

Eye Protection:SAFETY GLASSES

Work Hygienic Practices:WASH BEFORE EATING, DRINKING, OR SMOKING. DO NOT RUB EYES WHILE WORKING WITH SEALANT.

Supplemental Safety and Health

===== Physical/Chemical Properties =====

Viscosity:**

===== Stability and Reactivity Data =====

=====

Hazardous Decomposition Products:ACETIC ACID FROM MOISTURE CONTACT. CO AND VOLATILE ORGANICS AND SILICA AEROSOLS FROM THERMAL DEGRADATION.

===== Disposal Considerations =====

Waste Disposal Methods:NOT AN EPA HAZARDOUS WASTE. DISPOSE OF IN ACCORDANCE WITH APPROPRIATE GOVERNMENTAL REGULATIONS.

Disclaimer (provided with this information by the compiling agencies):
This information is formulated for use by elements of the Department of Defens

e. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.