

ALOX CORP -- ALOX 2028C -- 8030-00-213-3279

=====  
Product Identification  
=====

Product ID:ALOX 2028C

MSDS Date:12/09/1988

FSC:8030

NIIN:00-213-3279

MSDS Number: BLJSK

=== Responsible Party ===

Company Name:ALOX CORP

Address:3943 BUFFALO AVE

Box:517

City:NIAGARA FALLS

State:NY

ZIP:14302

Country:US

Info Phone Num:(716)282-1295

Emergency Phone Num:(716)282-1295

CAGE:60773

=== Contractor Identificati

on ===

Company Name:ALOX CORP

Address:3943 BUFFALO AVE

Box:517

City:NIAGARA FALLS

State:NY

ZIP:14302

Country:US

Phone:716-282-1295

CAGE:60773

Company Name:STEVEN INDUSTRIES

Address:39 AVENUE C

Box:8

City:BAYONNE

State:NJ

ZIP:07002-3417

Country:US

Phone:201-437-6501

CAGE:33150

=====  
Composition/Information on Ingredients  
=====

Ingred Name:ALIPHATIC MINERAL SPIRITS

CAS:64475-85-0

RTECS #:PY8240000

Fraction by Wt: 50%

Other REC Limits:NONE SPECIFIED

ACGIH TLV:100 PPM

=====

=====  
===== Hazards Identification =====  
=====

Routes of Entry: Inhalation:YES Skin:NO Ingestion:YES  
Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO  
Health Hazards Acute and Chronic:HARMFUL IF INHALED. CAUSES IRRITATION.  
REPORTS HAVE ASSOCIATED REPEATED & PROLONGED OCCUPATIONAL  
OVEREXPOSURE TO SOLVENTS WITH PERMANENT BRAIN & NERVOUS SYSTEM  
DAMAGE. INTENTIONAL MISUSE BY DELIBERATE LY CONCENTRATING &  
INHALING THE CONTENTS MAY BE HARMFUL OR FATAL.

Effects of Over

exposure:INHALATION: NAUSEA, DIZZINESS, IRRITATION OF  
NOSE AND THROAT, WATERING OF EYES. SKIN: CONTACT WITH HEATED  
MATERIAL MAY CAUSE THERMAL BURNS, REPEATED OR PROLONGED CONTACT MAY  
CAUSE DEFATTING, OIL ACNE, IRRITATION OR ALLERGIC REACTION IN  
SENSIIVE INDIVIDUALS. INGESTION: IRRITATION, VOMITING, DIARRHEA,  
NAUSEA.

=====  
===== First Aid Measures =====  
=====

First Aid:INHALATION: REMOVE TO FRESH AIR, TREAT SYMPTOMS-ADMINISTER  
OXYGEN IF BREATHIN  
G IS IMPAIRED. EYES: FLUSH WITH WATER FOR AT  
LEAST 15 MINUTES, CONSULT DR. SKIN: WASH WITH SOAP & WATER TREAT  
BURNS FROM HO T MATERIAL AS THERMAL BURNS. INGESTION:DO NOT INDUCE  
VOMITING-CONSULT DR.

=====  
===== Fire Fighting Measures =====  
=====

Flash Point Method:TOC  
Flash Point:142 F (61C)  
Extinguishing Media:DRY CHEMICAL, CARBON DIOXIDE, WATER FOG.  
Fire Fighting Procedures:HANDLE AS PETROLEUM PRODUCT (I.E. DO NOT USE  
WATER EXCEPT AS FOG OR TO COOL CONTAI  
NERS OR TO FLUSH AWAY SPILLS).  
Unusual Fire/Explosion Hazard:SAME AS PETROLEUM PRODUCT (I.E. WATER  
STREAMS ON BURNING MATERIAL MAY SPREAD FIRE).

=====  
===== Accidental Release Measures =====  
=====

Spill Release Procedures:ATTEMPT TO RECOVER. KEEP PETROLEUM PRODUCTS  
OUT OF STREAMS AND WATERWAYS - FOLLOW SARA SECTION 313

=====  
===== Handling and Storage =====  
=====

Handling and Storage Precautions:AVOID PROLONGED OR REPEATED CONTACT,  
KEEP CONT

AINERS CLOSED WHEN NOT IN USE.

Other Precautions:IF INGESTION & VOMITING OCCURS, MONITOR PATIENT FOR 48 HOURS FOR BREATHING DIFFICULTIES.

===== Exposure Controls/Personal Protection =====

Respiratory Protection:IF VAPORS OR MIST ARE GENERATED USE APPROPRIATE MASK FOR BREATHING DIFFICULTIES.

Ventilation:LOCAL EXHAUST PREFERRED IF VAPORS OR MIST IS GENERATED.

Protective Gloves:OIL IMPERVIOUS IF CONTACT IS ANTICIPATED

Eye Protection:SAFETY GLASSES

Other Protective Equipm

ent:AS NEEDED TO PROTECT AGAINST HOT PRODUCT OR PROTECT AGAINST REPEATED OR PROLONGED CONTACT.

Work Hygienic Practices:AVOID REPEATED OR PROLONGED CONTACT-WASH BEFORE EATING, SMOKING OR USING TOILET. LAUNDER SATURATED CLOTHING BEFORE REUSE

Supplemental Safety and Health

===== Physical/Chemical Properties =====

HCC:V4

Boiling Pt:B.P. Text:>150

Vapor Pres:1

Spec Gravity:0.86 @60F

Evaporation Rate & Reference: