View NSN Online: https://aerobasegroup.ae/nsn/6830-00-290-4377

ALLIED CORPORATION, CHEMICAL SECTOR -- DICHLORODIFLUOROMETHANE -- 6830-00-290-4377

Product ID: DICHLORODIFLUOROMETHANE MSDS Date:08/01/1985 FSC:6830 NIIN:00-290-4377 MSDS Number: BLKXV === Responsible Party === Company Name: ALLIED CORPORATION, CHEMICAL SECTOR Box:1139R City:MORRISTOWN State:NJ ZIP:07960 Country:US Info Phone Num:201-455-4157 **Emergency Phone Num:20** 1-455-2000 CAGE:OLYW2 === Contractor Identification === Company Name: ALLIED CORPORATION, CHEMICAL SECTOR Box:1139R City:MORRISTOWN State:NJ ZIP:07960 Country:US Phone:201-455-2000 CAGE:OLYW2 Company Name: HONEYWELL INTL INC ENVIRONMENTAL SYSTEMS AND SERVICES Address:101 COLUMBIA RD Box:City:MORRISTOWN State:NJ ZIP:07962 Country:US Phone:973-455-3922 CAGE:70308 Company Name: PHOENIX DISTRIBUTORS CAGE:PHOEN

Ingred Name:DICHLORODI

FLUOROMETHANE (SARA III) CAS:75-71-8 RTECS #:PA8200000 Fraction by Wt: 100% Other REC Limits:NONE SPECIFIED OSHA PEL:1000 PPM ACGIH TLV:1000 PPM; 9192 EPA Rpt Qty:5000 LBS DOT Rpt Qty:5000 LBS **Ozone Depleting Chemical:1** Routes of Entry: Inhalation:YES Skin:YES Ingestion:NO Health Hazards Acute and Chronic: INHALATION: THIS MATERIAL IS LOW IN TOXICITY AT CONCENTRATIONS AS HIGH AS 4% (40,000 PPM). WHEN OXYGEN LEVELS I N AIR ARE REDUCED TO 12-14%, SYMPTOMS OF ASPHYXIATION WILL OCCUR; LOSS OF COORDINATION, I NCREASED PULSE RATE, CARDIAC SENSITIZATION & DEEPER RESPIRATION ARE ALSO POSSIBLE. INGESTION: NOT APPLICABLE SINCE Effects of Overexposure: MATERIAL IS GASEOUS AT NORMAL TEMPERATURE & PRESSURE. SKIN: CONTACT W/LIQUID MATERIAL CAN CAUSE FROSTBITE, INDICATED BY PALLOR OR REDNESS, LOSS OF SENSATION & SWELLING. EYES: SAME AS FOR SKIN. Medical Cond Aggravated by Exposure:WORKERS WITH CARDI **OVASCULAR OR** PULMONARY PROBLEMS SHOULD HAVE MEDICAL EVALUATION BEFORE EXPOSURE.

First Aid:INHALE: REMOVE IMMED TO FRESH AIR. BREATHING STOPPED, GIVE CPR, PREFERABLY MOUTH-TO-MOUTH. USE OXYGEN AS REQUIRED, PROVIDED A QUALIFIED OPERATOR IS AVAILABLE. DO NOT GIVE EPINEPHRINE. SKIN/ EYE: IMMED IATELY BATHE ANY FROSTBITE (DO NOT RUB)W/LUKEWARM (NOT HOT) WATER. IN THE ABSENCE OF WATER, COVER W/SOFT WOOL OR OTHER

SUITABLE MAT'L. CONTACT PHYSICIAN FOR LOW TEMP BURNS FROM LIQUID CONTACT.

Flash Point:NA

Extinguishing Media: ANY STANDARD AGENT-CHOOSE ONE THAT IS APPROPRITE FOR TYPE OF FIRE. MATERIAL ITSELF IS NONFLAMMABLE.
Fire Fighting Procedures: FIREFIGHTERS WEAR NIOSH APPROVED SCBA FOR PROTECTION AGAINST SUFFOCATION & POSS TOXIC DECOMP PRODUCTS. USE WATER SPRAY TO KEEP FIRE-EXPOSED CONTAINERS COOL.
Unusual Fire/Expl osion Hazard:MAT'L IS LIQUID & GAS UNDER ITS OWN VAPOR PRESS. WHILE NOT COMBUSTIBLE ITSELF, CONTACT W/CERTAIN METALS MAY PRODUCE EXOTHERMIC REACTIONS OR EXPLOS COMBINATIONS.

Spill Release Procedures: USING A SELF-CONTAINED AIR SUPPLY AND PROTECTION AGAINST FROSTBITE, PERONNEL SHOULD ATTEMPT TO CLOSE VALVES OR REPAIR SOURCE OF LEAK. IF A LARGE QUANTITY IS RELEASED, EVACUATE PERSONNEL AND ALLOW TO D ISSIPATE.

Handling and Storage Precautions: AVOID CONTACT WITH EYE, SKIN OR CLOTHING. DO NOT PUNCTURE OR DROP CYLINDERS OR EXPOSE THEM TO OPEN FLAME/EXCESS HEAT. USE AUTHORIZED CONTAINERS ONLY.
Other Precautions: STORE IN COOL, DRY, WELL-VENT AREA AWAY FROM HEAT, FLAME OR COMBUSTIBLES. PROTECT CYLINDER & ITS FITTINGS FROM PHYSICAL DAMAGE. STORAGE IN SUBSURFACE LOCATIONS SHOULD BE AVOIDED. FOLLOW STANDARD SAFET Y PRECAU
TIONS.

Respiratory Protection:NONE GENERALLY REQUIRED FOR ADEQUATELY-VENTED SITUATIONS. FOR UNUSUAL SITUATIONS, WEAR A NIOSH-APPROVED, SUPPLIED-AIR RESPIRATOR OR A POSITIVE PRESSURE, SCBA.

Ventilation:USE VENTILATION ADEQUATE TO MEET TLV REQUIREMENTS & MINIMIZE EXPOSURE. SEE SUPPLEMENTAL DATA FOR MORE INFORMATION. Protective Gloves:IMPERV GLOVES W/PVA OUTER LAYER,NEOPRENE Eye Protection:CHEM SAFETY GOGGLES. NO CONT ACT LENSES.

Other Protective Equipment:WEAR IMPERV SHOES & CLOTHING WHERE LEAKAGE IS PROBABLE. THERMALLY INSULATE GLOVES, CLOTH & SHOES TO PREVENT FROSTBITE.

Supplemental Safety and Health

VENTILATION: PROVIDE LOCAL EXHAUST AT FILLING ZONES & WHERE LEAKAGE IS PROBABLE. MECHANICAL(GENERAL) VENTILATION IS ADEQUATE FOR OTHER OPERATING AREAS & FOR STORAGE AREAS. PROVIDE CONVENIENT WATER SOU RCE FOR FIRST-AID TREATMENT IN CASE OF FROSTBITE. EPA "HZDS WASTE", IF DISCARDED, UNUS ED-U075.

HCC:G3 Boiling Pt:B.P. Text:-22F,-30C Melt/Freeze Pt:M.P/F.P Text:-252F,-158C Vapor Pres:85 PSIA @ Vapor Density:4.26 Spec Gravity:.325 Evaporation Rate & amp; Reference:21.1 C Solubility in Water:0.028 @ 77 F Appearance and Odor:COLORLESS LIQUIFIED GAS WITH FAINT ETHEREAL ODOR.

Stability Indicator/Materials to Avoid:YES
ALUM IN THE FORM OF FRESHLY
ABRADED SRFC-POWDERED ALUM, MAGNESIUM PWDR, ZINC PWDR, CHEM ACTIVE METALS-SODIUM, POTASSIUM.
Stability Condition to Avoid:LIGHTED CIGARETTES, HOT SPOTS, WELDING. TEMPERATURES ABOVE 550 C. DECOMPOSES IN FIRES.
Hazardous Decomposition Products:HALOGENS, HALOGEN ACIDS & POSSIBLY CARBONYL HALIDES, SUCH AS PHOSGENE.

Waste Disposal Methods:DISPOSE OF WASTE GENETRON 12 DICHLORODIFLUOROMETHANE PER FEDERAL REGS. USERS R EVIEW OPERATIONS,

THEN CONSULT W/APPROP REGULATORY AGENCIES BEFORE DISCHARGING OR DISPOSING OF WASTE MAT'L. DISPOSAL BY LI CENSED WASTE DISPOSAL COMPANY MAY BE NECESSARY.

Disclaimer (provided with this information by the compiling agencies): This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use.

Any person utilizing this

document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.