

EPOXY TECHNOLOGY -- EPO TEK 920, PART B -- 8040-01-151-4256

=====
Product Identification
=====

Product ID:EPO TEK 920, PART B

MSDS Date:04/20/1989

FSC:8040

NIIN:01-151-4256

Kit Part:Y

MSDS Number: BLLDX

=== Responsible Party ===

Company Name:EPOXY TECHNOLOGY

Address:14 FORTUNE DRIVE

City:BILLERICA

State:MA

ZIP:01821

Country:US

Info Phone Num:508-667-3805

Emergency Phone Num:508-667-3805

CAGE:3324

6

=== Contractor Identification ===

Company Name:EPOXY TECHNOLOGY

Address:14 FORTUNE DRIVE

Box:City:BILLERICA

State:MA

ZIP:01821

Country:US

Phone:978-667-3805

CAGE:33246

=====
Composition/Information on Ingredients
=====

Ingred Name:NON-HAZARDOUS INGREDIENTS

Other REC Limits:NONE SPECIFIED

=====
Hazards Identification
=====

Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES

Health Hazards Acute and Chronic:INGESTION: CONTAINS MATERIAL

S THAT MAY

BE MODERATELY TOXIC. INGESTION CAN SEVERELY UPSET THE GASTRIC SYSTEM. INHALATION: HOT VAPORS CAN CAUSE HEADACHES, NAUSEA, DIZZINESS, RESPIRATORY IRRITATION. SKIN : MAY CAUSE DERMATITIS. EYE: IRRITATING TO THE EYES. CAN CAUSE INJURY. CHRONIC: MAY CAUSE DERMATITIS AND SENSITIZATION.

=====
===== First Aid Measures =====

First Aid: EYE CONTACT: IN CASE OF EYE CONTACT, FLUSH WELL WITH WATER AND CONSULT MEDICAL PROFESSIONAL. SKIN CONTACT: IN CASE OF SKIN CONTACT, CLEAN WITH SOAP AND WATER. DO NOT USE SOLVENTS. INGESTION: IF SWALLOWED, DILUTE WITH WATER OR MILK. CONTACT MEDICAL PROFESSIONAL. INHALATION: CAN BE IRRITATING TO RESPIRATORY TRACT. THIS TYPE OF EXPOSURE IS AVOIDABLE WITH ADEQUATE VENTILATION.

=====
===== Fire Fighting Measures =====

Flash Point: >200F, >93C
Extinguishing Media: DRY CHEMICAL, FOAM, CARBON DIOXIDE.
Fire Fighting Procedures: WEAR SELF-CONTAINED BREATHING APPARATUS & COMPLETE PERSONAL PROTECTIVE EQUIPMENT. REMOVE ALL IGNITION SOURCES. USE WATER SPRAY TO COOL FIRE EXPOSED CONTAINERS.
Unusual Fire/Explosion Hazard: AVOID FUMES LIBERATED BY HEAT.

=====
===== Accidental Release Measures =====

Spill Release Procedures: ELIMINATE IGNITION SOURCES. USE EYE AND SKIN PROTECTION. PLACE LEAKING CONTAINERS IN A WELL-VENTILATED AREA. ABSORB SPILLAGE WITH INERT MATERIAL AND DISPOSE.

=====
===== Handling and Storage

Handling and Storage Precautions: AVOID CONTACT WITH SKIN & EYES. AVOID BREATHING VAPORS. KEEP CONTAINERS CLOSED WHEN NOT IN USE. REMOVE ALL CONTAMINATED CLOTHING IMMEDIATELY & WASH.
Other Precautions: WASH SKIN THOROUGHLY WITH SOAP AND WATER AFTER HANDLING. SOLVENTS SHOULD NOT BE USED TO CLEAN SKIN BECAUSE OF INCREASED PENETRATION POTENTIAL-PROTECTIVE SKIN OILS CAN BE DISSOLVED BY SOLVENTS.

=====
===== Exposure Controls/Personal Protection =====

=====

Respiratory Protection:WEAR AN APPROVED RESPIRATOR WHENEVER HIGH LEVEL EXPOSURE TO VAPORS OR MIST IS ANTICIPATED.

Ventilation:LOCAL EXHAUST RECOMMENDED FOR EXPOSURE CONTROL.

Protective Gloves:IMPERVIOUS GLOVES-NEOPRENE OR EQUIVALENT

Eye Protection:CHEMICAL SPLASH GOGGLES RECOMMENDED

Other Protective Equipment:FACE SHIELD & IMPERVIOUS APRON. A SAFETY SHOWER & EYE WASH FACILITY SHOULD BE AVAIL. BARRIER CREAM & GLOVES RECOMMENDED.

Supplemental Safety and Health

=====

= Physical/Chemical Properties =====

Vapor Density:> AIR

Evaporation Rate & Reference: