View NSN Online: https://aerobasegroup.ae/nsn/5895-00-476-4443

LITTON ELECTRON DEVICES -- L2806A TRAVELING WAVE TUBE BAND 3 W/ALNICO MAGNETS -- 5865-00-476-4443

============= Product Identification ==================

Product ID:L2806A TRAVELING WAVE TUBE BAND 3 W/ALNICO MAGNETS

MSDS Date:04/15/1989

FSC:5865

NIIN:00-476-4443

MSDS Number: BLRDQ === Responsible Party ===

Company Name: LITTON ELECTRON DEVICES

Address:960 INDUSTRIAL RD

City:SAN CARLOS

State:CA ZIP:94070

Info Phone Num: (415) 591-8411

Emergency Phone Num: (415) 591-8411

CAGE:FO469

=== Contractor Identification ===

Company Name: LITTON ELECTRON DEVICES

Address:960 INDUSTRIAL RD

City:SAN CARLOS

State:CA ZIP:94070 Country:US

Phone:415-591-8411

CAGE:FO469

Company Name: LITTON ELECTRON DEVICES .

Address:960 INDUSTRIAL RD

Box: City: SAN CARLOS

State:CA ZIP:94070 Country:US

Phone:650-591-8411

CAGE:80080

======= Composition/Information on Ingredients ========

Ingred Name: ALUMINUM (SARA III)

CAS:7429-90-5

**RTE** 

CS #:BD0330000

OSHA PEL:15MG/M3 DUST/5 FUME ACGIH TLV:10MG/M3 DUST; 9192

Ingred Name: NICKEL (SARA III)

CAS:7440-02-0

RTECS #:QR5950000

Other REC Limits: 1 MG/CUM

OSHA PEL:1 MG/M3

ACGIH TLV:1 MG/M3; 9192

Ingred Name: COBALT (SARA III)

CAS:7440-48-4

RTECS #:GF8750000

Other REC Limits:0.05 PPM OSHA PEL:0.1 MG/M3;AS CO

ACGIH TLV:0.05 MG/M3;DUST 9293

Ingred Name: COPPER (SARA III)

CAS:7440-50-8

RTECS #:GL5325000

Other REC Limits:1 MG(CU)/M3 (DUST) OSHA PEL:0.1MG/M3 FUME/1 DUST

ACGIH TLV:0.2MG/M3 F

UME; 9192

EPA Rpt Qty:5000 LBS DOT Rpt Qty:5000 LBS

Ingred Name:TITANIUM DIOXIDE

CAS:13463-67-7

RTECS #:XR2275000

OSHA PEL:15 MG/M3 TDUST

ACGIH TLV:10 MG/M3 TDUST; 9293

Ingred Name: IRON OXIDE

CAS:1309-37-1

RTECS #:NO7400000 OSHA PEL:10 MG/M3 (FE)

ACGIH TLV:5 MG/M3(FE),B2; 9293

========= Hazards Identification ============================

Routes of Entry: Inhalation:YES Skin:YES Ingestion:NO Reports of Carcinogenicity:NTP:YES IARC:YES OSHA:NO

Health Hazards Acute and Chronic: INH

ALATION: UPPER RESPIRATORY TRACT IRRITATION. SKIN: ALLERGIC REACTION.
Explanation of Carcinogenicity:NICKEL IS A SUSPECTED HUMAN CARCINOGEN BY ACGIH.
Effects of Overexposure:INHALATION: UPPER RESPIRATORY TRACT IRRITATION. SKIN: ALLERGIC REACTION.
======================================
First Aid:OBTAIN MEDICAL ATTENTION IN ALL CASES.
======================================
Extinguishing Media:BLANKET, DRY NITROGEN, ARGON, OR DRY CHEMICAL. DON'T USE WATER OR HALON AGENTS.
Fire Fighting Procedures: POWDER BURNS RAPID/INTENSE. POWDER MAY REIGNITE AFTER EXTINGUISHED. RARE EARTH METAL POWDERS (SAMARIUM) BURN VIGOROUSLY IN HALOGEN OR ORGANIC ATMOSPHERE. Unusual Fire/Explosion Hazard: FINE METAL POWDERS PRODUCED BY DRY GRINDING/MACHING MAY CAUSE EXPLOSION. DRY POWDER/GRINDING SLUDGE MAY IGNITE SPONTANEOUSLY IN AIR OR OXYGEN.
============= Handling and Storage ==============
Handling and Storage Precautions:DON'T SHIP ON AIRCRAFT ANY MICROWAVE TUBES W/MAGNETIC FIELD >0.00525 GAUSS MEASURED AT 15 FT. (4.6 M) FROM ANY SURFACE OF THE PACKAGE. Other Precautions:NO SPECIAL PROTECTION IS REQUIRED FOR MICROWAVE TUBES AS SHIPPED. DON'T GRIND, CUT, FILE, SAW OR OTHERWISE CREATE DUST FROM MAGNETIC MATERIAL USED AS A PART OF MICROWAVE TUBES.
===== Exposure Controls/Personal Protection =======
Work Hygienic Practices:USE GOOD HYGIENE. Supplemental Safe ty and Health
========= Physical/Chemical Properties ==========
Melt/Freeze Pt:M.P/F.P Text:>2417F Spec Gravity:7.0-8.5 Solubility in Water:INSOLUBLE Appearance and Odor:METALLIC SILVER/LIGHT GRAY METAL, ODORLESS
========= Stability and Reactivity Data =========
Stability Indicator/Materials to Avoid:YES STRONG OXIDIZING AGENTS, ACIDS, OXYGEN, HALOGENATED HYDROCARBONS, & WATER
Hazardous Decomposition Products:HYDROGEN
====== Disposal C

onsiderations ==========

Waste Disposal Methods:RECYCLING OF MAGNETS USED IN MICROWAVE TUBES IS RECOMMENDED. RETURN TO MANUFACTURER FOR RECYCLING OR DISPOSE ACCORDING TO FEDERAL, STATE, & LOCAL REGULATIONS.

Disclaimer (provided with this information by the compiling agencies): This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and

disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.