

PERSON & COVEY INC -- DRY SOL -- 6505-01-146-4268

=====
Product Identification
=====

Product ID:DRYSOL
MSDS Date:03/09/1991
FSC:6505
NIIN:01-146-4268
MSDS Number: BLVCL
=== Responsible Party ===
Company Name:PERSON & COVEY INC
Address:616 ALLEN AVENUE
City:GLENDALE
State:CA
ZIP:91201-2014
Country:US
Info Phone Num:818-240-1030
Emergency Phone Num:818-240-1030
CAGE:51931
=== Contractor Identification
n ===
Company Name:PERSON & COVEY INC
Address:616 ALLEN AVENUE
Box:City:GLENDALE
State:CA
ZIP:91201-2014
Country:US
Phone:818-240-1030
CAGE:51931

=====
Composition/Information on Ingredients
=====

Ingred Name:ALUMINUM CHLORIDE
CAS:7446-70-0
RTECS #:BD0525000
Other REC Limits:NONE SPECIFIED
OSHA PEL:2 MG/M3
ACGIH TLV:2 MG/M3

Ingred Name:ETHYL ALCOHOL (ETHANOL)
CAS:64-17-5
RTECS #:KQ6300000
Other REC Limits:NONE SPECIFIED
OSHA PEL:1000 PPM
ACGIH TLV:1000 PPM; 9192

=====

=====
Hazards Identification
=====

Routes of Entry: Inhalation:YES Skin:YES Ingestion:NO
Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO
Health Hazards Acute and Chronic:ACUTE-INHALED:EXPOSURE TO >1000 PPM
MAY CAUSE HEADACHE,DROWSINESS,LOSS OF APPETITE,INABILITY TO
CONCENTRATE & UPPER RESPIRATORY SYSTEM IRRITATION.EXPOSURE TO
>20,000 PPM MAY CAUSE EXTREME NARCOSIS.EYE :MAY CAUSE IRRITATION &
CONJUNCTIVITIS.SKIN:MAY CAUSE IRRITATION.INGESTED:NAUSEA,V
OMITING &
DIARRHEA.CHRONIC-DERMATITIS.

Explanation of Carcinogenicity:THE IARC HAS REPORTED A RELATIONSHIP
BETWEEN INGESTION OF ALCOHOL & CANCER OF PHARYNX, ESOPHAGUS &
LIVER. PER MSDS.

Effects of Overexposure:EXPOSURE TO >1000 PPM MAY CAUSE HEADACHE,
DROWSINESS, LOSS OF APPETITE, INABILITY TO CONCENTRATE & UPPER
RESPIRATORY SYSTEM IRRITATION. EXPOSURE TO >20,000 PPM MAY CAUSE
EXTREME NARCOSIS. MAY CAUSE EYE IRRITATION & CONJUNCTIVITIS. MAY
CAUSE SKIN IRRITATION. INGESTED MAY CAUSE NAUSEA, VOMITING &
DIARRHEA.

Medical Cond Aggravated by Exposure:PERSONS WITH PRE-EXISTING SKIN
DISORDERS OR EYE PROBLEMS OR IMPAIRED LIVER, KIDNEY OR RESPIRATORY
FUNCTION MAY BE MORE SUSCEPTIBLE TO THE EFFECTS OF THE SUBSTANCE.

=====
First Aid Measures
=====

First Aid:OBTAIN MEDICAL ATTENTION IN ALL CASES.INGESTION:IF
CONSCIOUS,DRINK WATER OR MILK TO DILUTE.INHALATION:REMOVE FROM
EXPOSURE.PROVIDE CPR IF NEEDED.EYES:FLUSH
WITH WATER FOR AT LEAST
15 MINUTES,HOLDING EYELIDS OPEN.SKIN:IMMEDIATELY REMOVE
CONTAMINATED CLOTHING & FLUSH AFFECTED AREA WITH PLENTY OF WATER.

=====
Fire Fighting Measures
=====

Flash Point:55.0F,12.8C

Extinguishing Media:CARBON DIOXIDE, "ALCOHOL" FOAM OR DRY CHEMICAL.USE
WATER SPRAY TO KEEP FIRE EXPOSED CONTAINERS COOL & FLUSH SPILL
AWAY.

Fire Fighting Procedures:WEAR FULL PROTECTIVE CLOTHING AND
NIOSH-APPROVED SELF-CONTAINED BREATHING

G APPARATUS WITH FULL

FACEPIECE OPERATED IN THE PRESSURE DEMAND MODE.DILUTE SPILLS W/H2O

Unusual Fire/Explosion Hazard:SMOKE, FUMES OR HAZARDOUS DECOMPOSITION
PRODUCTS SUCH AS CARBON MONOXIDE, HYDROGEN CHLORIDE AND OXIDES OF
ALUMINUM

===== Accidental Release Measures =====

Spill Release Procedures:FIRE HAZARD:ELIMINATE ALL SOURCES OF IGNITION.
EVACUATE AREA. VENTILATE AREA. STOP RELEASE. DIKE TO CONTAIN SPILL.
WEAR PROPER SAFETY EQUIPMENT. ABSORB
SPILL WITH VERMICULITE AND
COLLECT INTO SUITABLE CONTAINER FOR DISPOSAL.

===== Handling and Storage =====

Handling and Storage Precautions:STORAGE-STORE IN COOL,WELL-VENTILATED
AREA,IN TIGHTLY CLOSED CONTAINERS,AWAY FROM HEAT,SPARKS & FLAMES.
Other Precautions:SEPARATE FROM OXIDIZERS. USE SPARK-RESISTANT TOOLS.
WHEN TRANSFERRING FOLLOW PROPER GROUNDING PROCEDURES. USE WITH
ADEQUATE VENTILATION. AVOID BREATHING VAPORS. AVOID CONTACT WITH

EYES, SKIN & CLOTHIN G

===== Exposure Controls/Personal Protection =====

Respiratory Protection:IF LEVELS EXCEED THE RECOMMENDED HEALTH
STANDARDS, WEAR A NIOSH/MSHA APPROVED ORGANIC VAPOR RESPIRATOR. FOR
EMERGENCY USE, WEAR A NIOSH APPROVED SELF-CONTAINED BREATHING
APPARATUS/A SUPPLIED AIR FULL FACEPIECE RESPIRATOR.

Ventilation:USE LOCAL AND/OR GENERAL EXHAUST VENTILATION.

Protective Gloves:NEOPRENE OR RUBBER

Eye Protection:CHEMICAL SAFETY GOGGLES & FULL FACEPIEC

E

Other Protective Equipment:FOR OPERATIONS WHERE SPILLS OR SPLASHING CAN
OCCUR,USE IMPERVIOUS BODY COVERING AND TOOLS,A SAFETY SHOWER AND
EYE BATH.

Work Hygienic Practices:WASH HANDS BEFORE EATING, DRINKING, SMOKING, OR
USING TOILET FACILITIES. WASH CONTAMINATED CLOTHING BEFORE REUSE.

Supplemental Safety and Health

===== Physical/Chemical Properties =====

HCC:F2

Boiling Pt:=78.C, 172.4F

Vapor Pres:44.6 @ 86F

Vapor Density:1.59

Spec Gravity:0.92

Solubili

ty in Water:COMPLETE

Appearance and Odor:CLEAR, AND COLORLESS TO SLIGHTLY YELLOW LIQUID WITH
A STRONG ALCOHOL ODOR

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES

STRONG OXIDIZING AGENTS, ACETYL CHLORIDE, WATER

Stability Condition to Avoid:HEAT, SPARKS, FLAMES AND OTHER SOURCES OF
IGNITION

Hazardous Decomposition Products:WHEN HEATED TO DECOMPOSITION, MAY
GENERATE CARBON MONOXIDE, HYDROGEN CHLORIDE AND OXIDES OF ALUMINU
M.

===== Disposal Considerations =====

Waste Disposal Methods:DISPOSE OF IN ACCORDANCE WITH ALL LOCAL, STATE
AND FEDERAL REGULATIONS.

Disclaimer (provided with this information by the compiling agencies):

This information is formulated for use by elements of the Department
of Defense. The United States of America in no manner whatsoever,
expressly or implied, warrants this information to be accurate and
disclaims all liability for its use. Any person

utilizing this

document should seek competent professional advice to verify and
assume responsibility for the suitability of this information to their
particular situation.