View NSN Online: https://aerobasegroup.ae/nsn/5330-00-197-8524

Product ID:STYLE 3030 I VALVE PACKING MSDS Date:05/25/1990 FSC:5330 NIIN:00-197-8524 MSDS Number: BMDNG === Responsible Party === Company Name: AMERICAN BRAIDING AND MFG.CORP Address:RT.79 & BEACON HILL ROAD Box:397 City:MORGANVILLE State:NJ ZIP:07751 Country:US Info Phone Num:201-591 -0725 Emergency Phone Num:201-591-0725 CAGE:4R345 === Contractor Identification === Company Name: AMERICAN BRAIDING AND MFG CORP Address:247 OLD TAVERN ROAD Box:City:HOWELL State:NJ ZIP:07731 Country:US Phone:732-938-6333 ...FAX 6377 CAGE:4R345 Ingred Name: ASBESTOS, CHRYSOTILE

CAS:12001-29-5 RTECS #:CI6478500 Fraction by Wt: 30% MIN Other REC Limits:NONE SPECIFIED OSHA PEL:0.2 FIBERS/CC ACGIH TLV:2 FIBERS/CC; A1;9192

=====

Routes of Entry: Inhalation:YES Skin:YES Ingestion:NO Reports of Carcinogenicity:NTP:YES IARC:YES OSHA:YES Health Hazards Acute and Chronic: ACUTE- DUST MAY CAUSE IRRITATION OF EYES & SKIN. CHRONIC- LONG TERM EXPOSURE TO ASBESTOS CAN CAUSE ASBESTOSIS, LUNG DISEASE, LUNG CANCER. Explanation of Carcinogenicity: ASBESTOS IS REGULATED BY OSHA AS A CARCINOGEN. Effects of Overexposure: ASBESTOSIS IS ASSOCIATED WITH SYMPTOM S OF LABORED BREATHING, CHEST PAIN, COUGHING AND FINGER CLUBBING. LIKE OTHER AEROSOLS, ASBESTOS FIBERS MAY IRRITATE THE UPPER RESPIRATORY TRACT. Medical Cond Aggravated by Exposure: PRE-EXISTING CONDITIONS SUCH AS CHRONIC BRONCHITIS, ASTHMA OR DERMATITIS. First Aid:SEEK MEDICAL ATTENTION. IN CASE OF EYE IRRITATION GENTLY RINSE WITH WATER FOR 15 MINUTES WHILE KEEPING EYELIDS OPEN. SKIN: WASH FREQUENTLY W ITH WATER. INHALATION: REMOVE TO FRESH AIR. INGESTION: CALL PHYSICIAN. Flash Point:NONE Extinguishing Media:NONE REQUIRED Fire Fighting Procedures:NONE Unusual Fire/Explosion Hazard:NON FLAMMABLE Spill Release Procedures: TREAT DUST AS FREE ASBESTOS. DO NOT DRY SWEEP OR USE COMPRESSED AIR. Neutralizing Agent:NOT APPLICABLE. Handling and Storage Precautions:STORAGE- AVOID CREATING DUST BY SANDING OR GRINDING THE PRODUCT. Other Precautions: USE IN WELL VENTILATED AREA. AVOID BREATHING DUST OR FIBERS. MINIMIZE CONTACT WITH SKIN. AVOID CONTACT WITH EYES. DO NOT RAISE DUST. 

Respiratory Protection:USE NIOSH/OSHA APPROVED HIGH EFFICIENCY DUST RESPIRATOR WHEN AIRBORNE FIBER CONCENTRATIONS EXCEED THE PEL.

Ventilation:LOCAL/GENERAL TO MAINTAIN PEL/TLV. CHECK LOCAL REGULATIONS FOR EMISSION STANDARDS.

Protective Gloves:NATURAL RUBBER OPTIONAL

Eye Protection: DUST-RESISTANT SAFETY GOGGLES

Other Protective Equipment: EYE WASH STATION AND SAFETY SHOWER, WORK CLOTHING AND APRON AS REQUIRED.

Work Hygienic Practices:DON'T TAKE PROTECTIVE GEAR/CLOTHING HOME IF EXPOSED TO DUST. DON'T SHAKE. DON'T EAT IN AREA WHERE ASBESTOS/DUST PRESENT.

Supplemental Safety and Health

HCC:T7 Spec Gravity:1.5 Solubility in Water:INSOLUBLE Appearance and Odor:BLACK SHINY BRAIDED ROPE

Stability Indicator/Materials to Avoid:YES STRONG ACIDS AND ALKALI Stability Condition to Avoid:FLAMES Hazardous Decomposition Products:NONE

Waste Disposal Methods:DISPOSE OF IN ACCORDANCE WITH ALL LOCAL, S TATE

AND FEDERAL REGULATIONS.

Disclaimer (provided with this information by the compiling agencies): This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this infor mation to their particular situation.