

X-ERGON DIV OF NCH CORP -- 6011 ELECTRODE -- 3439-00-262-2654

===== Product Identification =====

Product ID:6011 ELECTRODE

MSDS Date:09/01/1989

FSC:3439

NIIN:00-262-2654

MSDS Number: BMGPG

=== Responsible Party ===

Company Name:X-ERGON DIV OF NCH CORP

Address:1400 E NORTHGATE DRIVE

Box:152102

City:IRVING

State:TX

ZIP:75015-2102

Country:US

Info Phone Num:214-438-1381

Emergency Phone Num:214-438-138

1

Preparer's Name:J. MICHAEL COLE

CAGE:55649

=== Contractor Identification ===

Company Name:X-ERGON A PARTSMASTERS CO DIV NCH CORP

Box:152170

City:IRVING

State:TX

ZIP:75015

Country:US

Phone:972-438-1381

CAGE:55649

===== Composition/Information on Ingredients =====

Ingred Name:IRON

CAS:7439-89-6

RTECS #:NO4565500

Other REC Limits:NONE SPECIFIED

OSHA PEL:5 MG/M3

ACGIH TLV:10 MG/M3 AS FE2O3

Ingred Name:MANGANESE (SARA III)

CAS:7439-96-5

RTECS #:OO9275000

Other REC Limits:NONE

SPECIFIED
OSHA PEL:(C) 5 MG/M3 DUST
ACGIH TLV:5 MG/M3 DUST 9293

Ingred Name:CELLULOSE (PAPER FIBER)
CAS:9004-34-6
RTECS #:FJ5691460
Other REC Limits:NONE SPECIFIED
OSHA PEL:15 MG/M3 TDUST
ACGIH TLV:10 MG/M3; 9192

Ingred Name:TITANIUM DIOXIDE
CAS:13463-67-7
RTECS #:XR2275000
Other REC Limits:NONE SPECIFIED
OSHA PEL:15 MG/M3 TDUST
ACGIH TLV:10 MG/M3 TDUST; 9293

Ingred Name:POTASSIUM ALUMINUM SILICATE (FELDSPAR)
CAS:68476-25-5
Other REC Limits:NONE SPECIFIED
ACGIH TLV:2 MG/M3

Ingred Name:POTASS
IUM TITANATE
CAS:12030-97-6
Other REC Limits:NONE SPECIFIED

===== Hazards Identification =====

Routes of Entry: Inhalation:YES Skin:NO Ingestion:NO
Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO
Health Hazards Acute and Chronic:ACUTE: EXPOSURE TO FUMES MAY CAUSE
DIZZINESS, NAUSEA, OR DRYNESS OR IRRITATION OF NOSE, THROAT, OR
EYES. CHRONIC: MAY LEAD TO SIDEROSIS (IRON DEPOSITS IN THE LUNG)
AND IS BELIEVED BY SOME INVESTIGATOR S TO AFFECT PUL
MONARY
FUNCTION. ARC RAYS CAN INJURE EYES AND BURN SKIN. ELECTRIC SHOCK
CAN KILL.
Explanation of Carcinogenicity:NONE OF THE INGREDIENTS IN THIS PRODUCT
ARE LISTED BY NTP, IARC, OR OSHA AS A CARCINOGEN.
Effects of Overexposure:DIZZINESS, NAUSEA, DRYNESS OR IRRITATION OF THE
NOSE, THROAT, OR EYES.
Medical Cond Aggravated by Exposure:NONE SPECIFIED BY MANUFACTURER.

===== First Aid Measures =====

First Aid:INHALATION: REMOVE TO FRESH AIR AND S

SEEK MEDICAL AID.

ADMINISTER RESPIRATION. IF NO DETECTABLE PULSE, BEGIN EXTERNAL HEART MASSAGE. EYES: FLUSH WITH WATER FOR AT LEAST 15 MINUTES. SKIN: REMOVE CONTAMINATED CLOTHING. WASH SKIN WITH SOAP AND WATER. INGESTION: DO NOT INDUCE VOMITING. SEEK MEDICAL ATTENTION. IN CASE OF ELECTRICAL SHOCK TURN OFF POWER PRIOR TO REMOVAL FROM AREA AND ADMINISTER AID.

===== Fire Fighting Measures =====

Autoignition Temp: Autoignition Temp Text: UNKNOWN

Extinguishing Media: NONE SPECIFIED BY MANUFACTURER.

Fire Fighting Procedures: WEAR FIRE FIGHTING PROTECTIVE EQUIPMENT AND FULL FACE-PIECE SELF-CONTAINED BREATHING APPARATUS. COOL FIRE EXPOSED CONTAINERS WITH WATER SPRAY. CONTAIN RUNOFF.

Unusual Fire/Explosion Hazard: WELDING ARC AND SPARK CAN IGNITE COMBUSTIBLES. DO NOT USE WATER ON MOLTEN METAL BECAUSE HAZARDOUS METAL FUMES/DUST MAY BE PRODUCED.

===== Handling and Storage =====

Handling and S

torage Precautions: KEEP DRY.

Other Precautions: SPARKS, SPATTER, AND ARC CAN IGNITE FLAMMABLE PRODUCTS.

===== Exposure Controls/Personal Protection =====

Respiratory Protection: WELD FUME RESPIRATOR FOR CONFINED SPACE OR WHEN EXCEEDING TLV.

Ventilation: USE VENTILATION AND/OR LOCAL EXHAUST AT THE ARC TO KEEP THE FUMES/GASES BELOW THE TLV'S IN THE WORKERS BREATHING ZONE.

Protective Gloves: WELDER'S PROTECTIVE GLOVES

Eye Protection: PROTECTIVE WELDING LENS

Other Protecti

ve Equipment: PROTECTIVE CLOTHING SUCH AS LEATHER APRONS, ETC.

Work Hygienic Practices: WASH AFTER HANDLING.

Supplemental Safety and Health

WELDER SHOULD KEEP HIS OR HER HEAD OUT OF THE FUMES.

===== Physical/Chemical Properties =====

HCC: N1

Appearance and Odor: SOLID ROD

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid: YES
NONE.

Stability Condition to Avoid: NONE SPECIFIED BY MANUFACTURER.

Hazardous Decompo

sition Products:FUMES OF METALS AND METAL OXIDES,
CARBON MONOXIDE, CARBON DIOXIDE, OZONE, NITROGEN OXIDES, FLUORIDES,
AND COMPLEX OXIDES

===== Disposal Considerations =====

Waste Disposal Methods:DISCARD ANY PRODUCT (INCLUDING ANY RETAINED
MATERIALS OF USE), DISPOSABLE CONTAINER OR LINER IN AN
ENVIRONMENTALLY ACCEPTABLE MANNER, IN FULL COMPLIANCE WITH LOCAL,
STATE AND FEDERAL REGULATIONS.

Disclaimer (provided with this information by the co
mpiling agencies):

This information is formulated for use by elements of the Department
of Defense. The United States of America in no manner whatsoever,
expressly or implied, warrants this information to be accurate and
disclaims all liability for its use. Any person utilizing this
document should seek competent professional advice to verify and
assume responsibility for the suitability of this information to their
particular situation.