## 

Product ID:LEAD ACID BATTERY MSDS Date:02/25/1987 FSC:6140 NIIN:01-320-2644 MSDS Number: BMGVX === Responsible Party === Company Name: MATSUSHITA ELECTRIC Address:1 PANASONIC WAY Box:1501 City:SECAUCUS State:NJ ZIP:07094-2917 Country:US Info Phone Num:201-348-7000 Emergency Phone Num:201-348-7000 CAGE:54 473 === Contractor Identification === Company Name: ADVANCED INDUSTRIES INC Address:415 NORTHCUTT STREET Box:5666 City:LONGVIEW State:TX ZIP:75608 Country:US Phone:214-236-4101 CAGE:0GA21 Company Name: ARCAIR CO SUB OF AIR PRODUCTS AND CHEMICALS INC Address:4200 WEST HARRY ST Box:12250 City:WICHITA State:KS ZIP:67277 Country:US Phone:316-942-1421 CAGE:09687 Company Name: LAND M WELDING SUPPLY INC Address:568 WESTERN DR Box:City:MOBILE State:AL ZIP:36607-1420 Country:US Phone:334-470-9997 CAGE:1HJ9

Company Name: MATSUSHITA ELECTRIC Address:1 PANASONIC WAY Box:1501 City:SECAUCUS State:NJ ZIP:07094-2917 Country:US Phone:201-348-7000 CAGE:54473 Company Name:NETEX INDUSTRIES(FORMER NORTHEAST TEXAS IND) Address:1700 NORTH EDWARDS STREET Box:City:MOUNT PLEASANT State:TX ZIP:75455 Country:US Phone:903-577-0388 CAGE:0WAG0 Ingred Name:SULFURIC ACID (SARA III) CAS:7664-93-9 RTECS #:WS5600000 Fraction by Wt: 10-20% Other REC Lim its:NONE SPECIFIED OSHA PEL:1 MG/M3 ACGIH TLV:1 MG/M3; 9192 EPA Rpt Qty:1000 LBS DOT Rpt Qty:1000 LBS Ingred Name:LEAD (SARA III) CAS:7439-92-1 RTECS #: OF7525000 Fraction by Wt: 30-60% Other REC Limits:NONE SPECIFIED OSHA PEL:0.05 MG/M3;1910.1025 ACGIH TLV:0.15 MG/M3;DUST 9192 EPA Rpt Qty:1 LB DOT Rpt Qty:1 LB Ingred Name: LEAD PEROXIDE (LEAD DIOXIDE), (FOR OSHA PEL SEE 29CFR 1910.1025) CAS:1309-60-0 RTECS #:OG0700000 Fraction by Wt: 5-25% Other REC Limits:NONE SPECIFIED OSHA PEL:0.05 MG/M

5

ACGIH TLV:0.15 MG/M3(PB); 9192 Ingred Name: LEAD SULFATE (SARA III) CAS:7446-14-2 RTECS #:OG4375000 Fraction by Wt: 1-25% Other REC Limits:NONE SPECIFIED OSHA PEL:0.05 MG/M3 (PB) ACGIH TLV:0.15 MG/M3 (PB) 9192 EPA Rpt Qty:100 LBS DOT Rpt Qty:100 LBS LD50 LC50 Mixture: LD50 ORAL RAT IS 2140 MG/KG. Routes of Entry: Inhalation:YES Skin:NO Ingestion:NO Reports of Carcinogenicity:NTP:YES IARC:YES OSHA:NO Health Hazar ds Acute and Chronic: ACUTE: BURNS, SEVERE IRRITATION OF SKIN, EYES, MOUTH, THROAT, ESOPHAGUS AND STOMACH; INFLAMMATION OF BRONCHIAL MEMBRANES. CHRONIC: EROSION OF TEETH, INFLAMMATION OF NOSE, THROAT AND BRONCHIAL TUBES. Explanation of Carcinogenicity: LEAD IS ANTICIPATED CARCINOGENIC BY NPT, POSSIBLY CARCINOGENIC TO HUMANS BY IARC. Effects of Overexposure: COUGH, INCREASED RESPIRATORY RATE, STINGING, BURNING SENSATION ON SKIN, EYE IRRITATION, DISCOLORATION OF TEETH. Medical Con d Aggravated by Exposure: EXPOSURE TO MISTS MAY CAUSE LUNG DAMAGE AND AGGRAVATE PULMONARY CONDITIONS. First Aid: EYES/SKIN: FLUSH WITH PLENTY OF WATER. SEE DOCTOR IMMEDIATELY. REMOVE CONTAMINATED CLOTHING AND SHOES. INHALATION: REMOVE TO FRESH AIR. GIVE OXYGEN/CPR IF NEEDED. SEE DOCTOR. INGESTION: DO NOT INDUCE VOMIT. GIVE MILK OR WATER, FOLLOWED BY 2 OUNCES OF MILK OF MAGNESIA (NO CARBONATES). SEE DOCTOR I MMEDIATELY. Flash Point:NONE Lower Limits: 4.0 (HYDROGN) Upper Limits:75(HYDROGEN) Extinguishing Media: USE WATER FOG, CARBON DIOXIDE, FOAM, DRY CHEMICAL, OR DRY SAND. Fire Fighting Procedures: EVACUATE AREA. REMOVE ALL IGNITION SOURCES. WEAR FIRE FIGHTING PROTECTIVE EQUIPMENT AND A FULL FACED SCBA. COOL FIRE EXPOSED CONTAINERS WITH WATER SPRAY. Unusual Fire/Explosion Hazard: HYDROGEN GAS MAY BE PRODUCED AND MAY EΧ

3 (PB)

## PLODE IF IGNITED. REMOVE ALL IGNITION SOURCES. VENTILATE AREA.

Spill Release Procedures:WEAR APPROPIATE PROTECTIVE EQUIPMENT. DILUTE CAUTIOUSLY WITH WATER. COVER WITH SODA ASH OR QUICKLIME. SCOOP UP AND PLACE IN APPROPIATE DISPOSAL CONTAINER. FLUSH AREA WITH LARGE AMOUNTS OF WATER.

Neutralizing Agent:SODA ASH (SODIUM CARBONATE), BAKING SODA OR QUICKLIME (CALCIUM OXIDE).

======= Handling and Stor

Handling and Storage Precautions:STORE AT ROOM TEMPERATURE. STORE AWAY FROM FLAMES, IGNITION SOURCES, COMBUSTIBLE AND ORGANIC MATERIALS. AVOID PROLONGED OVERCHARGING.

Other Precautions:DO NOT CARRY BATTERY BY TERMINALS. DO NOT DROP BATTERY, PUNCTURE OR ATTEMPT TO OPEN BATTERY CASE. KEEP TERMINALS COVERED IN PLASTIC CASE. AVOID SHORTING BATTERIES.

Respiratory Protection:NONE NORMALLY

REQUIRED. NIOSH/MSHA-APPROVED

CARTRIDGE RESPIRATOR FOR ACIDS OR FULL FACE MASK AS APPROPIATE FOR EXPOSURE OF CONCERN WHEN TLV IS EXCEEDED.

Ventilation:GENERAL (MECHANICAL) VENTILATION. LOCAL EXHAUST IN CONFINED AREAS.

Protective Gloves: RUBBER GLOVES IF CONTACT IS EXPECTED.

Eye Protection: GOGGLES IF CONTACT IS EXPECTED.

Other Protective Equipment: RUBBER APRON AND BOOTS IF CONTACT IS

EXPECTED. EYE WASH STATION AND SAFETY SHOWER.

Work Hygienic Practices: WASH THOROUGHLY AFTER HANDLI

NG.

Supplemental Safety and Health

OVERCHARGING OR ABUSE TO THE TERMINALS CAN RESULT IN THE RELEASE OF ACID OR ACID VAPORS. DISCONNECT AND CLEAN TERMINALS WITH MILD BAKING SODA SOLUTION AND WASH WITH WATER. THIS MSDS WAS PREPARED FOR E XPOSURE TO SULFURIC ACID. MANUFACTURER STATES LCR SEALED LEAD BATTERIES DO NOT REQUIRE AN MSDS.

HCC:N1 pH:ACIDIC Solubility in Water:COMPLETE Appearance and Odor:ACID SOLUTION I

## N PLASTIC CASE

Stability Indicator/Materials to Avoid:YES

ORGANIC MATERIALS, CHLORATES, CARBIDES, FULMINATES, WATER, POWDERED METALS (NOTE; REACTS VIOLENTLY WITH WATER).

Stability Condition to Avoid:AVOID SHORTING, USE ONLY APPROVED CHARGING METHODS. AVOID HIGH HEAT, OPEN FLAMES AND OTHER SOURCES OF IGNITION Hazardous Decomposition Products:SULFURIC ACID FUMES, SULFUR DIOXIDE, SULFUR TRIOXIDE, CARBON MONOXIDE, HYDR OGEN GAS.

Waste Disposal Methods:CONSULT YOUR LOCAL ENVIRONMENTAL OFFICER. DISPOSE OF IN ACCORDANCE WITH FEDERAL, STATE AND LOCAL ENVIRONMENTAL REGUALTIONS.

Disclaimer (provided with this information by the compiling agencies): This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this

document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.