

3M, INDUSTRIAL SPECIALTIES DIVISION -- SCOTCH-WELD 3535B/A PART B URETHANE ADHESIV --
8465-01-011-6427

===== Product Identification =====

Product ID:SCOTCH-WELD 3535B/A PART B URETHANE ADHESIV

MSDS Date:11/09/1990

FSC:8465

NIIN:01-011-6427

Kit Part:Y

MSDS Number: BMQKJ

=== Responsible Party ===

Company Name:3M, INDUSTRIAL SPECIALTIES DIVISION

Address:3M CENTER

City:ST PAUL

State:MN

ZIP:55144-1000

Country:US

Info Phone Num:612-733-1110

Emergency Phone Num:612-733-1110

CAGE:52152

=== Contractor Identification ===

Company Name:MINNESOTA MINING & MFG CO INDUSTRIAL TAPE & SPECIALTIES
DIV

Address:3M CENTER

Box:City:ST PAUL

State:MN

ZIP:55144-1000

Country:US

Phone:1-800-364-3577

CAGE:52152

===== Composition/Information on Ingredients =====

Ingred Name:POLYESTER RESIN

Fraction by Wt: 40-50%

Other REC Limits:NONE SPECIFIED

Ingred Name:TALC (CONTAINING ASBESTOS)

CAS:14807-

96-6
RTECS #:MW2700000
Fraction by Wt: 15-25%
Other REC Limits:NONE SPECIFIED
OSHA PEL:0.2 FIBERS/CC
ACGIH TLV:0.2 FIBERS/CC; 9192

Ingred Name:POLYOXYPROPYLENE GLYCOL
CAS:25322-69-4
RTECS #:TR5250000
Fraction by Wt: 15-25%
Other REC Limits:NONE SPECIFIED

Ingred Name:TITANIUM DIOXIDE
CAS:13463-67-7
RTECS #:XR2275000
Fraction by Wt: 5-15%
Other REC Limits:NONE SPECIFIED
OSHA PEL:15 MG/M3 TDUST
ACGIH TLV:10 MG/M3 TDUST; 9293

Ingred Name:POLYOXYPROPYLENE TRIOL
CAS:25723-16-4
Fraction by Wt: 1-10%

Other REC Limits:NONE SPECIFIED

Ingred Name:ZEOLITES
CAS:1318-02-1
Fraction by Wt: 1-10%
Other REC Limits:NONE SPECIFIED

Ingred Name:O-DIETHYLBISANILINE
CAS:13680-35-8
Fraction by Wt: 1-10%
Other REC Limits:NONE SPECIFIED

Ingred Name:BETA-(3,4-EPOXYCYCLHEXYL)ETHYLTRIMETHYLOXYSILANE
CAS:3388-04-3

Fraction by Wt: 1% IS LISTED AS A
CARCINOGEN BY NTP, IARC, OR OSHA.

Effects of Overexposure:INHALATION: COUGHING, WHEEZING, SHORTNESS OF
BREATH. EYES: REDNESS, TEARING. SKIN: REDNESS, RASH. I

NGESTION:

NAUSEA, DIARRHEA, VOMITING.

Medical Cond Aggravated by Exposure:NONE SPECIFIED BY MANUFACTURER.

===== First Aid Measures =====

First Aid:INHALATION: PROVIDE FRESH AIR. RESUSCITATE OR GIVE OXYGEN IF NEEDED. EYES: FLUSH WITH PLENTY OF WATER FOR 15 MINUTES. SEE DOCTOR. SKIN: WASH WITH SOAP AND WATER. INGESTION: DO NOT INDUCE VOMITING. IMM EDIATELY GET MEDICAL ASSISTANCE OR CALLPOISON CONTROL CENTER.

===== Fire F
ighting Measures =====

Flash Point:NONE

Extinguishing Media:CARBON DIOXIDE, FOAM, DRY CHEMICAL, WATER

Fire Fighting Procedures:WEAR SELF-CONTAINED BREATHING APPARATUS AND FULL PROTECTIVE GEAR.

Unusual Fire/Explosion Hazard:NONE SPECIFIED BY MANUFACTURER.

===== Accidental Release Measures =====

Spill Release Procedures:VENTILATE THE AREA. COLLECT SPILLED MATERIAL. PLACE IN DOT APPROVED CONTAINER AND SEAL PENDING DISPOSAL.

Neutralizing Agent:
NONE SPECIFIED BY MANUFACTURER.

===== Handling and Storage =====

Handling and Storage Precautions:STORE IN A COOL, DRY ARTEA.

Other Precautions:KEEP CONTAINER CLOSED WHEN NOT IN USE. KEEP OUT OF REACH OF CHILDREN. AVOID CONTACT WITH SKIN AND EYES.

===== Exposure Controls/Personal Protection =====

Respiratory Protection:NONE NORMALLY REQUIRED. IF PEL/TLV EXCEEDED; USE NIOSH/MSHA APPROVED RESPIRATOR WITH ORGANIC VAPOR CARTRIDGE.

Vent
ilation:USE ADEQUATE MECHANICAL VENTILATION.

Protective Gloves:NITRILE OR PVA

Eye Protection:SAFETY GLASSES/CHEMICAL SPLASH GOGGLES

Other Protective Equipment:EYE WASH STATION. IMPERVIOUS APRON.

Work Hygienic Practices:WASH HANDS ATER USE AND BEFORE EATING, DRINKING, OR SMOKING. LAUNDER CONTAMINATED CLOTHES BEFORE REUSING.

Supplemental Safety and Health

===== Physical/Chemical Properties =====

HCC:N1

Spec Gravity:1.31

Solubility in Water:SLIGHT

Appearance and Od

or:WHITE VISCOUS LIQUID WITH A RESINOUS ODOR
Percent Volatiles by Volume:0

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES
NONE SPECIFIED BY MANUFACTURER.
Stability Condition to Avoid:NONE SPECIFIED BY MANUFACTURER.
Hazardous Decomposition Products:OXIDES OF CARBON AND NITROGEN

===== Disposal Considerations =====

Waste Disposal Methods:DISPOSE OF IN ACCORDANCE WITH LOCAL, STATE AND
FEDERAL REGULATIONS. MANUFACTURER SAYS TO INCINERATE AFTER MIXING
WITH A FLAMMABLE MATERIAL.

Disclaimer (provided with this information by the compiling agencies):
This information is formulated for use by elements of the Department
of Defense. The United States of America in no manner whatsoever,
expressly or implied, warrants this information to be accurate and
disclaims all liability for its use. Any person utilizing this
document should seek competent professional advice to verify and
assume responsibility for the suitability of this information to their
particular situation.