

CORONADO PAINT COMPANY, INC. -- PENETRATING OIL STAIN 69-27 -- 8010-00-165-8628

=====
Product Identification
=====

Product ID: PENETRATING OIL STAIN 69-27

MSDS Date: 12/20/1991

FSC: 8010

NIIN: 00-165-8628

MSDS Number: BMSKJ

=== Responsible Party ===

Company Name: CORONADO PAINT COMPANY, INC.

Address: 308 OLD COUNTY ROAD

City: EDGEWATER

State: FL

ZIP: 32132

Country: US

Info Phone Num: 904-428-6461

Emergency

Phone Num: 904-428-6461

Preparer's Name: THOMAS E. MAREK

CAGE: 33200

=== Contractor Identification ===

Company Name: CORONADO PAINT COMPANY, INC.

Address: 308 OLD COUNTY ROAD

Box: City: EDGEWATER

State: FL

ZIP: 32132-1812

Country: US

Phone: 904-428-6461

CAGE: 33200

=====
Composition/Information on Ingredients
=====

Ingred Name: MINERAL SPIRITS (VAPOR PRESSURE 2.0 MM HG)

CAS: 8052-41-3

RTECS #: WJ8925000

Fraction by Wt: 77.9%

Other REC Limits: NONE SPECIFIED

OSHA PEL: 500 PPM

ACGIH TLV: 100 PPM

; 9293

Ingred Name:VOC: 5.38 LBS./GAL
RTECS #:9999999VO
Other REC Limits:N/KE SPECIFIED

=====
===== Hazards Identification =====

Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES
Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO
Health Hazards Acute and Chronic:EYES- CAN CAUSE SEVERE IRRITATION,
REDNESS, TEARING, BLURRED VISION. SKIN- PROLONGED OR REPEATED
CONTACT CAN CAUSE MODERATE IRRITATION, DEFATTING, DERMATITIS.
BREATHING- EXCESSIVE INHALATION OF VAPORS CAN CAUSE NASAL AND
RESPIRATORY IRRITATION, DIZZINESS, WEAKNESS, FATIGUE, NAUSEA,
HEADACHE, POSSIBLE UNCONSCIOUSNESS
Effects of Overexposure:AND EVEN ASPHYXIATION. SWALLOWING- CAN CAUSE
GASTROINTESTINAL IRRITATION, NAUSEA, VOMITING AND DIARRHEA.
ASPIRATION INTO LUNGS CAN CAUSE CHEMICAL PNEUMONITIS WHICH CAN BE
FATAL.

=====
===== First Aid Measures =====

First Aid:SKIN-WASH EXPOSED AREA W/SOAP & WATER. REMOVE CONTAM CLOTH &
LAUNDER BEFORE REUSE. EYES-FLUSH W/LG AMTS WATER, LIFTING UPPER &
LOWER LIDS OCCASIONALLY, GET MEDICAL ATTENTION. INGESTION- DO NOT
INDUCE VOMITING. KEEP PERSON WARM & GET MEDICAL ATTENTION.
INHALATION- REMOVE TO FRESH AIR. IF BREATHING IS DIFFICULT, GIVE
OXYGEN. IF BREATHING HAS STOPPED, GIVE CPR. KEEP PERSON WARM, QUIET
& GET MED AID.

=====
===== Fire Fighting Measures =====

Flash Point Method:SCC
Flash Point:102F,39C
Lower Limits:1.0
Upper
Limits:6.0
Extinguishing Media:FOAM, DRY CHEMICAL, CARBON DIOXIDE.
Fire Fighting Procedures:WEAR SELF-CONTAINED BREATHING APPARATUS WITH A
FULL FACEPIECE OPERATED IN PRESSURE-DEMAND OR OTHER POSITIVE
PRESSURE MODE WHEN FIGHTING FIRES.
Unusual Fire/Explosion Hazard:VAPORS ARE HEAVIER THAN AIR & MAY TRAVEL
ALONG GROUND OR BE MOVED BY VENTILATION & IGNITE BY IGNITE SOURCES
AT LOCATIONS DISTANT FROM MATERIAL HANDLING POINT.

=====
===== Accidental Release Measures =====

=====

Spill Release Procedures: ABSORB LIQUID ON PAPER, VERMICULITE, FLOOR
ABSORBENT OR OTHER ABSORBENT MATERIAL AND PICK UP WITH SHOVEL.

===== Handling and Storage =====

Handling and Storage Precautions: AVOID PROLONGED OR REPEATED SKIN
CONTACT. KEEP AWAY FROM HEAT, SPARKS, OPEN FLAMES. USE WITH
ADEQUATE VENTILATION.

===== Exposure Controls/Personal Protection =====

Respiratory Protection: SELF CONTAINED NIOSH APPROVED RESPIR
ATOR IF TLV
IS REACHED.

Ventilation: LOCAL EXHAUST AS NEEDED TO REMAIN BELOW PEL.

Protective Gloves: NEOPRENE OR NITRILE RUBBER.

Eye Protection: SAFETY GLASSES OR CHEMICAL GOGGLES.

Other Protective Equipment: BARRIER CREAM, EYE BATH & SAFETY SHOWER.

Supplemental Safety and Health

===== Physical/Chemical Properties =====

HCC: F4

Boiling Pt: B.P. Text: 315F, 157C

Vapor Density: > AIR

Spec Gravity: 0.83

Evaporation Rate & Reference: