

BAKER SEALANTS AND COATINGS CO -- PAINT FOR CONCRETE AND MASONARY --
8010-00-597-8198

===== Product Identification =====

Product ID:PAINT FOR CONCRETE AND MASONARY
MSDS Date:03/25/1991
FSC:8010
NIIN:00-597-8198
MSDS Number: BMSNL
=== Responsible Party ===
Company Name:BAKER SEALANTS AND COATINGS CO
Address:234 SUYDAM AVE
Box:B
City:JERSEY CITY
State:NJ
ZIP:07304
Country:US
Info Phone Num:201-333-6986
Emergency Phone Num:201-333-6986 OR 800-424-9300
Preparer's Name:CHARLES FRIEDMAN
CAGE:34094

=== Contractor Identification ===
Company Name:BAKER SEALANTS AND COATINGS CO
Address:234 SUYDAM AVE
Box:City:JERSEY CITY
State:NJ
ZIP:07304-3306
Country:US
Phone:201-333-6986
CAGE:34094
Company Name:STEVEN INDUSTRIES
Address:39 AVENUE C
Box:8
City:BAYONNE
State:NJ
ZIP:07002-3417
Country:US
Phone:201-437-6501
CAGE:33150

===== Composition/Information on Ingredients =====

Ingred Na

me:BUTYL CELLOSOLVE
CAS:111-76-2
RTECS #:KJ8575000
Fraction by Wt: 5-10%
Other REC Limits:NONE SPECIFIED
OSHA PEL:S, 50 PPM
ACGIH TLV:S, 25 PPM; 9293

Ingred Name:CALCIUM CARBONATE
CAS:1317-65-3
RTECS #:EV9580000
Fraction by Wt: 10-15%
Other REC Limits:NONE SPECIFIED

Ingred Name:TITANIUM DIOXIDE
CAS:1317-80-2
RTECS #:VM2940000
Fraction by Wt: 5-10%
Other REC Limits:NONE SPECIFIED

Ingred Name:ACRYLIC RESIN
Fraction by Wt: 20-30%
Other REC Limits:NONE SPECIFIED

Ingred Name:VM&P NAPHTHA
CAS:8030
-30-6
RTECS #:DE3030000
Fraction by Wt: 20-25%
Other REC Limits:NONE SPECIFIED

Ingred Name:PETROLEUM SOLVENT
CAS:64742-95-6
Fraction by Wt: 5-10%
Other REC Limits:NONE SPECIFIED
ACGIH TLV:100 PPM

Ingred Name:TOLUENE (SARA III)
CAS:108-88-3
RTECS #:XS5250000
Fraction by Wt: 5-10%
Other REC Limits:NONE SPECIFIED
OSHA PEL:200 PPM/150 STEL
ACGIH TLV:50 PPM; 9293
EPA Rpt Qty:1000 LBS
DOT Rpt Qty:1000 LBS

Ingred Name:VOC: 508
RTECS #:9999999VO
Other REC Limits:NONE SPECIFIED

=====

Hazards Identification =====

Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES
Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO
Health Hazards Acute and Chronic:EYES: HIGH VAPOR CONCENTRATION CAUSES IRRITATION, REDNESS & TEARING. SKIN: PROLONG/REPEAT CONTACT MAY CAUSE IRRITATION, DRY SKIN & DERMATITIS. INHALE: MAY CAUSE HEADACHES, DIZZINESS, NERVOUS SYSTEM DAMAGE. INGEST: MAY CAUSE IRRITATION OF DIGESTIVE TRACT, SIGNS OF NERVOUS SYSTEM DEPRESS-
DROWSY,DIZZY,NO COORDIN, FATIGUE.
Medical Cond Aggravated by Exposure:PRE-EXISTING DERMATITIS

===== First Aid Measures =====

First Aid:EYES: MOVE TO FRESH AIR. FLUSH EYES W/FRESH WATER. IF NEEDED,SEEK MEDICAL AID. SKIN: REMOVE CONTAM CLOTHES. WASH AFFECTED AREAS W/MILD SOAP & WATER. IF NEEDED,SEEK MEDICAL AID. INHALE: MOVE VICTIM TO FRESH AIR. GIVE CPR IF BREATHING STOPS,SEEK MEDICAL AID. INGEST: IF CONSCIOUS: INDUCE VOMITING (SYRUP OF IPE CAC AS DIRECTED BY DR). IF DROWSY LAY ON LEFT SIDE W/HEAD DOWN. DO NOT LEAVE VICTIM ALONE.

===== Fire Fighting Measures =====

Flash Point Method:SCC
Flash Point:105F,41C
Autoignition Temp:Autoignition Temp Text:480F
Lower Limits:1.0
Upper Limits:7.0
Extinguishing Media:WATER FOG, FOAM, DRY CHEMICAL OR CARBON DIOXIDE

===== Accidental Release Measures =====

Spill Release Procedures:LARGE SPILLS: BE UPWIND, AWAY FROM SPILL. ELIM ALL SOURCES OF IGNITE. USE INERT MAT'L TO DAM & CONTAIN. DO NOT FLUSH AREA W/WATER. ABSORB W/ABSORBENT PADS. SM SPILL: VENT AREA, ELIM IGNITE SOURCES. ABSORB W/ABSORBENT MATERIAL.

===== Handling and Storage =====

Handling and Storage Precautions:AVOID USE NEAR OPEN FLAMES AND OTHER SOURCES OF IGNITION. STORE IN DRY, COOL AREA.

===== Exposure Controls/Personal Protection =====

Respiratory Protection:USING SELF-CONTAINED

BREATHING APPARATUS IS

RECOMMENDED IF AIRBORNE VAPOR CONCENTRATION EXCEEDS THE LIMIT.

Ventilation:LOCAL EXHAUST MAY BE REQUIRED IF VAPOR EXCEEDS THE LIMIT.

Protective Gloves:IMPERVIOUS, CHEMICAL RESISTANT GLOVES

Eye Protection:CHEMICAL RESISTANT GOGGLES

Supplemental Safety and Health

===== Physical/Chemical Properties =====

HCC:F4

Boiling Pt:B.P. Text:313 TO 382F

Melt/Freeze Pt:M.P/F.P Text:NA

Decomp Temp:Decomp Text:NA

Vapor Pres:7.5

Vapor Density:9.0

Spec Gra

vity:1.12

pH:6.5

Viscosity:67-85 KU

Evaporation Rate & Reference:1.8 (BU AC=1)

Solubility in Water:NEGLIGIBLE

Appearance and Odor:LIQUID, SOLVENT ODOR

Percent Volatiles by Volume:69

Corrosion Rate:NA

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES

STRONG ACIDS, BASES AND OXIDIZERS

Hazardous Decomposition Products:CARBON MONOXIDE AND CARBON DIOXIDE

===== Disposal Considerations =====

Waste Dispo

sal Methods:DISPOSE IN ACCORDANCE WITH FEDERAL, STATE & LOCAL REGULATIONS.

Disclaimer (provided with this information by the compiling agencies):

This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume res

possibility for the suitability of this information to their particular situation.