

TECHNOLUBE PRODUCTS CO -- MIL-H-6083E, HYDRAULIC FLUID, PETROLEUM BASE --
9150-00-935-9810

===== Product Identification =====

Product ID: MIL-H-6083E, HYDRAULIC FLUID, PETROLEUM BASE

MSDS Date: 06/11/1991

FSC: 9150

NIIN: 00-935-9810

MSDS Number: BMTNW

=== Responsible Party ===

Company Name: TECHNOLUBE PRODUCTS CO

Address: 5814 EAST 61ST STREET

City: LOS ANGELES

State: CA

ZIP: 90040-3412

Country: US

Info Phone

Num: 213-928-3311

Emergency Phone Num: 213-928-3311

Preparer's Name: RICHARD J. EBERHARDT

CAGE: 8Y842

=== Contractor Identification ===

Company Name: LUBRICATING SPECIALTIES CO. TECHNOLUBE PRODUCTS DIV

Address: 3365 E. SLAUSON AVE

Box: City: LOS ANGELES

State: CA

ZIP: 90058

Country: US

Phone: 562-776-4033; FAX: 562-776-4003

CAGE: 8Y842

===== Composition/Information on Ingredients =====

Ingred Name: DISTILLATES, SOLVENT-REFINED LIGHT NAPHTHENIC

CAS: 64741-97-5

RTECS #: PY8041000

Fraction by Wt

: 199F, >93C

Extinguishing Media: USE CARBON DIOXIDE, FOAM, DRY CHEMICAL, OR WATER FOG.

Fire Fighting Procedures: FIRE FIGHTERS SHOULD USE NIOSH APPROVED SCBA & FULL PROTECTIVE EQUIPMENT WHEN FIGHTING CHEMICAL FIRE. USE WATER SPRAY TO COOL NEARBY CONTAINERS EXPOSED TO FIRE.

Unusual Fire/Explosion Hazard: SLIGHTLY COMBUSTIBLE, WHEN HEATED ABOVE FLASH POINT WILL RELEASE FLAMMABLE VAPORS WHICH CAN BURN IN OPEN OR BE EXPLOSIVE IN CONFINED SPACES IF IGNITED.

===== Accid

ental Release Measures =====

Spill Release Procedures:STOP FLOW. WIPE OR MOP UP OR ABSORB WITH DIATOMACEOUS EARTH OR OTHER INERT MATERIAL. STORE IN APPROPRIATE CONTAINER FOR DISPOSAL.

===== Handling and Storage =====

Handling and Storage Precautions:AVOID STORAGE NEAR OPEN FLAME OR OTHER SOURCES OF IGNITION. EXCESSIVE MISTING MAY CAUSE SLIPPERY FLOORS. PROPER FOOTWEAR REQUIRED.

Other Precautions:WASH OR TAKE SHOWER IF GENERAL CONTACT OCCURS. REMOVE OIL-SOAKED CLTHING AND LAUNEDER BEFORE REUSE. DISCARD CONTAMINATED LEATHER GLOVES AND SHOES.

===== Exposure Controls/Personal Protection =====

Respiratory Protection:NONE NORMALLY REQUIRED.

Ventilation:SUFFICIENT TO MAINTAIN ATMOSPHERE BELOW TLV LIMIT.

Protective Gloves:RECOMMENDED

Eye Protection:REQUIRED

Other Protective Equipment:CHEMICALLY RESISTANT BOOTS AND APRONS ARE RECOMMENDED.

Work Hygienic Practices:WASH HANDS WITH SOAP AND WAATER BEFORE EATING, DRINKING, OR SMOKING.

Supplemental Safety and Health

ITEM IS FOR MIL-H-6083, REV E., AMENDMENT 1. QPL TEST # H-6013. MANUFACTURER'S CODE FOR THE ITEM/MSDS='A0700'

===== Physical/Chemical Properties =====

HCC:V6

Boiling Pt:B.P. Text:>392F,>200C

Vapor Pres:1

Spec Gravity:0.876

Evaporation Rate & Reference:LESS THAN ETHER

Solubility in Water:NEGLIGIBLE

Appearance and Odor:RED, OILY LIQUID; PETROLEUM ODOR

Percent Volatiles by Volume:NIL

=====

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid: YES

STRONG OXIDIZING AGENTS

Stability Condition to Avoid: DO NOT HEAT ABOVE FLASH POINT

Hazardous Decomposition Products: CARBON MONOXIDE AND ASPHYXIANTS.

===== Disposal Considerations =====

Waste Disposal Methods: DISPOSE OF WASTE IN ACCORDANCE WITH LOCAL, STATE AND FEDERAL REGULATIONS.

Disclaimer (provided with this information by the compiling agencies):

T

his information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.