View NSN Online: https://aerobasegroup.ae/nsn/9330-01-074-1025 NEVAMAR CORP -- NEVAMAR LAMINATED PLASTIC -- 9330-01-074-1025 Product ID:NEVAMAR LAMINATED PLASTIC MSDS Date:10/01/1990 FSC:9330 NIIN:01-074-1025 MSDS Number: BMTYT === Responsible Party === Company Name: NEVAMAR CORP Address:8339 TELEGRAPH RD City:ODENTON State:MD ZIP:21113-1322 Country:US Info Phone Num:301-569-5000 Emergency Phone Num:301-569-5000 CAGE:92570 == = Contractor Identification === Company Name: NEVAMAR CORP Address:8339 TELEGRAPH RD Box:City:ODENTON State:MD ZIP:21113-1322 Country:US Phone:301-569-5000 CAGE:92570

======= Composition/Information on Ingredients ========

Ingred Name: NON HAZARDOUS INGREDIENT

Fraction by Wt: 100%

Other REC Limits: NONE SPECIFIED

========== Hazards Identification ===========================

Routes of Entry: Inhalation:YES Skin:NO Ingestion:NO Reports of Carcinogenicity:NTP:NO IARC:NO OS

HA:NO

Health Hazards Acute and Chronic:INHALATION-LAMINATE DUST IS SIMILIAR TO WOOD DUST WHICH HAS BEEN CLASSIFIED HAZARDOUS AS A NUISANCE DUST. EYE-IRRITATION MAY ARISE FROM EXCESSIVE NUISSANCE DUST, ETC.

Explanation of Carcinogenicity:THIS COMPOUND CONTAINS NO INGREDIENTS AT CONCENTRATIONS OF 0.1% OR GREATER THAT ARE CARCINOGENS OR SUSPECT CARCINOGENS.

Effects of Overexposure: NONE SPECIFIED BY MANUFACTURER.

Medical Cond Aggravated by Exposure: NONE SPECIFIED BY MANUFACTURER.

First Aid:INHALATION-NOT APPLICABLE. INGESTION-NOT APPLICABLE. SKIN-NOT APPLICABLE. EYE-IF EXPOSURE TO NUISSANCE DUST OCCURS, FLUSH THOROUGHLY FOR AT LEAST 15 MINUTES. CONTACT PHYSICIAN IF IRRITATION PERSISTS.

============= Fire Fighting Measures ========================

Autoignition Temp: Autoignition Temp Text: UNKNON

Extinguishing Media:USE DRY CHEMICAL, FOAM, WATER SPRAY, WATER FOG OR CARBON DIOXIDE TO

EXTINGUISH FIRES.

Fire Fighting Procedures: USE WATER SPRAY TO COOL FIRE EXPOSED SURFACES TO FIRE AND TO PROTECT PERSONNEL.

Unusual Fire/Explosion Hazard:CHARACTERISTICS ARE SIMILIAR TO WOOD AND PAPER PRODUCTS.

============= Handling and Storage ================

Handling and Storage Precautions: CHARACTERISTICS ARE SIMILIAR TO WOOD AND PAPER PRODUCTS.

Other Precautions: FOLLOW SAFE WORKING PRACTICES.

===== Exposure Controls/Personal Protection ========

Respiratory Protection: NOT NORMALLY REQUIRED. USE NIOSH APPROVED DUST RESPIRATOR IF DUST IS PROBLEM WHILE SAWING.

Ventilation:PROVIDE SUFFICIENT VENTILATION & DUST COLLECTION WHEN CUTTING MATERIAL. USE LOCAL EXHAUST TO KEEP DUST BELOW 10 MG/M3.

Protective Gloves: CLOTH GLOVES

Eye Protection: SAFETY GLASSES OR GOGGLES

Other Protective Equipment: NONE SPECIFIED BY MANUFACTURER.

Work Hygienic Practices: FOLLOW SAFE WORKING PRACTICES.

Supplemental Safety and Health

======= Physica

I/Chemical Properties ==========
HCC:N1 Boiling Pt:B.P. Text:NONE Spec Gravity:1.2 Solubility in Water:SLIGHT Appearance and Odor:SOLID SHEET; SLIGHT ODOR.
======== Stability and Reactivity Data =========
Stability Indicator/Materials to Avoid:YES NONE. Stability Condition to Avoid:NONE. Hazardous Decomposition Products:NONE.
======= Disposal Considerations ==========
Waste Disposal Methods:DISPOSE OF ALL DUST AND CHIPS VIA NORMAL SAN ITARY LANDFILL.
Disclaimer (provided with this information by the compiling agencies): This information is formulated for use by elements of the Department

of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their articular situation.