View NSN Online: https://aerobasegroup.ae/nsn/6830-00-281-3053

## MATHESON GAS PRODUCTS INC -- CARBON DIOXIDE, GAS -- 6830-00-281-3053

============= Product Identification ===============

Product ID:CARBON DIOXIDE,GAS

MSDS Date:06/30/1994

FSC:6830

NIIN:00-281-3053

MSDS Number: BMWHG === Responsible Party ===

Company Name: MATHESON GAS PRODUCTS INC

Address:30 SEAVIEW DR

Box:1587

City:SECACUS

State:NJ

ZIP:07094-1882

Country:US

Info Phone Num:201-867-4100 Emergency Phone Num:800-424-9

300 (CHEMTREC)

CAGE:0NPS5

=== Contractor Identification ===

Company Name: CENTRAL SCIENTIFIC CO (FORMERLY IN FRANKLIN PARK, IL.)

Address:8315 LEE HWY

Box:City:FAIRFAX

State:VA ZIP:22031 Country:US

Phone:800-621-4778

CAGE:11273

Company Name: MATHESON GAS PRODUCTS INC

Address:30 SEAVIEW DR

Box:1587 City:SECACUS State:NJ

ZIP:07094-1882 Country:US

Phone:800-424-9300 (CHEMTREC)

CAGE:0NPS5

====== Composition/Information on Ingredients ========

Ingred Name: CARBON DIOXIDE

CAS:124-38-9

**RTEC** 

S #:FF6400000 Fraction by Wt: 100%

Other REC Limits: NONE RECOMMENDED

OSHA PEL:5000 PPM

ACGIH TLV:5000PPM/30000STEL;96

========= Hazards Identification ============================

LD50 LC50 Mixture: NONE SPECIFIED BY MANUFACTURER.

Routes of Entry: Inhalation:YES Skin:YES Ingestion:NO Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO

Health Hazards Acute and Chronic: INHAL: RING IN EARS, NAU, IRREG

HEARTBEAT, HI BLOOD

PRESSURE,HEAD,WEAK,DROW,DIZZ,CONFUS,RESTLESSNESS,SLEEPLESNESS,T INGL

SENS,TWITCH,INTOLERANCE OF EYES TO LIGHT,VISUAL DISTURB,SUFFOCATION,CONVUL,UNCONSC,C OMA.MAY ALSO CAUSE REPRODUCTIVE

EFFECTS.SKIN:BLISTERS,FROSTBITE,NUMBNESS.EYE:IRRIT,FROSTBITE,BLUR VIS.INGEST:FROSTBITE.

Explanation of Carcinogenicity:PER MSDS:CARCINOGEN STATUS:OSHA/NTP/IARC:NO.

Effects of Overexposure: SEE HEALTH HAZARDS ABOVE.

Medical Cond Aggravated by Exposure:PERSONS W/HISTORY OF CARDIOVASCULAR OR PULMONARY IMPAIRMENT. TARGET EFFECTS:SIMPLE ASPHYXIANT.POISON ING

MAY AFFECT RESP & NERVOUS SYSTEMS & HEART.

First Aid:INHAL:REMOVE FRM EXPO TO FRESH AIR IMMED.PERFORM ART RESP IF NECESSARY.TREAT SYMPT/SUPP.GET MED ATTN IMMED.QUAL MED PERSON SHOULD CONSIDER ADMIN OXY.SKIN:UNLIKELY EMERG TREAT REQUIRED.ADVERSE EFFECTS OCCUR GET MED ATT.FROSTBITE/FREEZE/CRYOG BURN OCCUR WARM IN WARM WATER @TEMP 107F/USE BLANKETS.EXERCISE AFFECTED PART.EYE:UNLIKELY EMERG TREAT REQU

IRED.CONTACT W/LIQ/GAS

WASH W/LG ATM SOF WATER(SUPPL)

========== Fire Fighting Measures ===========================

Flash Point: N/AVAILABLE

Autoignition Temp: Autoignition Temp Text: N/DATA

Lower Limits:NO DATA Upper Limits:NO DATA

Extinguishing Media:DRY CHEMICAL, CARBON DIOXIDE,LF FIRE:USE WATER SPRAY,FOG OR REGULAR FOAM.

Fire Fighting Procedures:MOVE CNTNR FRM FIRE W/O RISK.COOL FIRE EXPO CNTNR SIDE W/WATER TIL AFT FIRE OUT.STAY AWAY FRM TK END.ISOLATE 1/2MI ALL DIRECTI

ONS IF TK/RAILCAR/(FIRE/EXPLO HAZ) Unusual Fire/Explosion Hazard: NEGLIGIBLE FIRE HAZARD WHEN EXPOSED TO HEAT/FLAME.FIREFIGHT:TANK TRUCK IN FIRE.WATERSPRAY TO ABSORB VAP.AVOID BREATH VAP; KEEP UPWIND. ======== Accidental Release Measures ============ Spill Release Procedures: DO NOT TOUCH SPILLED MATL. STOP LEAK W/O RISK.KEEP UNNECESSARY PEOPLE Neutralizing Agent: NONE SPECIFIED BY MANUFACTURER. ============= Handling and Storage ========================== ling and Storage Precautions: STORE AWAY FROM INCOMPATIBLE MATERIALS. Other Precautions: PROTECT FROM PHYSICAL DAMAGE. ===== Exposure Controls/Personal Protection ======== Respiratory Protection: NONE NORMALLY REQUIRED. USE SELF-CONTAINED BREATHING APPARATUS IF IDLH CONDITIONS ARE PRESENT OR SUSPECTED. Ventilation: USE ADEQUATE MECHANICAL VENTILATION. Protective Gloves: NONE NORMALLY REQUIRED. Eye Protection: SAFETY GLASSES Other Protective Equipment: CLOTHING TO PREVENT REPEAT **ED OR PROLONGED** CONTACT. Work Hygienic Practices: WASH HANDS AFTER USE AND BEFORE EATING, DRINKING, OR SMOKING. Supplemental Safety and Health ========= Physical/Chemical Properties =========== HCC:G3 Boiling Pt:B.P. Text:-109F,-78C Melt/Freeze Pt:M.P/F.P Text:-71F,-57C Decomp Temp:Decomp Text:NP Vapor Pres:43700 @21C

Vapor Density:1.5

Spec Gravity: 1.522 221C

pH:SUPPLE Viscosity:NP

Solubility in Water: SOLUBLE.

Appearance and Odor: COLORLESS, ODORLESS GAS W/SLIGHT ACIDIC

TASTE.	
Percent Volatiles by Volume:NP	
Corrosion Rate:NP	

========= Stability and Reactivity Data =========

Stability Indicator/Materials to Avoid:YES

ACROLEIN,BAO2,CEO,DIETHYL MAGNESIUM,HYDRAZINE,ETHYLENEEIMINE,METAL HYDRIDES/ACETYLIDES,METALS,K,K-NA ALLOY,NA2O2.

Stability Condition to Avoid:DO NOT PERMIT PHYS DMG OR OVERHEATING OF CNTNRS.CONTENTS UNDER PRESSRUE, MAY RUPTURE VIOL/TRAVEL CONSIDERABLE (SUPPLEMEN)

Hazardous Decomposition Products:TEMPERATURES ABOVE 17 00C MAY CAUSE

DECOMPOSITION & RELEASE OF OXYGEN & HIGHLY TOXIC CARBON DIOXIDE.

====== Disposal Considerations ==========

Waste Disposal Methods:DISPOSE OF IN ACCORDANCE WITHLOCAL, STATE AND FEDERAL REGULATIONS.

Disclaimer (provided with this information by the compiling agencies): This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.