

MOBIL OIL CORPORATION -- VACTRA OIL 2 -- 9150-00-045-4317

===== Product Identification =====

Product ID:VACTRA OIL 2

MSDS Date:09/24/1991

FSC:9150

NIIN:00-045-4317

MSDS Number: BMWPB

=== Responsible Party ===

Company Name:MOBIL OIL CORPORATION

Address:3225 GALLOWS ROAD

City:FAIRFAX

State:VA

ZIP:22037

Info Phone Num:800-662-4525/(703) 849-3265

Emergency Phone Num:703-849-3265/609-737-4411 COLLECT

CAGE:1G112

=== Contractor Identification ===

Company Name:MOBIL CHEMICAL CO., CHEMICAL COATINGS DIV.

Address:RT 27 AND VINEYARD RD.

Box:250

City:EDISON

State:NJ

ZIP:08818-0250

Country:US

Phone:609-737-4411 OR 800-424-9300

CAGE:77988

Company Name:MOBIL OIL CORPORATION

Address:3225 GALLOWS RD

City:FAIRFAX

State:VA

ZIP:22037-0001

Phone:(703) 846-1482

CAGE:1G112

===== Composition/Information on Ingredients =====

Ingred Name:MINERAL OIL/DISTILLATES (PETROLEUM), HYDROTREATED HEAVY

PARAFINIC/64742-54-7/64742-01-4/64742-62-7/64741-88-4

CAS:64742-65-0

RTECS #:PY8038500

Fraction by Wt: >95.00%

Other REC Limits:NONE SPECIFIED

OSHA PEL:5 MG/M3 AS OIL MIST

ACGIH TLV:5 MG/M3 AS OIL MIST

Ingred Name:ANIMAL FATTY OIL/OILS, LARD

CAS:8016-28-2

Fraction by Wt: 1.0%

Other REC Limits:NONE SPECIFIED

Ingred Name:TOLUENE (SARA III)

CAS:108-88-3

RTECS #:XS5250000

Fraction by Wt: 0.002%

Other REC Limits:NONE SPECIFIED

OSHA PEL:200 PPM/150 STEL

ACGIH TLV:50 PPM; 9293

EPA Rpt Qty:1000 L

BS

DOT Rpt Qty:1000 LBS

Ingred Name:ALKENES, C15-20 ALPHA-, POLYMERS W/COTTONSEED OIL AND  
SULFUR CAS NO. 68603-33-8.

Fraction by Wt: 350F,>177C

Lower Limits:0.6

Upper Limits:7.0

Extinguishing Media:WATER FOG, CO2, FOAM/DRY CHEMICAL. WATER SPRAY MAY  
BE USED TO KEEP FIRE EXPOSED CONTAINERS COOL & FLUSH SPILLS AWAY.

Fire Fighting Procedures:WEAR FULL PROTECTIVE CLOTHING AND  
NIOSH-APPROVED SELF-CONTAINED BREATHING APPARATUS WITH FULL  
FACEPIECE OPERATED IN THE POSITIVE PRESSURE MODE.

Unusual Fire/Explosion Hazard:NONE

===== Accidental Release Measures =====

Spill Release Procedures:ABSORB ON FIRE RETARDANT TREATED SAWDUST,  
DIATOMACEOUS EARTH, ETC. SHOVEL UP.

===== Handling and Storage =====

Handling and Storage Precautions:STORAGE-STORE IN COOL, VENTILATED  
AREA, IN TIGHTLY CLOSED CONTAINERS, AWAY FROM HEAT, FLAMES &  
OXIDIZERS.

Other Precautions:AVOID BREATHING VAPORS OR MISTS. DO NOT GET IN EYES,

ON SKIN OR ON CLOTHING. USE IN WELL VENTILATED AREA.

===== Exposure Controls/Personal Protection =====

Respiratory Protection:NO SPECIAL REQUIREMENTS UNDER ORDINARY  
CONDITIONS OF USE & W/ADEQUATE VENTILATION.

Ventilation:MECHANICAL (GENERAL AND/OR LOCAL EXHAUST, EXPLOSION-PROOF)  
VENTILATION TO MAINTAIN EXPOSURE BELOW TLV(S).

Protective Gloves:NO SPECIAL EQUIPMENT REQUIRED

Eye Protection:NO SPECIAL EQUIPMENT REQUIRED

Other Protective Equipment:EYE WASH STATION, QUICK  
DRENCH SHOWER AND  
IMPERVIOUS CLOTHING

Work Hygienic Practices:GOOD PERSONAL HYGIENE PRACTICES SHOULD ALWAYS  
BE FOLLOWED.

Supplemental Safety and Health

FORMULA CHANGED. FOR PREVIOUS FORMULATION, SEE PNI A UNDER THE SAME  
NSN.

===== Physical/Chemical Properties =====

HCC:V6

Boiling Pt:B.P. Text:>600F,>316C

Melt/Freeze Pt:M.P/F.P Text:20.0F,-6.7C

Vapor Pres: