

ANCHOR PAINT MANUFACTURING CO. INC. -- G0911 -- 8010-00-527-2053

=====  
Product Identification  
=====

Product ID:G0911

MSDS Date:06/19/1989

FSC:8010

NIIN:00-527-2053

MSDS Number: BMWTH

=== Responsible Party ===

Company Name:ANCHOR PAINT MANUFACTURING CO. INC.

Address:6707 E. 14TH ST.

Box:1305

City:TULSA

State:OK

ZIP:74101

Country:US

Info Phone Num:918-836-4626

Emergency Phone Num:918-836-4626

CAGE:

0E2V8

=== Contractor Identification ===

Company Name:ANCHOR PAINT MANUFACTURING CO INC

Address:6707 E 14TH STREET

Box:City:TULSA

State:OK

ZIP:74101

Country:US

Phone:918-836-4626

CAGE:0E2V8

=====  
Composition/Information on Ingredients  
=====

Ingred Name:CARBON BLACK

CAS:1333-86-4

RTECS #:FF5800000

Fraction by Wt: 2.95%

Other REC Limits:NONE SPECIFIED

OSHA PEL:3.5 MG/M3

ACGIH TLV:3.5 MG/M3; 9192

Ingred Name:HYDROTREATED LIGHT PETROLEUM DISTILLATE

CAS:64742-47-8

Fraction by Wt:

43.74%  
Other REC Limits:NONE SPECIFIED  
OSHA PEL:100 PPM  
ACGIH TLV:100 PPM

Ingred Name:XYLENES (O-,M-,P- ISOMERS) (SARA III)  
CAS:1330-20-7  
RTECS #:ZE2100000  
Fraction by Wt: 1.53%  
Other REC Limits:NONE SPECIFIED  
OSHA PEL:100 PPM/150 STEL  
ACGIH TLV:100 PPM/150STEL;9192  
EPA Rpt Qty:1000 LBS  
DOT Rpt Qty:1000 LBS

Ingred Name:NAPHTHA, LIGHT ALIPHATIC (PETROLEUM) (THIS MATERIAL  
CONTAINS UP TO 5 VOL.% BENZENE AND 20 VOL.% N-HEXANE)  
CAS:64742-89-8  
Fraction by Wt: 9.39%  
Other REC Limits:NONE SPECIFIE  
D

Ingred Name:SOYBEAN PHOSPHATIDES  
Fraction by Wt: .53%  
Other REC Limits:NONE SPECIFIED  
OSHA PEL:300 PPM TWA  
ACGIH TLV:300PPM TWA

=====  
===== Hazards Identification =====

Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES  
Health Hazards Acute and Chronic:INHALATION;CAN CAUSE NASAL OR  
RESPIRATORY IRRITATION, DIZZINESS, WEAKNESS, FATIGUE, NAUSEA,  
HEADACH AND POSSIBLE UNCONSCIUONESS AND EVEN ASPHYXIATION. EYES;  
SEVERE IRRITATION,REDDNESS,TEARING,BLUR  
RED VISION AND SEEING HALO  
AROUND LIGHTS.INGESTION;GASTROINTESTINAL IRRITATION NAUSEA  
VOMITING, ASPIRATION INTO LUNGS/FATAL  
Effects of Overexposure:NARCOTIC,DIZZINESS,NAUSEA,  
Medical Cond Aggravated by Exposure:PERSONS WITH SEVERE  
SKIN,LIVE,HEART, OR KIDNEY PROBLEMS SHOULD AVAOID USE.

=====  
===== First Aid Measures =====

First Aid:INHALATION;REMOVE TO FRESH AIR, GIVE CPR IF NECESSARY. SKIN;  
WASH WITH SOUAP AND WATER. EYES; FLUSH WITH PLENTY OF WA

TER FOR AT

LEAST 15 MINUTES, CONTACT A PHYSICIAN. INGESTION; DRINK 1-2 GLASSES OF WATER TO DILUTE, DO NOT INDUCE VOMITING, CONSULT PHYSICIAN OR POISON CONTROL IMMEDIATELY. TREAT SYMPTOMATICALLY.

===== Fire Fighting Measures =====

Flash Point Method:TCC

Flash Point:45.0F,7.2C

Lower Limits:0.9

Upper Limits:7.0

Extinguishing Media:CARBON DIOXIDE, FOAM, DRY CHEMICALS

Fire Fighting Procedures:WATER MAY BE INEFFECTIVE, WATER SHOULD BE USED TO COOL CO

NTAINER EXPOSED TO FIRE.

Unusual Fire/Explosion Hazard:FORMS COMBUSTIBLE AND OR EXPLOSIVE MIXTURES WITH AIR OR OXYGE.

===== Accidental Release Measures =====

Spill Release Procedures:PUMP OR TRANSFER TO ANOTHER CONTAINER OR ABSORB AND REMOVE FROM AREA, NOSPARKING TOOL SHOULD BE USED

Neutralizing Agent:NA

===== Handling and Storage =====

Handling and Storage Precautions:KEEP CONTAINERS CLOSED, DO NOT STORE OR USE NEAR

SPARKS, FLAMES OR IGNITION SOURCES.

Other Precautions:GROUND ALL CONTAINERS WHEN TRANSFERRING LIQUIDS, AVOID PROLONG CONTACT WITH SKIN, AVOID FREE FALL OF LIQUID, DO NOT FLAME CUT, SAW, DRILL BRAZE OR WELD EMPTY CONTAINER OR DRUMS.

===== Exposure Controls/Personal Protection =====

Respiratory Protection:IN CONFINED AREA USE NIOSH/MSHA RESPIRATOR

Ventilation:REQUIRED TO KEEP VAPOR CONCENTRATIONS BELOW TVLS

Protective Gloves:CHEMICAL RESISTANT

Eye Protection:TO PROTECT A

GAINST SPLASHED LIQUIDS,

Other Protective Equipment:CHEMICAL RESISTANT APRON

Work Hygienic Practices:REMOVE CONTAMINATED CLOTHING WASH BEFORE REUSE.

WASH HAND BEFORE EATING,SMOKING USING RESTROOM

Supplemental Safety and Health

NA

===== Physical/Chemical Properties =====

HCC:F2

Boiling Pt:B.P. Text:230F,110C

Vapor Pres:23MM

Vapor Density:3.7 > AIR

Spec Gravity:.894

Evaporation Rate & Reference:2.1

Solubility in Water:NEGIBLE

Appearance and Odor:LIQUID,AROMATI

C,SOLVENT ODOR

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES

STRONG OXIDIZERS

Stability Condition to Avoid:STRONG OXIDIZERS, OPEN FLAMES AND IGNITION SOURCES.

Hazardous Decomposition Products:CARBON MONOXIDE, CARBON DIOXIDE, OXIDES OF NITROGEN

Conditions to Avoid Polymerization:DOES NOT HEED SPONTANEOUSLY

===== Disposal Considerations =====

Waste Disposal Methods:INCINERATE OR DISPOSE OF IN ACCORDANCE WITH LOCAL,STATE AND FEDERAL REQUIREMENTS.

Disclaimer (provided with this information by the compiling agencies):  
This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.