

DAVLIN PAINT CO INC -- TT-P-19D EXTERIOR LATEX PC BTTP19D -- 8010-00-055-5100

=====
Product Identification
=====

Product ID:TT-P-19D EXTERIOR LATEX PC BTTP19D

MSDS Date:02/26/1991

FSC:8010

NIIN:00-055-5100

MSDS Number: BMXFM

=== Responsible Party ===

Company Name:DAVLIN PAINT CO INC

Box:2308

City:BERKELEY

State:CA

ZIP:94702

Country:US

Info Phone Num:415-848-2863

Emergency Phone Num:800-424-9300 C

HEMTREC

Preparer's Name:PATRICIA SHAW

CAGE:3Z268

=== Contractor Identification ===

Company Name:DAVLIN PAINT CO INC

Address:700 ALLSTON WAY

Box:2308

City:BERKELEY

State:CA

ZIP:94702

Country:US

Phone:510-848-2863

CAGE:3Z268

=====
Composition/Information on Ingredients
=====

Ingred Name:SILICA, QUARTZ (DUST)

CAS:14808-60-7

RTECS #:VV7330000

Fraction by Wt: 0.25%

Other REC Limits:NONE SPECIFIED

OSHA PEL:SEE TABLE Z3

ACGIH TLV:0.1 MG/M3 RDUST;9293

Ingred Name:ETHYLENE GLYCOL (S

ARA III)
CAS:107-21-1
RTECS #:KW2975000
Fraction by Wt: 3%
Other REC Limits:NONE SPECIFIED
ACGIH TLV:50 PPM
EPA Rpt Qty:1 LB
DOT Rpt Qty:1 LB

=====
===== Hazards Identification =====

Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES
Reports of Carcinogenicity:NTP:NO IARC:YES OSHA:NO
Health Hazards Acute and Chronic:INHAL: IRRITATION OF EYES, NOSE,
THROAT. EYE: IRRITANT. SKIN: SKIN IRRITATION ON PROLONGED OR
REPEATED CONTACT. CONTACT MAY RESULT IN
SKIN ABSORPTION, BUT
SYMPTOMS OF TOXICITY ARE NOT ANTICIPATED BY TH IS ROUTE. INGESTION:
GASTROINTESTINAL IRRITATION. CHRONIC OVEREXPOS: IRRIT TO NOSE,
THROAT & LUNGS.
Explanation of Carcinogenicity:CRYSTALLINE SILICA IS LISTED BY IARC AS
A CARCINOGEN.
Effects of Overexposure:SKIN CONTACT: SKIN DRYING, RASH UPON
PROLONGED/REPEATED CONTACT. INGESTION: VOMITING, NAUSEA, OR
DIARRHEA.
Medical Cond Aggravated by Exposure:DERMATITIS, RESPIRATORY TRACT
IRRITATION.

=====
===== First Aid Measures =====

First Aid:INHALATION: MOVE PERSON TO FRESH AIR. IF SYMPTOMS PERSIST
CONSULT A PHYSICIAN. EYE CONTACT: FLUSH W/LRG QTY CLEAN WATER 15
MIN, CALL PHYSICIAN. SKIN CONTACT: WASH THOROUGHLY WITH SOAP &
WATER. INGESTI ON: DRINK 1 OR 2 GLASSES OF WATER TO DILUTE. DO NOT
INDUCE VOMITING. CONSULT A PHYSICIAN OR POISON CONTROL CENTER
IMMEDIATELY. TREAT SYMPTOMATICALLY.

=====
===== Fire Fighting Measures =====

Flash Point Method:TCC
Flash Point:241F,116C
Lower Limits:3.2
Upper Limits:15.3
Extinguishing Media:FOAM, ALCOHOL FOAM, CO2, DRY CHEMICAL.
Fire Fighting Procedures:IF THIS MATERIAL IS INVOLVED IN A FIRE, NIOSH
APPROVED SELF-CONTAINED RESPIRATORY EQUIPMENT SHOULD BE WORN.
Unusual Fire/Explosion Hazard:VAPORS CAN COLLECT ABOVE LIQ IN CLSD
CNTNR & STORAGE VESSEL WHICH MAY FLASH IF EXPOS TO IGNIT SOURCE.
CLSD CNTNR MAY EXPLODE W/HEAT. SPLATTER ABOVE 100 F.

=====

Accidental Release Measures =====

Spill Release Procedures:KEEP SPECTATORS AWAY. FLOOR MAY BE SLIPPERY, USE CARE TO AVOID FALLING. DIKE & CONTAIN SPILL WITH INERT MATERIAL. TRANSFER LIQUID & DIKING MATERIAL TO CONTAINERS FOR RECOVERY AND DISPOSAL. KEEP SPILLS OUT OF SEWERS AND OPEN WATER.

===== Handling and Storage =====

Handling and Storage Precautions:DO NOT STORE ABOVE 100 F. KEEP FROM FREEZING.

Other Precautions:DO NOT TAKE INTERNALLY. KEEP CONTAINERS CLOSED WHEN NOT IN USE.

===== Exposure Controls/Personal Protection =====

Respiratory Protection:USE AN APPROPRIATE PROPERLY FITTED RESPIRATOR (NIOSH/MSHA) DURING & AFTER APPLICATION UNLESS AIR MONITORING DEMONSTRATES VAPOR/MIST LEVELS ARE BELOW APPLICABLE LIMITS. FOLLOW RESPIRATOR MANUFACTURER'S DIRECTIONS FOR RESPIRATOR USE.

Ventilation:PROVIDE SUFFICIENT VENTILATION TO CONTROL EXPOSURE LEVELS BELOW AIRBORN EXPOSURE LIMITS.

Protective Gloves:CONSULT GLOVE MFR FOR APPROPRIATE TYPE

Eye Protection:CHEM SAFETY GLASSES, GOGGLES

Other Protective Equipment:PROTECTIVE CLOTHING WHENEVER POSSIBLE TO PREVENT REPEATED OR EXTENDED EXPOSURE OF SKIN.

Work Hygienic Practices:WASH HANDS AFTER USING. REMOVE WET PAINT FROM SKIN WITH WATER BEFORE IT DRIES.

Supplemental Safety and Health

===== Physical/Chemical Properties =====

HCC:N1

Boiling Pt:B.P. Text:212 TO 471F

Vapor Density:< AIR

Spec Gravity

ty:1.4 (WATER=1)

Evaporation Rate & Reference:SLOWER THAN ETHER.

Solubility in Water:DILUTABLE.

Appearance and Odor:PIGMENTED LIQUID.

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES

Hazardous Decomposition Products:UNDER SEVERE THERMAL DEGRADATION, LOW MOLECULAR WEIGHT HYDROCARBONS MAY BE FORMED.

===== Disposal Considerations =====

Waste Disposal Methods:KEEP OUT OF DRAINS, SEWERS, AND WASTE

RWAYS. LAND

FILL OR INCINERATE ACCORDING TO LOCAL, STATE, AND FEDERAL REGULATIONS.

Disclaimer (provided with this information by the compiling agencies):

This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and

assume responsibility for the suitability of this information to their particular situation.