

DAVLIN PAINT COMPANY -- TT-P-19D EXTERIOR LATEX, BTTP19D -- 8010-00-823-7962

=====
Product Identification
=====

Product ID:TT-P-19D EXTERIOR LATEX, BTTP19D

MSDS Date:02/26/1991

FSC:8010

NIIN:00-823-7962

MSDS Number: BMXJC

=== Responsible Party ===

Company Name:DAVLIN PAINT COMPANY

Box:2308

City:BERKELEY

State:CA

ZIP:94702

Country:US

Info Phone Num:415-848-2863

Emergency Phone Num:800-424-9300 CHE

MTREC

Preparer's Name:PATRICIA SHAW

CAGE:HO931

=== Contractor Identification ===

Company Name:DAVLIN PAINT CO INC

Address:700 ALLSTON WAY

Box:2308

City:BERKELEY

State:CA

ZIP:94702

Country:US

Phone:510-848-2863

CAGE:3Z268

Company Name:DAVLIN PAINT COMPANY

Box:2308

City:BERKELEY

State:CA

ZIP:94702

Country:US

Phone:415-848-2863

CAGE:HO931

=====
Composition/Information on Ingredients
=====

Ingred Name:SILICA, QUARTZ

CAS:14808-60-7

RTECS #:VV7330000

Fraction by Wt: 0.25%

Other REC

Limits:NONE SPECIFIED
OSHA PEL:SEE TABLE Z3
ACGIH TLV:0.1 MG/M3 RDUST;9293

Ingred Name:ETHYLENE GLYCOL (SARA III)
CAS:107-21-1
RTECS #:KW2975000
Fraction by Wt: 3%
Other REC Limits:NONE SPECIFIED
ACGIH TLV:50 PPM
EPA Rpt Qty:1 LB
DOT Rpt Qty:1 LB

===== Hazards Identification =====

Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES
Reports of Carcinogenicity:NTP:NO IARC:YES OSHA:NO
Health Hazards Acute and Chronic:INHALATION: EYES, NOSE, THROAT

IRRITATION. EYE: IRRITANT. SKIN: IRRITATION. CONTACT MAY RESULT IN SKIN ABSORPTION, BUT SYMPTOMS OF TOXICITY ARE NOT ANTICIPATED BY THIS ROUTE. INGESTION: CAN CAUSE GAST ROINTESTINAL IRRITATION. CHRONIC OVEREXPOS: NOSE, TROAT, LUNG IRRITATION.
Explanation of Carcinogenicity:CRYSTALLINE SILICA IS LISTED BY IARC AS A CARCINOGEN.
Effects of Overexposure:SKIN: RASH, SKIN DRYING. INGESTION: VOMITING, NAUSEA, OR DIARRHEA.
Medical Cond Aggravated by Exposure:DERMATITUS, RESPIRATORY TRACT IRRITATION.

===== First Aid Measures =====

First Aid:INHALATION: MOVE PERSON TO FRESH AIR. IF SYMPTOMS PERSIST CONSULT PHYSICIAN. EYE: FLUSH W/LARGE QTY OF CLEAN WATER FOR 15 MIN & CALL PHYSICIAN. SKIN: WASH THOROUGHLY WITH SOAP AND WATER. INGESTION: DR INK 1 OR 2 GLASSES OF WATER TO DILUTE. DO NOT INDUCE VOMITING. CONSULT A PHYSICIAN OR POISON CONTROL CENTER IMMEDIATELY. TREAT SYMPTOMATICALLY.

===== Fire Fi

ghting Measures =====

Flash Point Method:TCC

Flash Point:241F,116C

Lower Limits:3.2%

Upper Limits:15.3%

Extinguishing Media:FOAM, ALCOHOL FOAM, CO2, DRY CHEMICAL.

Fire Fighting Procedures:IF THIS MATERIAL IS INVOLVED IN A FIRE, NIOSH APPROVED SELF-CONTAINED RESPIRATORY EQUIPMENT SHOULD BE WORN.

Unusual Fire/Explosion Hazard:VAPORS CAN COLLECT ABOVE LIQ IN CLSD CNTNR & STORAGE VESSEL WHICH MAY FLASH IF EXPOS TO IGNIT SOURCE. CLSD CNTNR MAY EXPLODE W/HEAT. MAT'L SPLAT TERS ABOVE 100F.

===== Accidental Release Measures =====

Spill Release Procedures:KEEP SPECTATORS AWAY. FLOOR MAY BE SLIPPERY, USE CARE TO AVOID FALLING. DIKE & CONTAIN SPILL WITH INERT MATERIAL. TRANSFER LIQUID & DIKING MATERIAL TO CONTAINERS FOR RECOVERY AND DISPOSAL. KEEP SPILLS OUT OF SEWERS AND OPEN WATER.

===== Handling and Storage =====

Handling and Storage Precautions:DO NOT STORE ABOVE 100 F. KEEP FROM FR EEZING.

Other Precautions:DO NOT TAKE INTERNALLY. KEEP CONTAINERS CLOSED WHEN NOT IN USE.

===== Exposure Controls/Personal Protection =====

Respiratory Protection:USE AN APPROPRIATE, PROPERLY FITTED RESPIRATOR (NIOSH/MSHA) DURING AND AFTER APPLICATION UNLESS AIR MONITORING DEMONSTRATES VAPOR/MIST LEVELS ARE BELOW APPLICABLE LIMITS. FOLLOW RESPIRATOR MANUFACTURE R'S DIRECTIONS FOR RESPIRATOR USE.

Ventilation:PROVIDE SUFFICIENT VENT TO CONTROL EXPOSURE LEVELS BE LOW AIRBORN EXPOSURE LIMITS.

Protective Gloves:SEE GLOVE MFR TO DETERMINE APPROP TYPE.

Eye Protection:CHEM SAFETY GLASSES, GOGGLES

Other Protective Equipment:USE PROTECTIVE CLOTHING WHENEVER POSSIBLE TO PREVENT REPEATED OR EXTENDED EXPOSURE OF SKIN.

Work Hygienic Practices:WASH HANDS AFTER USING. REMOVE WET PAINT FROM SKIN WITH WATER BEFORE IT DRIES.

Supplemental Safety and Health

===== Physical/Chemical Properties =====

Boiling Pt:B.P. Text:212 TO 471F

Vapor Density:< AIR
Spec Gravity:1.4 (WATER=1)
Evaporation Rate & Reference:SLOWER THAN ETHER.
Solubility in Water:DILUTABLE.
Appearance and Odor:PIGMENTED LIQUID.

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES
Hazardous Decomposition Products:UNDER SEVERE THERMAL DEGRADATION, LOW
MOLECULAR WEIGHT HYDROCARBONS MAY BE FORMED.

===== Disposal Considerations =====

Waste Disposal Methods:KEEP OUT OF DRAINS, SEWERS AND WATERWAYS. LAND
FILL OR INCINERATION ACCORDING TO LOCAL, STATE AND FEDERAL
REGULATIONS.

Disclaimer (provided with this information by the compiling agencies):
This information is formulated for use by elements of the Department
of Defense. The United States of America in no manner whatsoever,
expressly or implied, warrants this information to be accurate and
disclaims all liability for its use. Any person utilizing this
document should seek competent professional advice to verify and
assume responsibility for the suitability of this information to their
particular situation.