

DESOTO INC -- SD AL POLY ACTIVATOR PC 910X376 -- 8010-00-181-8302
===== Product Identification =====

Product ID:SD AL POLY ACTIVATOR PC 910X376

MSDS Date:01/01/1987

FSC:8010

NIIN:00-181-8302

Kit Part:Y

MSDS Number: BMZBL

=== Responsible Party ===

Company Name:DESOTO INC

Address:1700 S MT PROSPECT RD

City:DES PLAINES

State:IL

ZIP:60018-1804

Country:US

Info Phone Num:708-391-9000 / FAX 708-624-9420

Emergency Phone Num:708-391-9000

Preparer's Name:SHERRIE M STEVENSON

CAGE:62758

=== Contractor Identification ===

Company Name:DESOTO INC

Address:1700 S MT PROSPECT RD

City:DES PLAINES

State:IL

ZIP:60018-1804

Country:US

Phone:708-391-9000

CAGE:62758

===== Composition/Information on Ingredients =====

Ingred Name:METHYL N-AMYL KETONE (VAPOR PRESSURE 2.1 MM HG)

CAS:110-43-0

RTECS #:MJ5075000

Fraction by Wt: 30%

Other REC Limits:NONE SPECIFIED

OSHA PEL:100 PPM

ACGIH TLV:50 PPM

ingred Name:CYCLOHEXANONE (SARA III) (VAPOR PRESSURE 2.0 MM HG)
CAS:108-94-1
RTECS #:GW1050000
Fraction by Wt: 5%
Other REC Limits:NONE SPECIFIED
OSHA PEL:S, 50 PPM
ACGIH TLV:S, 25 PPM; 9293
EPA Rpt Qty:5000 LBS
DOT Rpt Qty:5000 LBS

ingred Name:METHYL ETHYL KETONE (SARA III) (VAPOR PRESSURE 9.5 MM HG)
CAS:78-93-3
RTECS #:EL6475000
Fraction by Wt: 25%
Other REC Limits:NONE SPECIFIED
OSHA PEL:200 PPM/300 PPM STEL
ACGIH TLV:200 PPM
EPA Rpt Qty:5000 LBS
DOT Rpt Qty:5000 LBS

ingred Name:XYLENE (SAR
A III) (VAPOR PRESSURE 10.0 MM HG)
CAS:1330-20-7
RTECS #:ZE2100000
Fraction by Wt: 5%
Other REC Limits:NONE SPECIFIED
OSHA PEL:100 PPM/150 PPM STEL
ACGIH TLV:100 PPM
EPA Rpt Qty:1000 LBS
DOT Rpt Qty:1000 LBS

ingred Name:TOLUENE (SARA III)
CAS:108-88-3
RTECS #:XS5250000
Fraction by Wt: AIR.
Spec Gravity:10.46 LBS/GAL
Evaporation Rate & Reference:SLOWER THAN N-BUTYL AC
Appearance and Odor:LIQUID, SOLVENT ODOR.
Percent Volatiles by Volume:59

===== Stability and Reactivity Data

=====

Stability Indicator/Materials to Avoid: YES

AVOID CONTACT WITH WATER, ALCOHOLS AND AMINES.

Stability Condition to Avoid: NONE RECOGNIZED UNLESS NOTED BELOW.

TEMPERATURES ABOVE MAXIMUM STORAGE TEMPERATURES.

Hazardous Decomposition Products: COMBUSTION PROD ARE HAZARDOUS

INCLUDING CO & CO2 MAY ALSO INCLUDE NITROGEN OXIDES & TRACES OF HCN
& ISOCYANATE MONOMER.

===== Disposal Considerations =====

Waste Disposal Methods: ENSURE THAT MAT'L

IS PACKAGED, STORED,

TRANSPORTED & MANAGED IN ACCORD W/LOCAL, STATE & FEDERAL REGS. NO
DISPOSAL METHOD IS TO BE USED THAT WOULD POSE AN ENVIRONMENTAL OR
HUMAN HEALTH THREAT INCLUDING ANY WHICH WOULD CONTAMINATE
GROUND/SURFACE WATER.

Disclaimer (provided with this information by the compiling agencies):

This information is formulated for use by elements of the Department
of Defense. The United States of America in no manner whatsoever,
expressly or implied, warrants this in

formation to be accurate and

disclaims all liability for its use. Any person utilizing this
document should seek competent professional advice to verify and
assume responsibility for the suitability of this information to their
particular situation.