

NASHUA CORPORATION -- XEROX FUSER LUBRICANT FL-45,FL-75 -- 6850-01-164-5738

=====  
Product Identification  
=====

Product ID:XEROX FUSER LUBRICANT FL-45,FL-75

MSDS Date:06/28/1990

FSC:6850

NIIN:01-164-5738

MSDS Number: BMZZQ

=== Responsible Party ===

Company Name:NASHUA CORPORATION

Address:44 FRANKLIN STREET

City:NASHUA

State:NH

ZIP:03061

Country:US

Info Phone Num:800-258-1370

Emergency Phone Num:603

-880-5555

Preparer's Name:R.L. SEVIGNY

CAGE:0EK44

=== Contractor Identification ===

Company Name:NASHUA CORP OFFICE PRODUCTS DIV.

Address:44 FRANKLIN ST

Box:City:NASHUA

State:NH

ZIP:03060

Country:US

Phone:603-880-2323

CAGE:34936

Company Name:NASHUA CORPORATION

Address:44 FRANKLIN STREET

City:NASHUA

State:NH

ZIP:03061

Country:US

Phone:603-880-5555

CAGE:0EK44

=====  
Composition/Information on Ingredients  
=====

Ingred Name:POLYDIMETHYLSILOXANE

CAS:63148-62-9

RTECS #:JT6485000

Fra

ction by Wt: 100.0%

===== **Hazards Identification**=====

Routes of Entry: Inhalation:UNKNOWN Skin:UNKNOWN Ingestion:YES  
Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO  
Health Hazards Acute and Chronic:NO KNOWN CHRONIC OR CACUTE HAZARDS  
WHEN USED AS INTENDED.  
Explanation of Carcinogenicity:NOT RELAVENT  
Effects of Overexposure:MAY CAUSE TEMPORARY DISCOMFORT TO EYES;HAS A  
LAXATIVE EFFECT UPON INGESTION.  
Medical Cond Aggravated by Exposure:NONE KNOWN  
TO MFR

===== **First Aid Measures**=====

First Aid:SKIN:WASH WITH SOAP & WATER. EYES:FLUSH EYES WITH WATER FOR  
15 MINUTES,CALL A PHYSICIAN. INGESTED:DRINK WATER AND CALL POISON  
CONTROL CENTER.

===== **Fire Fighting Measures**=====

Flash Point Method:OC  
Flash Point:600F/316C  
Extinguishing Media:WATERFOG,CO\*2,DRY CHEMICAL,FOAM.  
Fire Fighting Procedures:SELF CONTAINED BREATHING APPARATUS, PROTECTIVE  
CLOTHING.  
Unusual  
Fire/Explosion Hazard:NONE KNOWN TO MFR.

===== **Accidental Release Measures**=====

Spill Release Procedures:USE ABSORBENT MATERIAL TO COLLECT AND CONTROL  
SP[ILLAGE.  
Neutralizing Agent:NO INFORMATION GIVEN ON MSDS BY SUPPLIER

===== **Handling and Storage**=====

Handling and Storage Precautions:AVOID RUBBING EYES WITH HANDS WHILE  
USING THIS MATERIAL.CLEAN UP SPILLS COMPLETELY AS RESIDUE IS  
SLIPPERY.  
Other Precautions:CLEAN U

P SPILLS COMPLETELY AS RESIDUE IS SLIPPERY.

UPON EYE CONTACT, REMOVE AND CLEAN CONTACT LENSES PRIOR TO REUSE.

===== Exposure Controls/Personal Protection =====

Respiratory Protection:NOT REQUIRED.

Ventilation:NONE REQUIRED.

Protective Gloves:NONE REQUIRED

Eye Protection:SAFETY GLASSES.

Other Protective Equipment:NONE REQUIRED.

Work Hygienic Practices:USE GOOD INDUSTRIAL HYGIENE PRACTICE. WASH  
AFTER USING THE PRODUCT AND BEFORE EATING, DRINKING, ETC.

Supplemental Saf

ety and Health

MSDS RECEIVED FROM NAVY (FOCAL POINT N). NAVY IDENTIFIED NSN.

===== Physical/Chemical Properties =====

HCC:N1

Boiling Pt:B.P. Text:>600F/316C

Vapor Pres: