

HYSOL DIVISION, THE DEXTER CORPORATION -- EPK 11C KIT PART B (HARDENER) --  
8040-01-004-1031

=====  
===== Product Identification =====

Product ID:EPK 11C KIT PART B (HARDENER)

MSDS Date:10/25/1984

FSC:8040

NIIN:01-004-1031

Kit Part:Y

MSDS Number: BNCHH

=== Responsible Party ===

Company Name:HYSOL DIVISION, THE DEXTER CORPORATION

Address:211 FRANKLIN ST.

City:OLEAN

State:NY

ZIP:14760

Country:US

Info Phone

Num:716-372-6300

Emergency Phone Num:716-372-6300

Preparer's Name:JAMES HORNBURG

CAGE:14347

=== Contractor Identification ===

Company Name:DEXTER CORP THE DEXTER ELECTRONIC MATERIAL DIV

Address:211 FRANKLIN ST.

Box:City:OLEAN

State:NY

ZIP:14760-1297

Country:US

Phone:716-372-6300/6309

CAGE:04347

Company Name:HYSOL DIVISION, THE DEXTER CORPORATION

Box:312

CAGE:14347

=====  
===== Composition/Information on Ingredients =====

Ingred Name:DIETHYLENETRIAMINE

CAS:111-40-0

RTECS #:IE1225000

Fraction by Wt: 12%  
Other REC Limits:NONE SPECIFIED  
ACGIH TLV:1 PPM

Ingred Name:TALC  
CAS:14807-96-6  
RTECS #:WW2710000  
Fraction by Wt: 42%  
Other REC Limits:NONE SPECIFIED

Ingred Name:SILICA #  
Fraction by Wt: 15%  
Other REC Limits:NONE SPECIFIED

Ingred Name:# FILLER PARTICLES ARE THOROUGHLY WETTED BY VEHICLE SO  
AIRBORNE EXPOSURE DOES NOT OCCUR UNLESS CURED MATERIAL IS ##  
RTECS #:9999999ZZ  
Other REC Limits:NONE SPECIFIED

Ingred Name:## SUBSEQUENTLY GROUND, MACHINED OR SANDED.  
RTECS #:999999  
9ZZ  
Other REC Limits:NONE SPECIFIED

=====  
===== Hazards Identification =====

Health Hazards Acute and Chronic:CAUSES SEVERE EYE AND SKIN BURNS.  
PRODUCT IS A STRONG SKIN SENSITIZER.

=====  
===== First Aid Measures =====

First Aid:IN CASE OF SKIN CONTACT WASH IMMEDIATELY WITH SOAP AND WATER.  
IN CASE OF EYE CONTACT FLUSH WITH COPIOUS AMOUNTS OF WATER FOR AT  
LEAST 15 MINUTES. CONSULT A PHYSICIAN.

=====  
===== Fire  
Fighting Measures =====

Flash Point Method:OC  
Flash Point:215F,102C  
Extinguishing Media:USE WATER SPRAY, DRY CHEMICAL, ALCOHOL FOAM, OR  
CO2.  
Fire Fighting Procedures:USE WATER TO KEEP FIRE-EXPOSED CONTAINERS  
COOL. WATER SPRAY MAY BE USED TO FLUSH SPILLS AWAY FROM EXPOSURES &  
TO DILUTE SPILLS TO NONFLAMMABLE MIXTURES.  
Unusual Fire/Explosion Hazard:CARE MUST BE TAKEN TO PREVENT IGNITION  
WHEN PROCESSING OR HANDLING AT TEMPERATURES ABOVE THE FLASH POINT.

=====

===== Accidental Release Measures =====

Spill Release Procedures:SCRAPE UP EXCESS, TRANSFER TO METAL CONTAINER.

===== Handling and Storage =====

Handling and Storage Precautions:PROTECT FROM PHYSICAL DAMAGE. STORE IN A COOL, DRY, WELL VENTILATED AREA AWAY FROM ANY AREA WHERE FIRE HAZARD MAY BE ACUTE.

Other Precautions:IS A STRONG SKIN SENSITIZER. AVOID SKIN CONTACT.

===== Exposure Controls/Personal Protection =====

=

Respiratory Protection:N/K

\*DO NOT RECIRCULATE UNLESS SCRUBBED WITH ACID.

Ventilation:WHERE COMPARATIVELY SMALL AMOUNTS ARE BEING USED, VENTILATION SHOULD MOVE AIR OVER THE WORK & AWAY FROM WORKER. \*

Protective Gloves:PLASTIC OR RUBBER

Eye Protection:GOGGLES WHERE THERE IS DANGER OF SPLASH.

Other Protective Equipment:USE OF PROTECTIVE SKIN CREAM IS RECOMMENDED.

Supplemental Safety and Health

===== Physical/Chemical Properties =====

S =====

Boiling Pt:B.P. Text:404F,207C

Vapor Pres: