View NSN Online: https://aerobasegroup.ae/nsn/6550-01-317-4927

Product ID:57011 FORMALIN MSDS Date:07/24/1992 FSC:6505 NIIN:01-317-4927 MSDS Number: BNKLZ === Responsible Party === Company Name: BIOCHEMICAL SCIENCES INC SUB OF CMS Address:603 HERRON DR Box:518 City:BRIDGEPORT State:NJ ZIP:08014-0518 Country:US Info Phone Num:609-467-1813/800-524-0294 Em ergency Phone Num:508-651-1250/800-524-0294 CAGE:0B0Y1 === Contractor Identification === Company Name: BIOCHEMICAL SCIENCES INC Address:200 COMMODORE DRIVE Box:City:SWEDESBORO State:NJ ZIP:08085 Country:US Phone:800-524-0294 CAGE:0B0Y1 Ingred Name: FORMALDEHYDE, FORMALIN (2A CARCINOGEN BY NTP, IARC, OSHA) INTENDED CHANGE

CAS:50-00-0 RTECS #:LP8925000 Fraction by Wt: 3.4-4% OSHA PEL:0.75 PPM/2 PPM ACGIH TLV:0.37 MG/CUM IC (2A) EPA Rpt Qty:100 LBS DOT Rpt Qty:100 LBS

======================================
Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES Reports of Carcinogenicity:NTP:YES IARC:YES OSHA:YES Health Hazards Acute and Chronic:IRRITATION OF SKIN, EYES, NOSE, THROAT & UPPER RESPIRATORY TRACT. INGESTION: POISONOUS, MAY CAUSE BURNING OF MOUTH; DEATH MAY RESULT. CHRONIC: FORMALDEHYDE IS A MUTAGENIC. Explanation of Carcinogenicity:SEE INGREDIENTS Effects o
f Overexposure:INGESTION: VOMITING, ABDOMINAL PAIN & DIARRHEA. Medical Cond Aggravated by Exposure:DISEASES OF THE LUNGS & SKIN
Medical Cond Aggravated by Exposure. DISEASES OF THE LONGS & SKIN
======================================
First Aid:SKIN: REMOVE CONTAMINATED CLOTHING. WASH AREA W/PLENTY OF SOAP & WATER. EYES: FLUSH W/PLENTY OF WATER FOR 15 MINS. INGESTION: INDUCE VOMITING IMMEDIATELY BY GIVING TWO GLASSES OF WATER & PRESSING FING ER DOWN THROAT. CONTACT A PHYSICIAN IMMEDIATELY. INHALATION: REMOVE TO FRE SH AIR. IF BREATHING STOPS, BEGIN ARTIFICIAL RESPIRATION. OBTAIN MEDICAL ATTENTION IN ALL CASES.
======================================
Extinguishing Media:DRY POWDER, FOAM, CO2, WATER SPRAY Fire Fighting Procedures:WEAR SELF-CONTAINED BREATHING APPARATUS & PROTECTIVE CLOTHING.
======================================
Spill Release Procedures:WIPE UP W/DAMP SPONGE OR MOP. LARGE: ABSORB LIQUID W/SAND OR SIMILAR MATERIAL & KE EP FROM ANY FORMS OF IGNITION.
======================================
Handling and Storage Precautions: USE PRECAUTIONS FOR COMBUSTIBLE LIQUIDS. KEEP AWAY FROM OPEN FLAMES.
======================================
Respiratory Protection:IF VAPOR CONCENTRATION BECOMES HIGH, USE NIOSH APPROVED RESPIRATOR. Ventilation:LOCAL EXHAUST Protective Gloves:RUBBER Eye Protection:SAFETY GLASSES Other Protective Equipment:NORMAL LABORATOR

## Y APPAREL Work Hygienic Practices:WASH W/SOAP & WATER AFTER HANDLING. Supplemental Safety and Health

Boiling Pt:B.P. Text:215F Vapor Pres:79 Vapor Density:>1 Spec Gravity:1.07 Evaporation Rate & amp; Reference:AS WATER Solubility in Water:COMPLETE Appearance and Odor:COLORLESS LIQUID W/CHARACTERISTIC ODOR

Stability Indicator/Materials to Avoid:YES CAUSTIC SO DA, ASH & ALKALIS, AMINES, ACIDS & STRONG OXIDIZING AGENTS Hazardous Decomposition Products:BURNING MAY PRODUCE CO & CO2 S

Conditions to Avoid Polymerization:HEAT, SPARKS, FLAME

Waste Disposal Methods:DISPOSE OF IN ACCORDANCE W/LOCAL, STATE, & FEDERAL REGULATIONS.

Disclaimer (provided with this information by the compiling agencies): This information is formulated for use by elements of the Department o

f Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.