View NSN Online: https://aerobasegroup.ae/nsn/6750-00-965-4846

## EASTMAN KODAK COMPANY -- KODAK RAPID FIXER, PART A; CAT NO 146 4106 -- 6750-00-965-4846

========= Product Identification ==============

Product ID:KODAK RAPID FIXER, PART A; CAT NO 146 4106

MSDS Date:01/30/1990

FSC:6750

NIIN:00-965-4846

MSDS Number: BNMRS === Responsible Party ===

Company Name: EASTMAN KODAK COMPANY

Address:343 STATE STREET

City:ROCHESTER

State:NY ZIP:14650 Country:US

Info Phone Num:716-722-5151

Em

ergency Phone Num:716-722-5151

Preparer's Name: HEALTH & ENVIRONMENTAL LB

CAGE:19139

=== Contractor Identification ===

Company Name: EASTMAN KODAK CO GOVERNMENT MARKETS CONTRACTS

Address:343 STATE ST Box:City:ROCHESTER

State:NY

ZIP:14650-1115 Country:US

Phone:716-722-5151/(800) 242-2424

CAGE:19139

======= Composition/Information on Ingredients ========

Ingred Name:WATER

CAS:7732-18-5

RTECS #:ZC0110000 Fraction by Wt: 40-50%

Other REC Limits: NONE RECOMMENDED

Ingred Name: AMMONIUM THI

**OSULFATE** CAS:7783-18-8 RTECS #:XN6465000 Fraction by Wt: 40-45% Other REC Limits: NONE RECOMMENDED Ingred Name:SODIUM ACETATE CAS:126-96-5 RTECS #:AJ4375000 Fraction by Wt: 127-093% Other REC Limits: NONE RECOMMENDED Ingred Name:BORIC ACID CAS:10043-35-3 RTECS #:ED4550000 Fraction by Wt: 1-5% Other REC Limits: NONE RECOMMENDED Ingred Name: ACETIC ACID (SARA III) CAS:64-19-7 RTECS #:AF1225000 Fraction by Wt: 1-5% Other REC Limits: NONE RECOMMENDED **OSHA PEL:10 PPM** ACGIH TLV:10 PPM/15 STEL; 9293 **EPA** Rpt Qty:5000 LBS DOT Rpt Qty:5000 LBS LD50 LC50 Mixture:LD50 O/RAT20ML/KG Routes of Entry: Inhalation:NO Skin:NO Ingestion:YES Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO Health Hazards Acute and Chronic:INHAL:LOW HAZARD FOR RECOMMENDED HANDLING.EYES:MAY CAUSE TRANSIENT IRRITATION.SKIN:LOW HAZARD FOR RECOMMENDED HANDLING.INGEST: EXPECTED TO BE LOW INGESTION HAZARD. Effects of Overexposure:EYES:IRRITATION. Me dical Cond Aggravated by Exposure:NOT REPORTED. 

First Aid:EYES:FLUSH WITH PLENTY OF WATER.INGEST:IF CONSCIOUS,DRINK 1-2 GLASSES OF WATER;GET PROMPT QUALIFIED MEDICAL ATTENTION.SKIN:NOT REPORTED.INHAL:NOT REPORTED.

============== Fire Fighting Measures =======================

Flash Point:NONE

Extinguishing Media: USE APPROPRIATE AGENT FOR SURROUNDING FIRE.

Fire Fighting Procedures: USE SELF-CONTAINED BREATHING A

PPARATUS. Unusual Fire/Explosion Hazard:HAZARDOUS DECOMPOSITION PRODUCTS MAY BE FORMED DURING FIRE.
========= Accidental Release Measures ==========
Spill Release Procedures:FLUSH MATERIEL TO SEWER WITH LARGE AMOUNT OF WATER.DISCHARGE MAY BE SUBJECT TO FEDERAL,STATE OR LOCAL LAWS. Neutralizing Agent:NONE.
=========== Handling and Storage ============
Handling and Storage Precautions:KEEP CAONTAINER TIGHTLY CLOSED AND AWAY FROM STRONG ALKAL
I. Other Precautions:NONE.
====== Exposure Controls/Personal Protection ========
Respiratory Protection:NOT REQUIRED UNDER NORMAL SERVICE. Ventilation:GOOD GENERAL VENTILATION SHOULD BE SUFFICIENT. Protective Gloves:IMPERVIOUS FOR REPEATED CONTACT. Eye Protection:SAFETY GLASSES. Other Protective Equipment:TO AVOID SKIN CONTACTAS NEEDED. Work Hygienic Practices:WASH HANDS.SEPERATE WORK CLOTHES FROM STREET CLOTHES.LAUNDER WORK CLOTHES BEFORE REUSE.KEEP FOOD OUT OF THE WORK AREA. Supplemental Safety and Health
KEY 1;N1.
======================================
Boiling Pt:B.P. Text: