

EASTMAN KODAK COMPANY -- 102 3209 DURAFLO RT DEVELOPER REPLENISHER, --
6750-01-319-6473

===== Product Identification =====

Product ID:102 3209 DURAFLO RT DEVELOPER REPLENISHER,

MSDS Date:06/09/1990

FSC:6750

NIIN:01-319-6473

Kit Part:Y

MSDS Number: BNNKP

=== Responsible Party ===

Company Name:EASTMAN KODAK COMPANY

Address:343 STATE STREET

City:ROCHESTER

State:NY

ZIP:14650

Country:US

Info Phone Num:

716-722-5151

Emergency Phone Num:716-722-5151

CAGE:19139

=== Contractor Identification ===

Company Name:EASTMAN KODAK CO GOVERNMENT MARKETS CONTRACTS

Address:343 STATE ST

Box:City:ROCHESTER

State:NY

ZIP:14650-1115

Country:US

Phone:716-722-5151/(800) 242-2424

CAGE:19139

===== Composition/Information on Ingredients =====

Ingred Name:WATER

CAS:7732-18-5

RTECS #:ZC0110000

Fraction by Wt: 70-80%

Other REC Limits:NONE SPECIFIED

Ingred Name:POTASSIUM CARBONATE

CAS:584-08-7

RTECS #:

TS7750000
Fraction by Wt: 5-10%
Other REC Limits:NONE SPECIFIED

Ingred Name:SODIUM SULFITE
CAS:7757-83-7
RTECS #:WE2150000
Fraction by Wt: 1-5%
Other REC Limits:NONE SPECIFIED

Ingred Name:HYDROQUINONE (SARA III)
CAS:123-31-9
RTECS #:MX3500000
Fraction by Wt: 2%
Other REC Limits:NONE SPECIFIED
OSHA PEL:2 MG/M3
ACGIH TLV:2 MG/M3; 9192
EPA Rpt Qty:1 LB
DOT Rpt Qty:1 LB

Ingred Name:POTASSIUM HYDROXIDE (SARA III)
CAS:1310-58-3
RTECS #:TT2100000
Fraction by Wt: 1-5%
Other REC Limits:NONE SPECIFIED
D
OSHA PEL:C, 2 MG/M3
ACGIH TLV:C 2 MG/M3; 9192
EPA Rpt Qty:1000 LBS
DOT Rpt Qty:1000 LBS

Ingred Name:SODIUM CARBONATE
CAS:497-19-8
RTECS #:VZ4050000
Fraction by Wt: 1-5%
Other REC Limits:NONE SPECIFIED

===== Hazards Identification =====

Routes of Entry: Inhalation:NO Skin:YES Ingestion:YES
Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO
Health Hazards Acute and Chronic:INHALATION- LOW HAZARD FOR RECOMMENDED
HANDLING. EYES- CAUSES BURNS. SKIN- PRO

LONGED OR REPEATED SKIN

CONTACT MAY CAUSE BURNS. MAY CAUSE AN ALLERGIC SKIN REACTION.

INGESTION- HARMFUL IF SWALLOWED. MAY CAUSE BURNS OR SEVERE IRRITATION OF THE GASTROINTESTINAL TRACT.

Effects of Overexposure:NONE SPECIFIED BY MANUFACTURER.

Medical Cond Aggravated by Exposure:NONE SPECIFIED BY MANUFACTURER.

===== First Aid Measures =====

First Aid:EYES- IMMEDIATELY FLUSH EYES WITH PLENTY OF WATER FOR AT LEAST 15 MIN. AND GET PROMPT MEDIC

AL ATTENTION. SKIN- FLUSH SKIN

WITH PLENTY OF WATER FOR AT LEAST 15 MIN AND WASH WITH A NON-ALKALINE TYPE OF SKIN CLEANER. REMOVE CONTAMINATED CLOTHING AND SHOES. GET MEDICAL ATTENTION IF SKIN BURNS OR AN ALLERGIC SKIN REACTION DEVELOPS. INGESTION- DO NOT INDUCE VOMITING. GIVE WATER AND GET PHYSICIAN.

===== Fire Fighting Measures =====

Flash Point:NONCOMBUSTIBLE

Extinguishing Media:USE APPROPRIATE AGENT FOR SURROUNDING FIRE.

Fire Fighting

Procedures:WEAR SELF-CONTAINED BREATHING APPARATUS AND PROTECTIVE CLOTHING.

Unusual Fire/Explosion Hazard:FIRE OR EXCESSIVE HEAT MAY CAUSE PRODUCTION OF HAZARDOUS DECOMPOSITION PRODUCTS.

===== Accidental Release Measures =====

Spill Release Procedures:SMALL AMOUNTS- NEUTRALIZE. FLUSH MATERIAL TO AN ACID-FREE SEWER WITH LARGE AMOUNTS OF WATER. LARGE SPILL- ABSORB SPILL WITH INERT MATERIAL AND PLACE IN A CONTAINER FOR CHEMICAL WASTE. FLUSH RESIDU

AL SPILL AND AREA WITH WATER.

Neutralizing Agent:SODIUM BISULFATE

===== Handling and Storage =====

Handling and Storage Precautions:KEEP CONTAINER TIGHTLY CLOSED AND AWAY FROM ACIDS.

Other Precautions:NONE

===== Exposure Controls/Personal Protection =====

Respiratory Protection:SUPPLEMENTARY RESPIRATORY PROTECTION MAY BE NEEDED IN SPECIAL CIRCUMSTANCE.

Ventilation:GOOD VENTILATION SHOULD BE SUFFICIENT.

Protective Gloves:PROTECTIVE

GLOVES AND CLOTHING.
Eye Protection:SAFETY GLASSES, GOGGLES.
Other Protective Equipment:PROTECTIVE CLOTHING AS NEEDED TO PREVENT
CONTACT WITH MATERIAL.
Work Hygienic Practices:WASH HANDS THOROUGHLY AFTER HANDLING.
Supplemental Safety and Health
NONE

===== Physical/Chemical Properties =====

HCC:B3
Boiling Pt:B.P. Text:>212F,>100C
Vapor Pres:18 MM HG
Vapor Density:0.6
Spec Gravity:1.268
pH:>12.0
Solubility in Water:COMPLETE
Appearance and Odor:CLEAR, SLIGHTLY YEL
LOW SOLUTION, ODORLESS.
Percent Volatiles by Volume:70

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES
STRONG ACIDS.
Stability Condition to Avoid:EXTREME TEMPERATURES.
Hazardous Decomposition Products:MAY PRODUCE OXIDES OF SULFUR.

===== Disposal Considerations =====

Waste Disposal Methods:DISCHARGE, TREATMENT, OR DISPOSAL MAY BE SUBJECT
TO FEDERAL, STATE AND LOCAL REGULATIONS.

Disclaimer (provided with this information by the compiling agencies):
This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.