

SOUTH SIDE ENTERPRISES CORP -- 2190 TEP LUBE LUBRICATING OIL,STEAM TURBINE --
9150-00-942-9343

===== Product Identification =====

Product ID:2190 TEP LUBE LUBRICATING OIL,STEAM TURBINE

MSDS Date:09/09/1992

FSC:9150

NIIN:00-942-9343

MSDS Number: BNRRP

=== Responsible Party ===

Company Name:SOUTH SIDE ENTERPRISES CORP

Address:RT 92

Box:100

City:CHASE CITY

State:VA

ZIP:23924

Country:US

Info Phone Num

:804-279-4371 (DGSC-SSH)

Emergency Phone Num:703-448-5369 WRONG NUMBER!

Preparer's Name:DGSC-SSH

CAGE:48122

=== Contractor Identification ===

Company Name:SOUTH SIDE ENTERPRISES CORP

Address:RT 92

Box:100

City:CHASE CITY

State:VA

ZIP:23924

Country:US

Phone:703-448-5369 WRONG NUMBER!

CAGE:48122

===== Composition/Information on Ingredients =====

Ingred Name:MINERAL OIL, PETROLEUM DISTILLATES, SOLVENT-DEWAXED HEAVY
PARAFFINIC

CAS:64742-65-0

RTECS #:PY8038500

Other REC Limits

:NONE SPECIFIED BY M.
OSHA PEL:5 MG/M3 OIL MIST
ACGIH TLV:5 MG/M3 (OIL MIST)

===== Hazards Identification =====

Routes of Entry: Inhalation:YES Skin:YES Ingestion:NO
Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO
Health Hazards Acute and Chronic:ACUTE- ORAL:LOW TOXICITY. MAY CAUSE
VOMITING & DIARRHEA. SMALL AMOUNT ASPIRATED INTO LUNGS WILL CAUSE
LUNG INJURY. INHALATION:MIST/VAPORS/FUMES MAY CAUSE RESPIRATORY
TRACT IRRITATION. EYE:MAY CAUSE
IRRITATION. SKIN:REPEATED CONTACT
MAY CAUSE IRRITATION. CHRONIC:NONE KNOWN.
Effects of Overexposure:ORALLY MAY CAUSE VOMITING & DIARRHEA. SMALL
AMOUNT ASPIRATED INTO LUNGS WILL CAUSE LUNG INJURY. INHALATION OF
MIST/VAPORS/FUMES MAY CAUSE RESPIRATORY TRACT IRRITATION. CONTACT
WITH EYES MAY CAUSE IRRITATION. REPEATED SKIN CONTACT MAY
CAUSE IRRITATION.
Medical Cond Aggravated by Exposure:PRE-EXISTING SKIN DISORDERS MAY BE
MORE SUSCEPTIBLE TO THIS MATERIAL.

=====

===== First Aid Measures =====

First Aid:GET MEDICAL ATTENTION IF SYMPTOMS PERSIST. SKIN:REMOVE
EXCESS. WASH SKIN WITH SOAP & WATER. EYE:FLUSH WITH WATER FOR 15
MINUTES, HOLDING EYELIDS OPEN. INHALED:REMOVE TO FRESH AIR &
PROVIDE OXYGEN/CPR IF NEEDED. ORAL:DO NOT INDUCE VOMITING.GET
IMMEDIATE MEDICAL ATTENTION.

===== Fire Fighting Measures =====

Flash Point:>200F,>93C
Extinguishing Media:USE WATER FOG, CO2, FOAM, OR DRY C
HEMICAL. DO NOT
USE A DIRECT STREAM OF WATER. PRODUCT MAY FLOAT & CAN BE REIGNITED.
Fire Fighting Procedures:WEAR FIRE FIGHTING PROTECTIVE EQUIPMENT AND A
FULL FACED SELF CONTAINED BREATHING APPARATUS. COOL FIRE EXPOSED
CONTAINERS WITH WATER SPRAY.
Unusual Fire/Explosion Hazard:COMBUSTION OR HEAT OF FIRE MAY PRODUCE
HAZARDOUS DECOMPOSITION PRODUCTS AND VAPORS. WATER OR FOAM MAY
CAUSE FROTHING.

===== Accidental Release Measures =====

Spill Release

Procedures:STOP FLOW. RECOVER BY VACUUMING. WIPE OR MOP
UP OR ABSORB WITH DIATOMACEOUS EARTH OR OTHER INERT MATERIAL. STORE
IN APPROPRIATE CONTAINER FOR DISPOSAL.

===== Handling and Storage =====

Handling and Storage Precautions:STORAGE- STORE IN COOL PLACE.
EXCESSIVE MISTING MAY CAUSE SLIPPERY FLOORS. PROPER FOOTWEAR
REQUIRED.
Other Precautions:WASH HANDS WITH SOAP AND WATER BEFORE EATING,
DRINKING, OR SMOKING. DO NOT CREATE MIST AND AVO
ID INHALING MIST OR
VAPORS.

===== Exposure Controls/Personal Protection =====

Respiratory Protection:NONE NORMALLY REQUIRED. IF VAPOR OR MIST IS
GENERATED, USE RESPIRATOR APPROVED BY NIOSH AS APPROPRIATE.
Ventilation:GOOD GENERAL VENTILATION IS SUFFICIENT FOR MOST CONDITIONS.
Protective Gloves:NEOPRENE, NITRILE, OR POLYVINYL ALCOHOL
Eye Protection:USE CHEMICAL SAFETY GOGGLES
Other Protective Equipment:EYE WASH STATION & SAFETY SHOWER. CHEMICALLY
RESISTANT BOOTS AN
D APRONS RECOMMENDED.
Work Hygienic Practices:OBSERVE GOOD PERSONAL HYGIENE PRACTICES AND
RECOMMENDED PROCEDURES.
Supplemental Safety and Health
NO MSDS WAS AVAILABLE FROM MANUFACTURER. THIS MSDS WAS PREPARED BY THE
PROFESSIONALS OF DGSC-SSH WITHOUT ANY WARRANTY. IT IS THE USER'S
RESPONSIBILITY TO GATHER INFORMATION AND USE THE MATERIAL PROPER LY
TO PROTECT EMPLOYEES AND ENVIRONMENT.

===== Physical/Chemical Properties =====

HCC:V6
Spec Gravity: