

DEXTER ADHESIVES AND STRUCTURAL MATERIALS DIVISION -- EPK IC RESIN ONLY, PC AA0001 --
8030-00-998-3321

===== Product Identification =====

Product ID:EPK IC RESIN ONLY, PC AA0001

MSDS Date:10/01/1991

FSC:8030

NIIN:00-998-3321

Kit Part:Y

MSDS Number: BNRRZ

=== Responsible Party ===

Company Name:DEXTER ADHESIVES AND STRUCTURAL MATERIALS DIVISION

Address:2850 WILLOW PASS ROAD

City:PITTSBURG

State:CA

ZIP:94565-3237

Country:US

Info Phone Num:415-687-4201

Emergency Phone Num:800-424-9300(CHEMTREC)

CAGE:33564

=== Contractor Identification ===

Company Name:DEXTER CORPORATION ADHESIVE & COATING SYSTEMS

Address:2850 WILLOW PASS ROAD

Box:312

City:BAY POINT

State:CA

ZIP:94565-3299

Country:US

Phone:202-483-7616

CAGE:33564

Company Name:STEVEN INDUSTRIES

Address:39 AVENUE C

Box:8

City:BAYONNE

State:NJ

ZIP:07002-3417

Country:US

Phone:201-437-6501

CAGE:33150

Company Name:VARIAN ASOCIATES INC, VACUUM PROD

UCTS DIV
Address:121 HARTWELL AVE
Box:City:LEXINGTON
State:MA
ZIP:02173-3125
Country:US
Phone:617-7200
CAGE:04399

=====
Composition/Information on Ingredients
=====

Ingred Name:TALC
CAS:14807-96-6
RTECS #:MW2700000
Fraction by Wt: 40-70%
Other REC Limits:NONE SPECIFIED
OSHA PEL:0.2 FIBERS/CC
ACGIH TLV:0.2 FIBERS/CC

Ingred Name:BISPHENOL A/EPICHLOROHYDRIN EPOXY RESIN
CAS:25068-38-6
RTECS #:KC2100000
Fraction by Wt: 40-70%
Other REC Limits:NONE SPECIFIED

Ingred Name:VOC: 10 G
/L (ESTIMATE)
RTECS #:9999999VO
Other REC Limits:NONE SPECIFIED

=====
Hazards Identification
=====

Routes of Entry: Inhalation:YES Skin:YES Ingestion:NO
Health Hazards Acute and Chronic:BRIEF CONTACT MAY IRRITATE THE SKIN OR
CAUSE A RASH. REPEATED OR PROLONGED SKIN CONTACT MAY RESULT IN
ALLERGIC SENSITIZATION. *DO NOT HEAT MIXED ADHESIVE UNLESS
CURING SURFACES TO BE BONDED. FA ILURE TO OBSERVE THESE PRECAUTIONS
MAY RESULT IN EXCESSIVE HEAT
BUILD-UP CAUSING AN EXOTHERM. THE
EXOTHERM HAS THE**

Explanation of Carcinogenicity:COMPONENT 1: NOT CLASSIFIED AS A HUMAN
CARCINOGEN (GROUP 3) PER IARC.

Effects of Overexposure:SKIN RASH, IRRITATION.
**POTENTIAL FOR RELEASE OF TOXIC GASSES.

Medical Cond Aggravated by Exposure:SKIN SENSITIZATION.

=====
First Aid Measures
=====

First Aid:EYE: FLUSH EYES WITH WATER FOR 15 MINUTES. IF IRRITATION
PERSISTS, GET MEDICAL ATTENTION. SK

IN: WASH SKIN THOROUGHLY WITH SOAP AND WATER. IF IRRITATION PERSISTS, GET MEDICAL ATTENTION. INHALATION: REMOVE VICTIM TO FRESH AIR. IF SYMPTOMS PERSIST, GET MEDICAL ATTENTION. INGESTION: DRINK PLENTY OF WATER. GET MEDICAL ATTENTION IMMEDIATELY.

===== Fire Fighting Measures =====

Flash Point Method:PMCC
Flash Point:480F,249C
Extinguishing Media:DRY CHEMICAL, OR HALON FIRE EXTINGUISHER, OR WATER SPRAY, FOAM OR FOG.
Fire Fighting Procedures:
WEAR SCBA AND FULL PROTECTIVE CLOTHING SUCH AS TURN-OUT GEAR. CARTRIDGE RESPIRATORS DO NOT PROVIDE ADEQUATE PROTECTION FOR FIRE FIGHTERS OR EXOTHERM MITIGATION.
Unusual Fire/Explosion Hazard:MAY LIBERATE LARGE QUANTITIES OF DENSE FOUL-SMELLING SMOKE WHICH MAY CONTAIN UNIDENTIFIED TOXIC GASES.

===== Accidental Release Measures =====

Spill Release Procedures:WEAR PROTECTIVE CLOTHING, GLOVES AND SAFETY GLASSES. SCRAPE UP OR SHOVEL INTO DOT APPROVED WASTE CONTAINERS.
Neutralizing Agent:NOT APPLICABLE.

===== Handling and Storage =====

Handling and Storage Precautions:STORE AT ROOM TEMP UP TO 12 MONTHS. KEEP CONTAINER TIGHTLY CLOSED WHEN NOT IN USE. FOLLOW CURING SCHEDULE AS RECOMMENDED IN PRODUCT LITERATURE.
Other Precautions:DO NOT CUT, GRIND, WELD OR DRILL ON OR NEAR THIS CONTAINER.

===== Exposure Controls/Personal Protection =====

Respiratory Protection:IF LOCAL EXHAUST VENTILATION INADEQUATE, A RESPIRATOR EQUIPPED WITH ORGANIC VAPOR CARTRIDGES MAY BE APPROPRIATE. IF DRY SANDING OR GRINDING CURED PRODUCT, A NIOSH/MSA APPROVED RESPIRATOR WITH HEPA CARTRIDGES IS RECOMMENDED.
Ventilation:LOCAL EXHAUST VENTILATION AT THE POINT OF USE.
Protective Gloves:BUTYL RUBBER, PVC OR NITRILE RUBBER
Eye Protection:SAFETY GLASSES W/SIDE SHIELD OR CHEM GOGGLES
Other Protective Equipment:AN EYEWASH AND SAFETY SHOWER SHOULD BE NEARBY AND READY FOR USE.

Supplemental Safety and Health

WASTE DISPOSAL MAY BE MORE RESTRICTIVE OR OTHERWISE DIFFERENT FROM
FEDERAL LAWS AND REGULATIONS. CONSULT STATE AND LOCAL REGULATIONS
REGARDING PROPER DISPOSAL OF THIS MATERIAL.

===== Physical/Chemical Properties =====

Boiling Pt:B.P. Text:>500F,>260C

Decomp Temp:Decomp Text:NOT TESTED

Spec Gravity:1.57

Viscosity: