

JET-LUBE INC -- LEAD-FREE MIL-A-907E ANTI-SEIZE LUBRICANT -- 8030-00-286-5453

=====
Product Identification
=====

Product ID:LEAD-FREE MIL-A-907E ANTI-SEIZE LUBRICANT

MSDS Date:01/07/1992

FSC:8030

NIIN:00-286-5453

MSDS Number: BNTFB

=== Responsible Party ===

Company Name:JET-LUBE INC

Address:4849 HOMESTEAD ROAD

Box:21258

City:HOUSTON

State:TX

ZIP:77226

Country:US

Info Phone Num:713-674-7617/713-37

0-6206(AFTER HR)

Emergency Phone Num:713-674-7617

Preparer's Name:D. A. OLDIGES

CAGE:0A307

=== Contractor Identification ===

Company Name:JET-LUBE INC

Address:4849 HOMESTEAD RD

Box:21258

City:HOUSTON

State:TX

ZIP:77026

Country:US

CAGE:0A307

=====
Composition/Information on Ingredients
=====

Ingred Name:PETROLEUM OIL

CAS:64741-96-4

RTECS #:PY8040000

Fraction by Wt: 70%

Other REC Limits:NONE SPECIFIED

OSHA PEL:5 MG/M3 TWA-OIL MIST

Ingred Name:COPPER POWDER (SARA 313)

CAS:7440-

50-8
RTECS #:GL5325000
Fraction by Wt: 10%
Other REC Limits:NONE SPECIFIED
ACGIH TLV:1 MG/M3 FUME
EPA Rpt Qty:5000 LBS
DOT Rpt Qty:5000 LBS

=====
===== Hazards Identification =====

Routes of Entry: Inhalation:NO Skin:YES Ingestion:NO
Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO
Effects of Overexposure:REDNESS AND IRRITATION OF SKIN. REPEATED SKIN
CONTACT FOR PERSONS HYPERSENSITIVE TO PETROLEUM PRODUCTS CAN CAUSE
REDNESS AND IRRITATION OF SKIN

=====
===== First Aid Measures =====

First Aid:INHALATION: CLEAR AIR PASSAGE, CALL PHYSICIAN. INGESTION: IF
INGESTED, CALL PHYSICIAN. EYES: WASH WITH COPIOUS QUANTITIES OF
WATER. SKIN: REMOVE BY WIPING, OR WATERLESS HAND CLEANER, FOLLOWED
BY WASHI NG.

=====
===== Fire Fighting Measures =====

Flash Point Method:COC
Flash Point:430F,221C
Autoignition Temp:Autoignition Temp Text:>500F
Extinguishing Media:USE FOAM, DRY CHEMICAL, W
ATER SPRAY (FOG), CARBON
DIOXIDE OR VAPORIZING LIQUID TYPE EXTINGUISHING AGENTS.
Fire Fighting Procedures:USE SUPPLIED-AIR BREATHING EQUIPMENT FOR
ENCLOSED OR CONFINED SPACES.

=====
===== Accidental Release Measures =====

Spill Release Procedures:SCOOP UP EXCESS, WIPE UP WITH RAGS, PICK-UP
RESIDUE WITH DIATOMACEOUS EARTH TO AVOID WALKING HAZARD

=====
===== Handling and Storage =====

Handling and Storage Precautions:NORMAL PRECAUT

IONS AS WITH ANY
PETROLEUM PRODUCT

===== Exposure Controls/Personal Protection =====

Other Protective Equipment: PERSONS WITH HYPERSENSITIVE SKIN SHOULD USE
GLOVES

Work Hygienic Practices: WASH HANDS BEFORE EATING

Supplemental Safety and Health

===== Physical/Chemical Properties =====

HCC: N1

Boiling Pt: B.P. Text: 624F, 329C

Vapor Pres: 5

Spec Gravity: (WATER = 1) 1.20

Evaporation Rate & Reference: (N-BUTYL ACETATE = 1)