

TEXACO INC -- CAPELLA WF 32,01587 -- 9150-00-823-7905

===== Product Identification =====

Product ID:CAPELLA WF 32,01587

MSDS Date:01/04/1995

FSC:9150

NIIN:00-823-7905

MSDS Number: BPFDX

=== Responsible Party ===

Company Name:TEXACO INC

Address:1111 RUSK

Box:52332

City:HOUSTON

State:TX

ZIP:77052

Country:US

Info Phone Num:713-650-4000/800-782-7852

Emergency Phone Num:914-831-3400/800-424-9300(CHEMT  
REC)

CAGE:3B431

=== Contractor Identification ===

Company Name:SALATHE OIL CO INC

Address:2226 PETERS RD

Box:City:HARVEY

State:LA

ZIP:70058

Country:US

Phone:504-366-4542

CAGE:0T5C6

Company Name:TEXACO PIPELINE INC (SUB OF TEXACO INC)

Address:9700 RICHMOND AVE

Box:42286

City:HOUSTON

State:TX

ZIP:77242-2286

Country:US

Phone:713-953-4260

CAGE:3B431

===== Composition/Information on Ingredients =====

Ingred Name:MINERAL OIL/HYDROTREATED LIGHT NAPHTHENIC PETROLEUM  
DISTILLATES

C

AS:64742-53-6  
RTECS #:PY8036000  
Fraction by Wt: 65 - 80%  
Other REC Limits:NONE RECOMMENDED  
OSHA PEL:5 MG/M3 (OIL MIST)  
ACGIH TLV:5 MG/M3 (OIL MIST)

Ingred Name:DISTILLATES, ACID-TREATED HEAVY NAPHTHENIC  
CAS:64742-18-3  
RTECS #:PY8032000  
Fraction by Wt: 20 - 35%  
Other REC Limits:NONE RECOMMENDED  
OSHA PEL:300 PPM  
ACGIH TLV:300 PPM

===== Hazards Identification =====

LD50 LC50 Mixture:TLV FOR OIL MIST IS 5 MG/M3.  
Routes of Entry: Inhalation:YES Skin:NO Ingestion  
:NO  
Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO  
Health Hazards Acute and Chronic:TARGET ORGANS:EYE, SKIN, RESPIRATORY  
TRACT. ACUTE- MAY CAUSE EYES & SKIN IRRITATION. PROLONGED/REPEATED  
SKIN CONTACT CAUSES DEFATTING. INHALATION OF VAPORS/OIL MIST MAY  
CAUSE IRRITATION. INGESTION MAY CAUSE NAUSEA. ASPIRATION HAZARD.  
CHRONIC- UNKNOWN.  
Explanation of Carcinogenicity:NONE  
Effects of Overexposure:IRRITATION, NAUSEA  
Medical Cond Aggravated by Exposure:PERSONS WITH PRE-EXISTING  
SKIN  
DISORDERS MAY BE MORE SUSCEPTIBLE TO THE EFFECTS OF THIS PRODUCT.

===== First Aid Measures =====

First Aid:GET MEDICAL HELP IF SYMPTOMS PERSIST. INHALED:REMOVE TO FRESH  
AIR. PROVIDE CPR/OXYGEN IF NEEDED. EYES:FLUSH WITH WATER FOR 15  
MINUTES. HOLD EYELIDS OPEN. SKIN:WIPE OFF EXCESS. WASH SKIN WITH  
SOAP & WATER. ORAL:IF CONSCIOUS & SEVERAL MOUTHFULS OF PRODUCT ARE  
SWALLOWED, DRINK 2 GLASSES OF WATER. SEEK MEDICAL ATTENTION. IF  
S

PONTANEOUS VOMITING OCCURS, MONITOR FOR BREATHING DIFFICULTIES.

===== Fire Fighting Measures =====

Flash Point Method:COC

Flash Point:330F,166C

Extinguishing Media:USE WATER FOG, CARBON DIOXIDE, FOAM/DRY CHEMICAL.  
WATER/FOAM MAY CAUSE FROTHING.

Fire Fighting Procedures:WEAR FIRE FIGHTING PROTECTIVE EQUIPMENT AND  
NIOSH-APPROVED SELF CONTAINED BREATHING APPARATUS. COOL FIRE  
EXPOSED CONTAINERS WITH WATER SPRAY.

Unusual Fire/Explosion Hazard:CONTAINER  
MAY BURST.

===== Accidental Release Measures =====

Spill Release Procedures:VENTILATE AREA. RECOVER FREE OIL IF POSSIBLE.  
ABSORB SPILL WITH INERT MATERIAL SUCH AS SAND, CLAY, EARTH &  
SHOVELD INTO CONTAINERS FOR LATER DISPOSAL. PREVENT RUN-OFF TO  
ENTER WATERWAYS, SEWERS. ALL R ESPONSE ACTIVITIES MUST COMPLY WITH  
HAZWOPER.

Neutralizing Agent:NOT RELEVANT

===== Handling and Storage =====

Handling and Storage Precauti

ons:STORE AWAY FROM HEAT & STRONG

OXIDANTS. KEEP CONTAINERS CLOSED WHEN NOT IN USE. KEEP OUT OF REACH  
OF CHILDREN.

Other Precautions:DO NOT GET IN EYES, ON SKIN OR ON CLOTHING. WASH  
THOROUGHLY AFTER HANDLING. AVOID BREATHING OIL MIST. DISCARD  
LUBRICANT-SOAKED SHOES. REMOVE LUBRICANT-SOAKED CLOTHING AND  
LAUNDER BEFORE RE-USE.

===== Exposure Controls/Personal Protection =====

Respiratory Protection:NONE NORMALLY REQUIRED. IF EXPOSURE MAY OR DOES  
EXCEED O

CCUPATIONAL EXPOSURE LIMITS, WEAR A NIOSH-APPROVED ORGANIC  
VAPOR RESPIRATOR.

Ventilation:USE ADEQUATE VENTILATION TO KEEP OIL MISTS OF THIS MATERIAL  
BELOW APPLICABLE STANDARD(S).

Protective Gloves:NITRILE OR NEOPRENE RECOMMENDED

Eye Protection:SAFETY GLASSES, FACE SHIELD RECOMMENDED

Other Protective Equipment:EYE WASH STATION AND SAFETY SHOWER.  
INDUSTRIAL-TYPE WORK CLOTHING AND APRON AS REQUIRED.

Work Hygienic Practices:OBSERVE GOOD PERSONAL HYGIENE PRACTICES AND  
RECOMMENDED PROC

EDURES.  
Supplemental Safety and Health  
USE AS DIRECTED

===== Physical/Chemical Properties =====

HCC:V6  
NRC/State Lic Num:NOT RELEVANT  
Spec Gravity:0.8916  
Viscosity:30.1CST @104F  
Solubility in Water: