View NSN Online: https://aerobasegroup.com/nsn/8030-00-631-8013

Product ID:WS-516 MSDS Date:01/01/1987 FSC:8030 NIIN:00-631-8013 Kit Part:Y **MSDS Number: BPFYQ** === Responsible Party === Company Name: J&R INDUSTRIES, INC. Address:800 EAST ANAHEIM ST. City:WILMINGTON State:CA ZIP:90744 Country:US Info Phone Num:213-830-9904 Emergency Phone Num:213-830-9904 CAGE:LO716 === Contrac tor Identification === Company Name: J AND R INDUSTRIES (FACTORY LOCATION) Address:800 E. ANAHEIM ST Box:City:WILMINGTON State:CA ZIP:90744 Country:US Phone:310-476-7121 CAGE:7X230 Company Name: J&R INDUSTRIES, INC. Address:800 EAST ANAHEIM ST. City:WILMINGTON State:CA ZIP:90744 Country:US Phone:213-830-9904 CAGE:LO716

Ingred Name:POLYSULFIDE POLYMER Fraction by Wt: 65% Other REC Limits:NONE SPECIFIED

Ingred Name:CALCIUM CARB

ONATE CAS:1317-65-3 RTECS #:EV9580000 Fraction by Wt: 25% Other REC Limits:NONE SPECIFIED

Ingred Name:PHENOLIC RESIN Fraction by Wt: 5% Other REC Limits:NONE SPECIFIED

Ingred Name:TOLUENE (SARA III) CAS:108-88-3 RTECS #:XS5250000 Fraction by Wt: 5% Other REC Limits:NONE SPECIFIED OSHA PEL:200 PPM/150 STEL ACGIH TLV:50 PPM; 9293 EPA Rpt Qty:1000 LBS DOT Rpt Qty:1000 LBS

Health Hazards Acute and Chronic:IRRITATION, NAUSEA, H EADACHE, AND DIZZINESS.

First Aid:FLUSH EYES WITH PLENTY OF WATER. FLUSH SKIN WITH WATER. REMOVE VICTIM TO FRESH AIR. CONTACT PHYSICIAN.

Flash Point:120F,49C Lower Limits:1 Upper Limits:7 Extinguishing Media:USE WATER, FOAM, DRY CHEMICAL OR CO2. Fire Fighting Procedures:WARNING: COMBUSTIBLE. CLEAR FIRE AREA. WEAR HELMET AND FACE SHIELD AND NIOS H APPROVED BREATHING APPARATUS. Unusual Fire/Explosion Hazard:KEEP AWAY FROM HEAT AND OPEN FLAME.

Spill Release Procedures: WASH WITH PLENTY OF WATER.

Handling and Storage Precautions:WARNING: COMBUSTIBLE. STORE IN A COOL PLACE AWAY FROM HEAT AND OPEN FLAME. AVOID SKIN AND EYE CONTACT AND BREATHING OF VAPORS.

======= Exposure Controls/Personal

Protection ========

Respiratory Protection:AVOID PROLONGED BREATHING. USE NIOSH APPROVED RESPIRATOR. Ventilation:MECHANICAL (GENERAL) VENTILATION. Protective Gloves:WEAR PROTECTIVE GLOVES. Eye Protection:WEAR GOGGLES. Supplemental Safety and Health

HCC:F4 Boiling Pt:B.P. Text:231F,111C Vapor Pres:22 @ 70F Vapor Density:3.8 Spec Gravity:1.3 (WATER=1) Evaporation Rate & amp; Reference:2.0 (BU AC=1) Solubility in Wate r:NONE Appearance and Odor:WHITE PASTE, AROMATIC. Percent Volatiles by Volume:4

Stability Indicator/Materials to Avoid:YES
HEAT, OPEN FLAME, STRONG OXIDANTS.
Stability Condition to Avoid:HEAT, SPARKS AND OPEN FLAME. SKIN CONTACT.
Hazardous Decomposition Products:CO2, SULFUR DIOXIDE, ORGANIC SULFUR COMPOUNDS.

Waste Disposal Methods:UNDER EPA-RCRA (40 CFIR 261.33) HAZARDOUS WASTE NO: U220 REFER TO LATEST EPA REGULATIONS.

Disclaimer (provided with this information by the compiling agencies): This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibil ity for the suitability of this information to their particular situation.