

RAYMARK CORP -- WOVEN BRAKE LINING -- 2530-00-278-6529

=====  
Product Identification  
=====

Product ID:WOVEN BRAKE LINING

MSDS Date:03/20/1990

FSC:2530

NIIN:00-278-6529

MSDS Number: BPJBC

=== Responsible Party ===

Company Name:RAYMARK CORP

Address:123 E STIEGEL ST

City:MANHEIM

State:PA

ZIP:17545-1626

Country:US

Info Phone Num:717-665-2211

Emergency Phone Num:717-665-2211

CAGE:8X148

=== Contractor Id

entification ===

Company Name:RAYMARK CORP

Address:123 E STIEGEL ST

Box:City:MANHEIM

State:PA

ZIP:17545-1626

Country:US

Phone:717-665-2211

CAGE:8X148

=====  
Composition/Information on Ingredients  
=====

Ingred Name:BRASS WIRE (NON-HAZARDOUS)

Fraction by Wt: 12-18%

Other REC Limits:NONE RECOMMENDED

Ingred Name:FIBERGLASS

Fraction by Wt: 40-60%

Other REC Limits:NONE RECOMMENDED

Ingred Name:MODIFIED PHENOLIC RESIN

Fraction by Wt: 20-30%

Other REC Limits:NONE RECOMMENDED

Ingred

Name:ORGANIC FIBERS

Fraction by Wt: 12-18%

Other REC Limits:NONE RECOMMENDED

=====  
===== Hazards Identification =====

Routes of Entry: Inhalation:YES Skin:NO Ingestion:NO  
Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO  
Health Hazards Acute and Chronic:TEMPORARY IRRITATION OF THE MOUTH,  
NOSE AND THROAT.  
Effects of Overexposure:MAY CAUSE TEMPORARY RESPIRATORY IRRITATION.  
Medical Cond Aggravated by Exposure:ANY CONDITION GENERALLY AGGRAVATED  
BY MECHANICA  
L IRRITANTS IN AIR OR ON SKIN.

=====  
===== First Aid Measures =====

First Aid:INHALATION- REMOVE FROM EXPOSURE. GET MEDICAL ATTENTION IF  
IRRITATION PERSISTS. SKIN- WASH WITH MILD SOAP AND RUNNING WATER.  
EYES- FLUSH WITH FLOWING WATER FOR AT LEAST 15 MIN. IF SYMPTOMS  
PERSIST, SEEK IMMEDIATE MEDICAL ATTENTION. INGESTION- UNLIKELY.  
CONSULT PHYSICIAN IF UNUSUAL REACTION IS NOTED.

=====  
===== Fire Fighting Measures =====

==

Extinguishing Media:WATER, FOAM, DRY CHEMICAL.  
Fire Fighting Procedures:IN A SUSTAINED FIRE, SELF-CONTAINED BREATHING  
APPARATUS (SCBA) SHOULD BE WORN.  
Unusual Fire/Explosion Hazard:NONE

=====  
===== Accidental Release Measures =====

Spill Release Procedures:USE VACUUM IF DUST IS INVOLVED.  
Neutralizing Agent:NONE

=====  
===== Handling and Storage =====

Handling and Storage Precautions:STORE IN DRY PLACE.  
Other Precautions:WEAR LONG SLEE

VED SHIRTS, LOOSE FITTING CLOTHING AND  
USE GOOD PERSONAL HYGIENE.

===== Exposure Controls/Personal Protection =====

Respiratory Protection:NIOSH-APPROVED NUISANCE DUST RESPIRATOR IF TLV  
IS EXCEEDED.

Ventilation:USE LOCAL EXHAUST VENTILATION.

Protective Gloves:AS NEEDED.

Eye Protection:MAY BE APPROPRIATE IN CERTAIN OPERATIONS

Other Protective Equipment:LONG SLEEVED SHIRTS, LOOSE FITTING  
CLOTHING.

Work Hygienic Practices:WASH WITH MILD SOAP AND WATER AFTER HANDLING

Supplemental Safety and Health  
NONE

===== Physical/Chemical Properties =====

HCC:N1

Spec Gravity:1.60

Appearance and Odor:TAN, LITTLE OR NO ODOR.

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES  
NONE SPECIFIED BY MANUFACTURER.

Stability Condition to Avoid:AVOID CREATING DUST.

Hazardous Decomposition Products:INCOMPLETE COMBUSTION MAY RELEASE  
TOXIC MATERIALS.

===== Disposal Considerations =====

Waste Disposal Methods:IN ACCORDANCE WITH STATE AND LOCAL REGULATIONS.

Disclaimer (provided with this information by the compiling agencies):  
This information is formulated for use by elements of the Department  
of Defense. The United States of America in no manner whatsoever,  
expressly or implied, warrants this information to be accurate and  
disclaims all liability for its use. Any person utilizing this  
document should seek competent professional advice to

verify and  
assume responsibility for the suitability of this information to their  
particular situation.