

AMERICAN DURABLE INC -- 6537585 -- 2530-00-653-7585

===== Product Identification =====

Product ID:6537585

MSDS Date:11/17/1992

FSC:2530

NIIN:00-653-7585

MSDS Number: BPJDR

==== Responsible Party ===

Company Name:AMERICAN DURABLE INC

Address:6080 CLAUDE WAY E

City:INVER GROVE HEIGHTS

State:MN

ZIP:55075

Country:US

Info Phone Num:612-455-6314

Emergency Phone Num:612-455-6314

Preparer's Name:HMIS TECHN

ICIAN

CAGE:7Z634

==== Contractor Identification ===

Company Name:AMERICAN DURABLE INC

Address:6080 CLAUDE WAY E

Box:City:INVER GROVE HEIGHTS

State:MN

ZIP:55075

Country:US

Phone:612-455-6314

CAGE:7Z634

===== Composition/Information on Ingredients =====

Ingred Name:ASBESTOS, CHRYSOTILE

CAS:12001-29-5

RTECS #:CI6478500

Other REC Limits:NONE RECOMMENDED

OSHA PEL:0.2 FIBERS/CC

ACGIH TLV:2 FIBERS/CC; A1;9293

===== Hazards Identification =====

Rout

es of Entry: Inhalation: YES Skin: NO Ingestion: NO

Reports of Carcinogenicity: NTP: YES IARC: YES OSHA: YES

Health Hazards Acute and Chronic: ACUTE: MINOR EYES/SKIN IRRITATION.

INGESTION- IRRITATION OF GI TRACT. INHALATION-IRRITATION OF RESPIRATORY TRACT. CHRONIC: ASBESTOSIS, LUNG CANCER, & MESOTHELIOMA, ALL OF WHICH ARE DISABLING AND FATAL DISEASES OF THE LUNG. INHALATION AND INGESTION OF ASBESTOS FIBERS MAY CAUSE CANCER OF THE BOWEL.

Explanation of Carcinogenicity: ASBESTOS IS

A KNOWN HUMAN CARCINOGEN.

Effects of Overexposure: INHALATION: FATIGUE AND SHORTNESS OF BREATH

THAT GETS WORSE WITH TIME AND EVENTUALLY BECOMES DISABLING. EYES:

IRRITATION. SKIN: IRRITATION. INGESTION: MILD STOMACH DISTRESS.

DIARRHEA, VOMITING, AND NAUSEA.

Medical Cond Aggravated by Exposure: ASTHMA, EMPHYSEMA, AND TUBERCULOSIS

ARE ALL GENERALLY AGGRAVATED BY EXPOSURE TO ASBESTOS FIBERS.

===== First Aid Measures =====

First Aid: INHALATION:

REMOVE TO FRESH AIR. SEE DOCTOR. EYES: RINSE

THOROUGHLY WITH WATER FOR 15 MINUTES. SEE DOCTOR. SKIN: WASH

THOROUGHLY WITH SOAP AND WATER. IF IRRITATION PERSISTS, SEE DOCTOR.

INGESTION: DILUTE WITH WATER. DO NOT INDUCE VOMITING. SEE DOCTOR.

===== Fire Fighting Measures =====

Flash Point: NOT REQUIRED

Extinguishing Media: USE WATER FOG, CARBON DIOXIDE, FOAM, OR DRY CHEMICAL.

Fire Fighting Procedures: WEAR FIRE FIGHTING PROTECTIVE EQUIPMENT AND A

FULL FACED SELF CONTAINED BREATHING APPARATUS.

Unusual Fire/Explosion Hazard: COMBUSTION OR HEAT OF FIRE MAY PRODUCE HAZARDOUS DECOMPOSITION PRODUCTS AND VAPORS.

===== Accidental Release Measures =====

Spill Release Procedures: VACUUM THE MATERIAL WITH A HEPA FILTERED VACUUM. THE EQUIPMENT SHALL BE USED & EMPTIED SO AS TO MINIMIZE THE RE-ENTRY OF ASBESTOS INTO THE WORKPLACE. OTHERWISE, WET THE MATERIAL WITH WATER & SURFACTANT AND THEN SHOVEL OR MOP

UP

CONTAMINATION.

===== Handling and Storage =====

Handling and Storage Precautions: PRODUCT IS NONFRIABLE & WILL NOT SHED FIBERS IN NORMAL USE AND STORAGE. USED PRODUCT SHALL BE WETTED BEFORE, DURING & AFTER DISASSEMBLY.

Other Precautions: USED PRODUCT SHALL BE IDENTIFIED AND DISPOSED OF IN ACCORDANCE WITH ALL LOCAL, STATE AND FEDERAL REGULATIONS.

===== Exposure Controls/Personal Protection =====

Respiratory Protection: WEAR

A NIOSH/MSHA APPROVED HEPA RESPIRATOR IF REQUIRED. WEAR SELF-CONTAINED BREATHING APPARATUS IF REQUIRED FOR HIGH LEVELS OF CONTAMINATES.

Ventilation: LOCAL EXHAUST SUFFICIENT TO ENTRAIN ALL PARTICULATE EMISSIONS. HEPA FILTER REQUIRED. NO LEAKS ON PRESSURE SIDE OF FAN.

Protective Gloves: COTTON OR LEATHER

Eye Protection: SAFETY GLASSES OR GOGGLES

Other Protective Equipment: USE COVERALLS OR DISPOSABLE CLOTHING.

Work Hygienic Practices: WET WORK TO THE DEGREE POSSIBLE. WASH HANDS AFTER HANDLING PRODUCT. LAUNDER CONTAMINATED CLOTHING BEFORE REUSE.

Supplemental Safety and Health

MSDS GENERATED BY HMIS TECHNICIAN.

===== Physical/Chemical Properties =====

HCC:T6

Solubility in Water: INSOLUBLE

Appearance and Odor: DRY, MOLDED, 14" DIAMETER BY 2" WIDTH

Percent Volatiles by Volume: 0

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid: YES

STRONG OXIDIZING AGENTS, STRONG MINERAL ACIDS, AND STRONG ALKALIS

Stability Condition to Avoid: ACCUMULATIONS OF DUST

Hazardous Decomposition Products: ASBESTOS DUST

===== Disposal Considerations =====

Waste Disposal Methods: WET THE MATERIAL WITH WATER AND SURFACTANT.

PLACE IN 6 MIL THICK POLYETHYLENE PLASTIC BAG. PLACE THESE BAGS INTO ANOTHER POLY BAG OR A SAFE PLACE UNTIL IT CAN BE SHIPPED TO AN APPROVED DISPOSAL SITE. IDENTIFY WITH ASBESTOS CANCER WARNING LABEL.

Disclaimer (provided with this information

by the compiling agencies):

This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.