View NSN Online: https://aerobasegroup.ae/nsn/2530-00-278-6505

STANCO INDUSTRIES INC -- WOVEN BRAKE LINING - 100 ALC -- 2530-00-278-6505

Product ID:WOVEN BRAKE LINING - 100 ALC MSDS Date:05/01/1986 FSC:2530 NIIN:00-278-6505 MSDS Number: BPMRN === Responsible Party === Company Name:STANCO INDUSTRIES INC Address:8220 MOSLEY ST Box:87 **City:HOUSTON** State:TX ZIP:77001 Country:US Info Phone Num:713-944-3160 **Emergency Phone Num:713** -944-3160 CAGE:LO101 === Contractor Identification === Company Name: STANCO INDUSTRIES INC Address:8220 MOSLEY ST Box:87 **City:HOUSTON** State:TX ZIP:77001 Country:US Phone:713-944-3160 CAGE:LO101 Company Name: STANDCO INDUSTRIES-STERLING Address:8220 MOSLEY ST Box:City:HOUSTON State:TX ZIP:77001 Country:US Phone:713-224-6311 CAGE:07756

Ingred Name:ASBESTOS, CHRYSOTILE CAS:12001-29-5 RTECS #:CI6478500 Fraction by Wt: 40% Other REC Limits:NONE RECOMMENDED OSHA PEL:0.2 FIBERS/CC ACGIH TLV:2 FIBERS/CC; A1;9293

Ingred Name:RAYON Other REC Limits:NONE RECOMMENDED

Ingred Name:BRASS WIRE Other REC Limits:NONE RECOMMENDED

Ingred Name:SOLIDIFIED TUNG Other REC Limits:NONE RECOMMENDED

Ingred Name:SOLIDIFIED LINSEED Other REC Limits:NONE RECOMMENDED

Routes of Entry: Inhalation:YES Skin:NO Ingestion:YES Reports of Carcinogenicity:NTP:YES IARC:YES OSHA: YES
Health Hazards Acute and Chronic:THERE IS NO HAZARD IN HANDLING THE FINISHED PRODUCT. IF ADDITIONAL SAWING, DRILLING OR MACHINING IS PERFORMED, ASBESTOS FIBERS CAN BE RELEASED.
Explanation of Carcinogenicity: ASBESTOS IS A KNOWN HUMAN CARCINOGEN.
Effects of Overexposure:SEE "MEDICAL CONDITIONS" BELOW. Medical Cond Aggravated by Exposure:OVEREXPOSURE TO FREE ASBESTOS CAN INCREASE THE CHRONIC RISK OF LUNG FIBROSIS, CANCER AND/OR MESOTHELIMO. TOBACCO SMOKING CAN INCREASE THE EXPO
SURE PROCESS.
======================================
First Aid:NONE.
======================================
Autoignition Temp: Autoignition Temp Text: 835F

Autoignition Temp:Autoignition Temp Text:835 Extinguishing Media:WATER Fire Fighting Procedures:NONE Unusual Fire/Explosion Hazard:NONE

Spill Release Procedures: DUST FROM MACHINING OPERATION SHOULD BE REMOVED USING OSHA APPROVED VACUUM.

\_\_\_\_\_

Handling and Storage Precautions:NORMAL CARE SHOULD BE USED TO PREVENT BREAKING OF FINISHED PARTS WHICH COULD RELEASE ASBESTOS FIBERS TO THE ATMOSPHERE. Other Precautions:NONE.

Other Precautions:NONE.

Spec Gr avity:1.4 Solubility in Water:NONE Appearance and Odor:TAN TO BROWN - VARNISH ODOR.

Stability Indicator/Materials to Avoid:YES NOT KNOWN Hazardous Decomposition Products:WHEN HEATED TO DECOMPOSITION - MAY EMIT TOXIC FUMES.

Waste Disposal Methods:DUST FROM MACHINING OPERATIONS SHOULD BE SEALED IN IMPERMEABLE BAGS OR CONTAINERS AND DISPOSED OF AS REQUI RED BY 29 CFR 1910.1001.

Disclaimer (provided with this information by the compiling agencies): This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this informatio n to their

particular situation.