

FEDERAL STANDARD CORP -- ACCUMULATOR ASSEMBLY,ORDNANCE # 7974982 --  
3040-00-508-0126

=====  
Product Identification  
=====

Product ID:ACCUMULATOR ASSEMBLY,ORDNANCE # 7974982

MSDS Date:03/06/1991

FSC:3040

NIIN:00-508-0126

MSDS Number: BPQTR

=== Responsible Party ===

Company Name:FEDERAL STANDARD CORP

Address:2600 E 25TH ST

City:MINNEAPOLIS

State:MN

ZIP:55406

Country:US

Info Phone Num:612-721-5063

Emer

gency Phone Num:612-721-5063

Preparer's Name:MARK WESTROM

CAGE:2R925

=== Contractor Identification ===

Company Name:FEDERAL STANDARD CORP

Address:2600 E 25TH ST

Box:City:MINNEAPOLIS

State:MN

ZIP:55406

Country:US

Phone:612-721-5063

CAGE:2R925

=====  
Composition/Information on Ingredients  
=====

Ingred Name:ALUMINUM ALLOYS:SERIES 2024 & 6061.MP:

900-1200F,482-649C.SPEC GRAV:2.5-2.9 (H\*2O=1).OSHA PEL 5 MG(AL)/M3  
RESP FRACTION.

Other REC Limits:NOT KNOWN

OSHA PEL:15 MG(AL)/

M3 T DUST  
ACGIH TLV:10 MG(AL)/M3 DUST

Ingred Name:ALUMINUM BASE METAL=AL. ALLOY ELEMENTS= COBALT, COPPER,  
IRON, LEAD, MAGNESIUM, MANGANESE, SILICON, TIN & ZINC  
Other REC Limits:NONE RECOMMENDED

Ingred Name:STAINLESS STEEL.MELTING POINT: 2700F,1482C.SPECIFIC  
GRAVITY: 8 (WATER=1).  
Other REC Limits:NOT KNOWN  
OSHA PEL:NOT KNOWN  
ACGIH TLV:NOT KNOWN

Ingred Name:STEEL BASE METAL=IRON. ALLOY ELEMENTS=  
C,AL,S,P,MN,CU,MO,SILICON,CHROMIUM,NICKEL,SELENIUM,COLUMBIUM,TANTAL  
UM,TITANIUM  
Oth  
er REC Limits:NONE RECOMMENDED

=====  
===== Hazards Identification =====

LD50 LC50 Mixture:NOT KNOWN  
Routes of Entry: Inhalation:YES Skin:NO Ingestion:NO  
Reports of Carcinogenicity:NTP:YES IARC:YES OSHA:YES  
Health Hazards Acute and Chronic:WELDING,BURNING,GRINDING,MACHINING  
RESULTING IN TEMP ABOVE MELTING POINT MAY GENERATE AIRBORNE  
PARTICULATE W/ METAL FUME FEVER.STEEL PRODUCTS IN NATURAL STATE DO  
NOT PRESENT INHAL/INGEST/CONTACT HEALT H HAZARDS.S  
TANDARD  
OPERATIONS W/ ALUMINUM PRESENT LOW HEALTH RISK BY INHAL & ARE  
CONSIDERED A NUISANCE DUST.  
Explanation of Carcinogenicity:CHROMIUM AND CR COMPOUNDS ARE LISTED IN  
IARC & NTP. NICKEL IS HUMAN CARC (ACGIH 1992-1993 LIST OF INTENDED  
CHANGES)  
Effects of Overexposure:EYES:FUMES/DUST OF STAINLESS STEEL MAY  
IRRITATE. INHALATION:EXCESS INHALATION OF METALLIC DUSTS OF  
STAINLESS STEEL MAY RESULT IN IRRITATION OF NOSE,THROAT.  
Medical Cond Aggravated by Exposure:DERMATITIS AND  
PULMONARY DISEASE OR  
DISORDERS. LEAD IS KNOWN TO CAUSE DEVELOPMENTAL AND REPRODUCTIVE  
TOXICITY (CALIFORNIA PROP. 65, 1987)

=====  
===== First Aid Measures =====

First Aid:EYES:IMMEDIATELY FLUSH WELL WITH RUNNING WATER FOR AT LEAST  
15 MINUTES TO REMOVE PARTICULATE.GET MEDICAL ATTENTION. SKIN:REMOVE  
CLOTHING & WASH SKIN THOROUGHLY WITH SOAP AND WATER.IF IRRITATION  
PERSIS TS,SEEK MEDICAL ATTENTION. INGESTION:IFSIGNIFICAN AMOUNT OF  
METAL IS I

INGESTED,SEEK MEDICAL ATTENTION. INHALATION:REMOVE TO FRESH AIR.IF CONDITION CONTINUES,CONSULT PHYSICIAN.

===== Fire Fighting Measures =====

Extinguishing Media:DRY POWDER OR SAND.DO NOT USE WATER OR HALOGEN ON DUST FIRES.

Fire Fighting Procedures:WEAR SELF CONTAINED BREATHING APPARATUS (SCBA) AND FULL TURNOUT GEAR .

Unusual Fire/Explosion Hazard:ACCUMULATOR ASSEMBLY CAN OPERATE AT VERY HIGH PRESS.IF AIR NOT PURGED FROM ACCUMULATOR DURING HO

OK-UP/HOOK-UP INCORRECT,RUPTURE/EXPLOSION IS POSSIBLE.(SEE SUPP)

===== Accidental Release Measures =====

Neutralizing Agent:NOT KNOWN

===== Handling and Storage =====

Handling and Storage Precautions:AVOID SERIOUS INJURY:PURGE ALL AIR BEFORE PRESS APPLIC DURING HOOKUP,DO NOT DISCONNECT UNTIL INTERNAL PRESS=0,IF LEAK OCCURS,IMMED SHUT DOWN (SEE SUP)

Other Precautions:KEEP AREA WELL VENTILATED.AVOID BREATHING METAL DUST

.ALUMINUM DOES NOT CHANGE COLOR DURING HEATING-USE CAUTION TO AVOID BURNS.STRESS RELIEVE ALUMINUM IGNOTS DURING SAWING TO PREVENT EXPLOSION.

===== Exposure Controls/Personal Protection =====

Respiratory Protection:IF EXPOSURE LIMITS ARE REACHED OR EXCEEDED USE NIOSH APPROVED RESPIRATOR.

Ventilation:KEEP AREA WELL VENTILATED.

Protective Gloves:YES

Eye Protection:CHEM SFTY GOGG .FSHLD AS APPROP.

Other Protective Equipment:APPROPRIATE PROTECTIVE CLOTHING AS NEEDED.

W

ork Hygienic Practices:USE GOOD HOUSEKEEPING PRACTICES TO PREVENT ACCUMULATION OF DUST AND TO KEEP AIRBORNE DUST TO A MINIMUM.

Supplemental Safety and Health

FIRE/EXPLO HAZ:ALUMINUM CHIPS/DUST MAY IGNITE/EXPLODE READILY.MATLS TO AVOID:VIOLENT EXPLO.MOLTEN AL MAY EXPLODE ON CONTACT WITH WATER/CERTAIN METAL OXIDES.HNDLG/STOR PREC:SYSTEM.BEFORE STORING RELEAS E ALL PRESS ON GAS SIDE.POINT HIGH PRESS VALVE (GAS) END AWAY FROM ALL PERSONNEL WHEN DEPRESSURIZING USING VALVE CORE.

=

===== Physical/Chemical Properties =====

Melt/Freeze Pt:M.P/F.P Text:SEE ING 1,2  
Decomp Temp:Decomp Text:NOT KNOWN  
Vapor Density:NOT KNOWN  
Spec Gravity:SEE ING 1,2  
Evaporation Rate & Reference:NOT KNOWN  
Solubility in Water:INSOLUBLE  
Appearance and Odor:SOLID WITH METALLIC APPEARANCE AND NO ODOR.

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES  
STRONG ACIDS.AL REACTS W/ HALOGEN ACIDS,NAOH,BROMATES,IODATES,AMMONIUM  
NITRATE,STRONG OXIDIZERS W/ POSSIBLE (SEE SUPP)  
Stability Condition to Avoid:DAMP ALUMINUM DUST MAY HEAT SPONTANEOUSLY  
RELEASING HYDROGEN TO FORM EXPLOSIVE AIR MIXTURES.  
Hazardous Decomposition Products:STAINLESS STEEL:METALLIC  
OXIDES.ALUMINUM:WELDING MAY GENERATE CO,CO\*2,OZONE,NITROGEN  
OXIDES,INFRARED/ULTRAVIOLET RADIA.

===== Disposal Considerations =====

Waste Disposal Methods:DISPOSAL MUST BE IAW FED,STATE,& LOCAL  
REGS.COORDINATE W/ SUPPORTING INSTALLATION/MACOM ENVIRONMENTAL  
OFFICE PRIOR TO DISP .STAINLESS STEEL:TREAT AS A DUST.ALUMINUM:TEST  
USED/UNUSED PRODUCT TO DETERMINE HAZARD STATUS & DISPOSAL  
REQUIREMENTS.

Disclaimer (provided with this information by the compiling agencies):  
This information is formulated for use by elements of the Department  
of Defense. The United States of America in no manner whatsoever,  
expressly or implied, warrants this information to be accurate and  
disclaims all liability for its use. Any person utilizing this  
document should seek competent professional advice to verify and  
assume responsibility for the suitability of this information to their  
particular situation.